

Little Giant Manufacturing Company, In

High Pressure Hotomatic Gas Water Heater

Hotomatic Heaters are manufactured in the square shape only.

Types	Hotomatic® No. 2HSQ	Hotomatic® No. 2HTSQ	Hotomatic® No. 3HSQ	Hotomatic® No. 3HTSQ	Hotomatic® 3HT High Pressure	Hotomatic® No. 4HTSQ
Gallons Per Hr. Recovery	90 (60°R) 45 (120°R)	90 (60°R) 45 (120°R)	150 (60°R) 75 (120°R)	150 (60°R) 75 (120°R)	150 (60°R) 75 (120°R)	225 (60°R) 112.5 (120°R)
Gallons Per Minute	1.5 (60°R) .75 (120°R)	1.5 (60°R) .75 (120°R)	2.5 (60°R) 1.25 (120°R)	2.5 (60°R) 1.25 (120°R)	2.5 (60°R) 1.25 (120°R)	3.75 (60°R) 1.87 (120°R)
BTU Input (Approx.)	65,000	65,000	120,000	120,000	120,000	180,000
Vent size	4"	4"	4"	4"	4"	6"
Height (Not Including diverter)	221/2"	221/2"	30"	30"	30"	32"
Square	1111/4"	111/4"	133/4"	133/4"	133/4"	173/4"
Weight (Crated)	47 lbs.	47 lbs.	79 lbs.	79 lbs.	79 lbs.	120 lbs.
Gas Line Size Up To 15' Long	½" I.D.	½" I.D.	½" I.D.	½" I.D.	½" I.D.	5⁄8" I.D.
Water Connections (Standard Pipe Size)	³ ⁄4" F	Cold – 1/4" M Hot 3/4" F	3∕4" F	Cold – 1/4" M Hot 3/4" F	Cold – 1/4" M Hot 3/4" F	Cold – 1/4" M Hot 3/4" F
Square Heater List Prices	\$1080.00	\$1140.00	\$1390.00	\$1450.00	\$1570.00	\$1850.00
Coil List Prices	\$575.00 18 G	\$600.00 18 G	\$690.00 18 G	\$749.00 18 G	\$1075.00 18 G	\$1200.00 18 G

*High Test Heaters (1300 PSI) add \$225.00

*Regular Heaters = 600 PSI

Spark Ignitor Model V-1\$49.00	Relief Valve Model #7413 – 600 psi		
Gas Pressure Regulator – Model #204 – 00\$49.00 140,000 BTU/Hr — For No. 1, No. 2, No. 3 Hotomatic® Heater	Gas Pressure Regulator – Model # LV4403C9\$130 575,000 BTU/Hr — For No. 4 Hotomatic® Heater Special POL Plug\$12		

IMPORTANT NOTE: It is extremely necessary that the Gas Pressure Regulator used to supply the heater with LP Gas has a capacity rating higher than the consumption of the heater. Too small a regulator will decrease the gas flow, the gas pressure and the amount of hot water produced. The Model #204 – 00 Regulator is rated at 140,000 BTU/Hr., which is sufficiently sized to supply the gas for Models #1, #2 or #3 Hotomatic® heaters. The Model LV4403C9 Regulator is rated at 575,000 BTU/Hr., which is the model we recommend for the #4 HT Hotomatic.

A gas supply hose that is too small will reduce the flow rate of the LP Gas. This reduces the gas pressure at the burner and the amount of hot water produced. Use a $\frac{1}{2}$ " I.D. Hose minimum for the #1, #2 or #3 HT Hotomatic heaters. Use a $\frac{3}{4}$ " I.D. Hose for the #4 HT Hotomatic heater.

We Have Been Making Water Heaters Since 1904. This long tradition of efficient performance is the result of rigid control of manufacturing details and the use of the finest materials and craftsmanship available. Little Giant Water Heaters have proven to be dependable under the true test of constant daily use. They will provide long, care free service and the maximum is satisfaction.

For further information on any of the products illustrated or water heaters for other applications, write or call your local dealer.

Distributed By:

All prices FOB Orange, Texas. Prices may change without notice.