

## INDUSTRIES WE SERVE



WATER DAMAGE



FIRE & SMOKE DAMAGE



MOLD REMOVAL



## PRODUCT SPECIFICATIONS

MODEL NO.	X-41ATR	X-42ATR (Hi-Temp)	X-34AR	X-34TR
VOLTS / CYCLE	115 Volts / 60 Hertz	115 Volts / 60 Hertz	115 Volts / 60 Hertz	115 Volts / 60 Hertz
MOTOR/RATED AIRFLOW	1/3 HP – 3,600 CFM	1/3 HP – 3,600 CFM	¼ HP – 1,720 CFM	¼ HP – 1,720 CFM
POWER	2.4 Amps (On Highest Speed)	2.4 Amps (On Highest Speed)	1.6 Amps (On Highest Speed)	1.6 Amps (On Highest Speed)
SPEED	Variable Speed Control	Variable Speed Control	Variable Speed Control	Variable Speed Control
RPM (LOW – HIGH)	400 – 1,600 RPM	400 – 1,600 RPM	800 – 1,700 RPM	800 – 1,700 RPM
UNIT / BOX WEIGHT	24.8 lbs. / 30.5 lbs.	25.2 lbs. / 31.2 lbs.	16.1 lbs. / 20.2 lbs.	15.3 lbs. / 19.4 lbs.
UNIT / BOX DIMENSIONS (L x W x H)	21.9" x 9.8" x 22.5" / 22.6" x 23.2" x 11.4"	21.9" x 9.8" x 22.5" / 22.6" x 23.2" x 11.4"	18.6" x 9.4" x 19.2" / 19.7" x 17.7" x 10"	18.6" x 9.4" x 19.2" / 19.7" x 17.7" x 10"
CORD LENGTH / GAUGE	20' / 14AWG	20' / 14AWG	20' / 14AWG	10' / 18AWG
HOUSING MATERIAL	Injection Mold ABS Plastic	Injection Mold ABS + PC (Polycarbonate) Plastic	Injection Mold ABS Plastic	Injection Mold ABS Plastic
OPERATING POSITIONS	360° Rotation (12.5" Height Rack Included)	360° Rotation (12.5" Height Rack Included)	360° Rotation (10" Height Rack Included)	360° Rotation (10" Height Rack Included)
BUILT-IN DAISY CHAIN	Yes	Yes	Yes	No
3-HOUR TIMER	Yes	Yes	No	Yes
STACKABLE	Yes – Up to 5 Units High (Recommended)	Yes – Up to 5 Units High (Recommended)	Yes – Up to 5 Units High (Recommended)	Yes – Up to 5 Units High (Recommended)
SAFETY CERTIFICATIONS	ETL/CETL (Equivalent to UL/CUL/CSA/NOM)	ETL/CETL (Equivalent to UL/CUL/CSA/NOM)	ETL/CETL (Equivalent to UL/CUL/CSA/NOM)	ETL/CETL (Equivalent to UL/CUL/CSA/NOM)

## ACCESSORIES

DUCTING HOSE (Sold Separately)	<b>16DH25 / 16DH15</b> – Yellow Polyester Duct Hose Available in 25' & 15' x 16" Ø Inside Diameter	N/A	N/A
ADAPTER KIT (Sold Separately)	<b>16DHK</b> – Adapter Kit that Connects Ducting Hose to Axial Fan	N/A	N/A

## PRODUCT FEATURES

**Auxiliary Outlet with Circuit Breaker for Daisy Chain**



**3-Hour Timer & Variable Speed Control Switch**





**External Rotor Induction Motor for Larger Torque That Produces High Efficient, Powerful & Quiet Airflow**

**Specially Designed Air Fin Guide for More Focused & Extended Airflow Range Up to 60 ft.**

**Stand-Alone Design with Rubber Footing that Works Even Without the Rack**

**Durable & Rugged ABS (X-41ATR) + PC (X-42ATR) Plastic Housing Design**

**Quick Release Knob for Easy Angle Adjustment**

**Wrap Around Cord Design**

**Rack / Stand Fully Installed Allowing 360° Angle Rotation**