


**A WIDE RANGE OF  
HIGH CAPACITY,  
LOW TEMPERATURE  
DEHUMIDIFIERS  
FOR INDUSTRY,  
INSTITUTION,  
RENTALS  
AND HOMES.**



## **SD120/SD200 SWIMMING POOL AND INDUSTRIAL DEHUMIDIFIERS**

Ebac's dehumidifiers clear the air in damp interior spaces. Condensation is removed from windows, walls and ceilings. Stuffy air is drawn off and dry air is pumped back in. You simply set the dial and air humidity remains at the desired level. In addition, Ebac dehumidifiers are energy savers.

**You should enjoy your indoor area, swimming pool, and/or spa...  
*Ebac dehumidifiers make sure you do.***

#### **Applications:**


- A. Swimming Pools: Residential, Institutional or Therapeutic
- B. Spas and Whirlpools.
- C. Health and Fitness Centers: Aerobic rooms, Racquetball and Handball Courts, Workout Areas, Locker and Laundry Rooms.
- D. Any small to medium sized enclosure with excessive moisture/humidity.

#### **Features:**

- 1) Quiet, 2 speed fan.
- 2) Self-contained for quick and easy installation - no duct work required.
- 3) Can be ducted, if desired.
- 4) Remote Humidstat can be mounted anywhere to automatically maintain desired humidity level.
- 5) Built-in, easily removable washable air filter.

#### **Operation:**

The effective answer to excessive humidity is a refrigeration-type dehumidifier. Warm moist air is drawn by a fan across a cold coil which causes the water vapor to condense onto the coil and drop into a container or tray. The cold air is then passed over a heat exchanger where it is warmed before being passed back into the surrounding area. A dehumidifier that has a humidistat which automatically switches it on and off saves energy and expense by maintaining the desired level of humidity with intermittent operation.



  
**Ebac Industrial Products, Inc.**

700 Thimble Shoals Blvd., Suite 109  
Newport News, VA 23606-2575  
E-Mail: Sales@EbacUSA.com

Telephone: (757) 873-6800  
Fax: (757) 873-3632  
Toll Free: 1-800-433-9011

## TECHNICAL DATA

### EBAC SD120, SD200 DEHUMIDIFIERS

TECHNICAL DATA:	SD120	SD200
POWER SUPPLY	115V 60HZ SINGLE PHASE	208/230V 60HZ SINGLE PHASE
AMPS	6.0	11.8
COMPRESSOR	1 HP ROTARY	2 HP RECIPROCATING
REFRIGERANT	R-22	R-22
FAN	2-SPEED CENTRIFUGAL	2-SPEED CENTRIFUGAL
CFM   LOW	560	560
HIGH	722	833
WATER REMOVAL (PINTS PER DAY)		
86° F, 65% RH	137	231
86° F, 75% RH	185	286
HEAT RECOVERY (BTUH)	9,390	15,500
OPERATING RANGE	41 – 95° F	41 – 95° F
HEIGHT	18"	18"
WIDTH	26"	26"
DEPTH	27"	27"
WEIGHT	152 lbs.	174 lbs.
COLOR	LIGHT BEIGE w/ BLACK FRONT	LIGHT BEIGE w/ BLACK FRONT

• Specifications are subject to change without notice •