

# Phoenix Axial Air Mover

with FOCUS™ Technology

The Phoenix Axial Air Mover revolutionized evaporative drying by producing airflow velocities of 3000 CFM, while using less than 2.5 amps of electricity. The Phoenix Axial Air Mover is the industry's only air mover specifically engineered with patent pending Focus™ Technology. Focus™ Technology not only produces air velocities greater than competitive products, but also focuses those velocities on hard-to-dry areas such as carpet and pad, sub-floor and walls.

The Phoenix Axial Air Mover operator interface is conveniently located for easy access and features a power indicator lamp, a 3-position switch, an hour meter, a GFCI outlet, and a circuit breaker, eliminating nuisance trips to the breaker box.

## Performance

- Greater air velocities than competitive products
- Focused velocities 0 to over 23.5 feet
- Directs air flow towards problematic corners, where the wall meets the floor
- Capable of reducing secondary damage claims stemming from the side-effects of trapped humidity like fungi, mold, mildew or structural damage
- 3000 CFM
- Long-life 2-speed motor
- Low noise, quiet operation

## Construction

- Lightweight and compact Linear Low Density Polyethylene (LLDP) housing is washable, chemical resistant and stacks for storage
- Colored Restoration Red for high visibility
- Ergonomic handle


The **Only Choice** for  
Restoration Professionals



## Features

- Less than 2.5 amps
- Power-on indicator light
- Automatic hour meter displays site run time
- On-board power management:
  - Circuit breaker protects air mover and attached devices and prevents nuisance visits to the junction box
  - GFCI protection promotes operator safety in wet applications
  - Duplex AC outlet allows daisy chaining of up to four axial air movers
- 20 ft AC cord with cord management
- Units interlock for ease of stacking during storage and handling
- Weighs 2.5 lbs less than competitive units

with **FOCUS™**  
TECHNOLOGY



**PHOENIX™**  
RESTORATION EQUIPMENT

# Phoenix Axial Air Mover



## Phoenix Axial Air Mover Specifications

- Part No.** 4025200
- Drive Motor** 1/4 hp 1-phase 110/120 VAC 2-speed 4-pole, PSC Electric Motor.
- CFM** Approximately 3000
- Cord** 20 ft Power Cord
- Outlet** 15A UL Rated GFCI Duplex Receptacle
- Current Draw** 2.5 Amps
- Voltage** 115 VAC
- Warranty**
  - Year One - 100% parts and labor (all components)
  - Year Two - 100% parts only (all components)
  - Year(s) Three through Seven - Only materials and workmanship of the housing are covered.



Innovative control panel includes power-on light, run-time hour meter, GFCI outlet and more.

## Dimensions

	Machine	Shipping
Width	19.125"	19.375"
Height	19.5"	20"
Depth	15.2" (intake to exhaust)	15.5"
Weight	29.5 lbs	32.7 lbs

## Popular Accessories And Replacement Parts

- 4025092 Motor
- 4025095 Blade
- 4021597 Hour Meter



Low Amp Draw - 2.5 Amps



Available stand\* provides a 360° range of motion, ideal for drying hard to reach areas.

\*Stand ordered separately



Units interlock for ease of stacking during storage and handling.