



Model Number: 8000-712-288

Shurflo 8000-712-288, 100psi 115 volt, 1.3GPM With Pressure Switch

Manufacturer: Shurflo

PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump

CAM: 2.5 Degree

CHECK VALVE: (2-Way Op.) Prevents Reverse Flow & 6 Ft. Head Forward Flow

MOTOR: Permanent Magnet, P/N 11-150-10, Thermally Protected

VOLTAGE: 115 VAC Nominal

PRESSURE SWITCH: Adjustable Shut-Off (Range 80-100 PSI), Factory Set @ 100 PSI, Turn On 85 PSI +/- 5 PSI

BYPASS: 80 PSI

LIQUID TEMPERATURE: 180 Degrees Fahrenheit (82 Degrees Centigrade) Max.

PRIME: Self-Priming Up To 7 Ft. Vertical,

Max. Inlet Pressure 30 PSI (2.1 Bar)

PORTS: 3/8"-18 NPT Female

MATERIAL OF CONSTRUCTION:

PLASTICS- Nylon

VALVES- Viton

DIAPHRAGM- Viton (Switch), Santoprene (Main)

FASTENERS- Zinc Plated Steel

NET WEIGHT: 4.9 Lbs (2.2 Kg)

DUTY CYCLE: Intermittent

TYPICAL APPLICATIONS: Soil Extraction and carpet cleaning pump

- UL/CSA Recognized Component

Net size: 8.25" L X 4" W X 4.125" H

ShurFlo 115VAC 1.3 GPM Transfer Diaphragm Pump

ShurFlo 8000-712-288 Industrial Transfer Diaphragm Pump

115 Volt AC, 1.3 GPM open flow, 100 PSI Demand switch, Internal bypass at 80 psi, Viton valves, Santoprene diaphragm. 3/8" NPT Poly (Female) Ports

- PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump
- CAM: 3.0 Degree
- CHECK VALVE: (2-Way Op.) Prevents Reverse Flow & 6 Ft. Head Forward Flow
- MOTOR: Permanent Magnet, P/N 11-150-00, Thermally Protected
- VOLTAGE: 115 VAC Nominal
- PRESSURE SWITCH: Adjustable Shut-Off (Range 100-80 PSI), Factory Set @ 100 PSI, Turn On 80 PSI +/- 5 PSI
- LIQUID TEMPERATURE: 170 Degrees Fahrenheit (77 Degrees Centigrade) Max.
- PRIME: Self-Priming Up To 8 Ft. Vertical,
 - Max. Inlet Pressure 30 PSI (2.1 Bar)
- PORTS: 3/8"-18 NPT Female

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

- MATERIAL OF CONSTRUCTION:
- PLASTICS- Polypropylene
- VALVES- Viton
- DIAPHRAGM- Santoprene
- FASTENERS- Zinc Plated Steel
- NET WEIGHT: 3.8 Lbs (1.72 Kg)
- DUTY CYCLE: Intermittent
- TYPICAL APPLICATIONS: Soil Extraction
- Also marketed under part number(s): SU8000-712-288

International shipping?

You can ship either one or two of these pumps for the same \$80 by the US Post Master to almost every country in the world.

- Model: 8000-712-288
- Shipping Weight: 4lbs
- Manufactured by: SHURflo

<http://www.gekko-inc.com/store/shurflo/377666-shurflo-8000-712-288.html>
also watch out for hesco

--> 20151021djc

Availability: This product was added to our catalog on Tuesday 14 February, 2012