

>



Model Number: RPV50E1

Hydrotek RPV50E1 Water Evacuation and Pump out Unit 115 volt 20 amp 50gpm - Build to order,
6 MONTH BACKORDER

Manufacturer: Hydrotek

Hydrotek RPV50E1 Water Evacuation and Pump out Unit 115 volt 20 amp 50 gpm
This item is currently UNAVAILABLE with an ETA ship date of SEPTEMBER 2026!

Performs water extraction work, dirt filtration and auto pump out.
Use with water extraction work or pressure washing recovery.
Please use a 5000 watt generator if not plugging into a wall outlet.

The RPV Hydro Vacuum is a water capture and transfer system. It transfers the water while vacuuming, eliminating the inefficient task of having to continually dump your collection tank. The new RPV is ideal for flood and fire restoration contractors because of the large volume of water that can be removed. It is also useful for anyone wanting to eliminate water runoff at a job site or a pressure washer contractor collecting wastewater. In addition, the RPV is able to discharge vertically. (Requires 2" diameter vacuum hose, 2" diameter discharge hose recommended) A building service contractor or auto detailer will like the additional feature to turn the RPV into a high powered shop/detail vacuum just by adding the optional dry work filter.

NOTE: These two new RPV models replace the RPT5E1, RPVACE1, RPVRE1, and RZF5E1 which will be discontinued.

HOME DELIVERY AND LIFT GATE FEE NOT INCLUDED IN SHIPPING RATE

Capture & Transfer Up To 3000 Gallons Of Water Per Hour With Hydro Vacuum.
Water & Flood

Recovery Vacuum Systems. They Feature A
Powerful. Industrial 2-Stage Vacuum Motor, & A
Heavy Duty Stainless Steel Pump Transfers
Waste water While Vacuuming Continues

No Need To Stop & Dump The Collection Tank

They Are Ideal For Interior & Exterior Facilities
Maintenance Contractors Needing To Collect Wash Water, Or Restoration
Contractors Needing

To Pick Up Large Volumes Of Water After A Fire
Or Flood. Increase Your Efficiency With Optional
Vacuum Tools Such As A Carpet Wand Or
Vacuum Scupper.

(For Use With Cold Water Or Hot Water Up To
200 Degree F.) Consistent Air Introduction At
The Pickup Is Needed To Prevent Hydraulicing)
Requires: 2" Vacuum Hose, 2" Discharge Hose
Recommended.

Dimensions Are: 17"W X 38"H

65 LBS

>

35 ft power cord
Max hose length during use: 100 ft with scupper, 25 ft with surface tools with air recovery.

Schamatics
Parts List
Press Release

Spec Sheet

We compare the top flood extraction units on the market to see how they compare.
Click Here is the list of features to look for.
Options:

Winco Generators
TB6000C

Winco Generators: TB6000C---Two-Bearing-Generator-Single Phase,
120/240 Volts, 50/25 Amps, 12HP, 3600 RPM

VB20

Vacu-Boom Spill Containment free shipping

Mosmatic Pressure Washing Equip
78.285

Mosmatic: 8" Tile and Grout Hand Held Spinner Wand With Brush Lip 5000
psi swivel 78.285 FL-ABB 200 - 8"

Mosmatic Pressure Washing Equip
78.292

>

Mosmatic: 12" Tile and Grout Spinner Wand FL-AER 300 With Vacuum Air
Recovery Pick up 4000 psi 78.292 (Discount shipping)

Clean Storm
AH30

Hose: Vacuum Hose - 50ft x 2.0in - Double Lined DHV50 DHV02

Hydrotek
ATP75

Hydrotek ATP75 Vacuum Scupper Head 12" Wide Stainless Steel 2"
Connection

Availability: This product was added to our catalog on Thursday 25 July, 2013