

>



Model Number: 4PPX30GSI

Cat 4PPX30GSI, Pump 2.7gpm 3000psi 3450 rpm, Direct Engine Connection

Manufacturer: Cat Pumps

Cat 4PPX30GSI Pump 2.7gpm 3000psi 3450 rpm Direct Engine Connection

MODEL 4PPX30GSI

Flow2.7 gpm (10.2 lpm)
Maximum Discharge Pressure3000 psi (310 bar)
Maximum RPM3450 rpm (3450 rpm)
Stroke0.280" (7.2 mm)

COMMON PUMP SPECIFICATIONS

Inlet Pressure Range.....Flooded to 60 psi (Flooded to 4 bar)
Bore0.551" (14 mm)
Crankcase Capacity8.5 oz. (0.25 l)
Maximum Liquid Temperature140°F (60°C)
Above 130°F call CAT PUMPS for inlet conditions and elastomer recommendations.
Inlet Ports (1)3/8" NPTF (3/8" NPTF)
Accessory Port (1) (Inlet)1/4" NPTF (1/4" NPTF)
Discharge Port w/Chemical Injector (1)3/8" NPTM (3/8" NPTM)
Chemical Injection Hose Barb1/4" (1/4")
Shaft Diameter (Hollow)3/4" (19.0 mm)
Weight10.7 lbs. (4.9 kg)
Dimensions8.03 x 7.83 x 6.61" (204 x 199 x 168 mm)

Owner Manual

FEATURES

- I Triplex plunger design provides a smooth liquid flow.
- I Specially formulated high pressure seals and concentric solid ceramic plungers assure true wear surface and extended seal life.
- I Stacked valve design for ease in servicing.
- I Ultra-compact, hollow-shafted pump for direct mounting to gas engine.
- I Integral Pressure Unloader with built-in by-pass standard on all units to assure system pressure control and pump protection.
- I Fixed chemical injector standard on all units offers cleaning flexibility.

Sales Tax Collected in CA and TX

>

Availability: This product was added to our catalog on Wednesday 30 April, 2014

Steambrite Supply