

>



Model Number: TW-521

Clean Storm TW-521 Car Detail and Carpet Cleaning Machine 5 Gallon Extractor Dual 2 Stage Vac 100psi Heater

Manufacturer: Clean Storm

FEATURES:

- **POLISHED FIBERGLASS TANK** - 5gal (19 Liters) Solution and recovery tank capacities. White tank and motor housing interior. Stainless steel rear handle facilitates ease of machine movement and serves as a cord wrap.
- **VACUUM** - Lam Electric 5.7" 2 stage tangential discharge models. Dual vacuum models can be ordered in air series (150" lift) or air parallel (200 cfm). Vacuum motor is protected from overflow with a positive ball float shutoff and from lint with the stainless steel screen. A removable lint bag is available for the intake elbow.
- **SOLUTION PUMP** - 60 or 100 psi Shurflo diaphragm pump with viton seals.
- **SWITCHES** - double pole single throw green lighted rocker switches with clear PVC splash proof caps, 20 amp rated @ 125 vac 16 amp rated @ 250vac.
- **WHEELS** - (2) front non-marking grey swivel type casters, and 6" non-marking PVC tread rear wheels.
- **CLEAR DOME** - high impact resistant plastic. Dome pivots on a slotted bracket to provide a perfect seal and compensates for gasket wear.
- **POWER CORD** - 12/3 X 25ft. SJTW safety yellow with molded 3 prong plug for (120 volt models). Or 25ft. (7.6 m) of 3 x 1.5 mm harmonized cord (16 amp/300v) for 240 volt models (please specify when ordering). Dual cord units are built with a circuit locator.(heated units are dual corded) Each cord requires a min. 15 amp circuit on 120 volt models and a 13 amp on 140 models.
- **HOSE ASSEMBLY** - 15ft. of 1-1/2" PVC crushproof vacuum hose and 3/8" solution hose with brass quick disconnects on ends. Heated models are supplied with a 1/4" hi-temp, hi pressure solution hose. Wand not included--
- **SERVICABILITY** - Tank is hinged on the back of the motor housing. Release (2) front latches and swing tank upwards to expose motor compartment. Tank is held in place from falling backwards by a landyard.
- **DIMENSIONS** - L: 24.5" (62cm) - W: 16" (41mm) - H: 27" (69mm)
- **HEATER** - 1000 and 1850 watt heating elements available. Heating elements are protected by (2) automatic thermal protectors set at 200 deg F (94 deg C) and a preset bypass valve releases hi-temperature solution back into the solution tank.
- **WEIGHT** - 54 lbs. (25kg) minimum with cord on the basic model.

20120825sdw

>

Availability: This product was added to our catalog on Tuesday 30 January, 2007

Steambrite Supply