

>



Model Number: VFA-42

Dwyer 26-003 Visiflow meter without knob [VFA-42] A019 86181170 86181180 000-074-030  
121725 1675-2216

Manufacturer: Dwyer Instruments

Dwyer Instrimnts VisiFlow VFA-42-BV

is used on many brands of industrial carpet cleaning truckmounts including Prochem, Hydramaster, Butler, White Magic, Power Clean, Ace, Mini Truckmounts, SteamBrite and more.... (styles that use last step chemical injection)

Compare to current or past OEM associations:

Dwyer VFA-42  
HydroForce PP18-808513  
Prochem 18-808513  
Prochem 86181170  
Sapphire Scientific 26-003  
8.618-118.0  
86181180  
Century 400 190-01A  
Karcher 8.618-117.0  
12311A  
Shark 8.710-101.0  
343728  
White Magic A019  
Hydramaster 000-074-030  
121725  
1675-2216  
26-003  
Legend Brands 104767

Pick up at Steam Brite & save 1/2 the shipping charge

The Visi-Float flowmeter bodies are cut and precision machined from solid, clear acrylic plastic blocks. This construction not only produces a handsome finished product, but permits complete visual inspection. As a result, the Visi-Float flowmeters are especially popular for medical and laboratory equipment applications.

Scales are easy to read - The front scale location and white background provides excellent visibility. The direct reading scales are hot stamped into the plastic and will not wear off. Mid-range calibration is established with a master flowmeter. Accuracy is  $\pm 5\%$  of full scale for VFA models,  $\pm 3\%$  for VFB. Scales average 2" long on the VFA models, 4" long on VFB. This model will show readings between 1.4 to 10 gallons per hour flow. The flow rating is only displayed while the cleaning operators is using water.

Durable and attractive construction - The machined acrylic bodies of the Visi-Float flowmeters are practically unbreakable. Fabrication is backed by over

>

60 years of experience in acrylic instrument machining. The tapered bore is precision machined to a smooth surface that provides perfect visibility of the indicating float. The VFA and VFB models are available with either brass or stainless steel inlet and outlet connections and are tapped for 1/8" NPT thread. All standard models employ Buna-N o-rings for leak proof operation and are available with either back or end connections for horizontal or vertical piping. Precision metering valves in brass or stainless steel are available for most VFA and VFB models.  
Easy installation - All Visi&ndash;Float&reg; flowmeters have metal mounting inserts on rear for panel mounting. They can also be supported directly by system piping.

Optional

Factory Installed on:  
.Steambrite 22 Hp TruckMount Predator Engine Tuthill 3006 (36) Blower  
Stainless Carpet Cleaning Machine Only w/ Freshwater Tank TM2236

---

*Availability: This product was added to our catalog on Sunday 08 March, 2009*