Model Number: C-LWC55

Chemspec ProRestore Unsmoke C-LWC55 Wall Wash with Biosolv 55 Gallon Drum Freight Included

Manufacturer: Chemspec

ProRestore C-LWC55 Unsmoke Wall Wash with Biosolv 55 gallons
Cleans smoke damaged hard surfaces
Wall Wash is formulated with proprietary brightening and deodorizing agents for cleaning smoke-damaged hard surfaces. This product is especially effective for prepping walls for painting – it quickly removes and both oily and dry soot, and does not require rinsing when used as directed. Especially effective for cleaning up after grease fires. A truly multi-use product, Wall Wash can also be used as a powerful degreaser for parts washing and can be added to any cleaning agent or paint to boost odor control.

Use Instructions
As a wall cleaner:
1. Remove excess smoke and soot using a lamb’s wool duster or HEPA filter vacuum.
2. After testing the contamination level and surface durability, add 4 oz. and up to 32 oz. (125 to 1000 mL) to each gallon (3.8 L) of water depending on the severity of the job.
3. Apply diluted Wall Wash with a wall cleaning machine, or spray on, and wipe down.

4. Rinsing with water is recommended if used at higher concentrations, or if used to clean high-touch surfaces.

As a booster:
1. Mix 8 ounces (250 ML) of Wall Wash per gallon (3.8 L) to any ordinary cleaning solution for use on walls, floor or other hard surfaces.
2. Rinsing with water is recommended if used at higher concentrations, or if used to clean high-touch surfaces.

Wall Wash SDS (6-23-2015)
Wall Wash GHS Label (1 gal.)
Wall Wash GHS Label (5 gal.)
Wall Wash GHS Label (55 gal.)
Wall Wash GHS Label 5 gal. (151027)
Wall Wash GHS Label 55 gal. (151027)

Availability: This product was added to our catalog on Friday 05 February, 2016

Steambrite Supply