

>



Model Number: 80409

PumpTec 80409 HTU-231-1/2HP Hydrostatic Test Unit 1/2 HP 120 Volt 500psi

Manufacturer: Pumptec

Hydrostatic Test pump, Series 356 pump, continuous-Duty Open Drip Proof 1/2 HP motor, 35' cord with GFCI, Adjustable pressure unloader valve, liquid filled pressure gauge, quick connect garden hose inlet, quick connect 3/8 outlet, heavy duty non-conductive mounting rails and grommets. Use to top off glycol systems.

Features:

- Heavy Duty Handle -- Epoxy-coded with grip
- On-Off Switch -- protected from moisture and physical damage
- Continuous-Duty -- Totally enclosed fan cooled 3/4 HP motor
- Quick Connect -- garden hose connects in a "snap"
- 35' Cord -- SJTW weather resistant UL
- Pressure Gauge -- 0-600 PSI liquid filled Industrial grade
- Adjustable Pressure -- 0-500 PSI with by-pass unloader valve
- Quick connect -- 3/8 NPT(F) outlet easily to test components
- Non-conductive mounting rails -- rust proof with heavy duty pads. Keeps unit high and dry when used outdoors
- Safe GFCI protection -- Electricity to unit is automatically shut-off if any short occur

PumpTec: AS1200 Water Otter 1200 psi Pressure washer pump and tile and carpet cleaning pump

>

OPTIONAL

Faucet Adapter 13/16s to Garden Hose Connection

OPTIONAL

Clean Storm Auto Fill Hose 6 ft By 1/2 Inch ID with 90 degree Fitting
for Hot water Garden Hose

Optional

Shower Head Hot Water Hook Up Kit SBM1834

>

Optional

Clean Storm Automatic Fill Kit for Carpet and Tile Cleaning Machines

- * Commercial Duty
 - * American-Made Pump and Motor
 - * 1,200 psi, 2.2 GPM at Nozzle Tip (turn down pressure if you like to as low as 200 psi)
 - * 14.3 Amp High Efficiency Motor
 - * Maintenance-Free 1,200 psi Pump
 - * 1,000 Hour Continuous, Full Load Rated
 - * Simple Repair, Low Cost Parts
 - * Each Component The Best Available
 - * GFCI with 35' Cord (120 volt versions only)
 - * Female Garden Hose Inlet
 - * 1/4 Female Quick Connect Outlet
 - * Max Water Temperature 140 degrees
 - * 120 Volt, 8 to 15 amps (depending on pressure), 240 volt version is this amp draw cut in half.
- fitted with an m44 motor, this is the motor used for a hard surface pumping system that is outside the extractor case.
Does come with a pressure gauge.
Out of box measurements 14" X 11" 11" H
Shipping wt: 50#s
Shipping dimensions: 20" X 16" X 15"
Amp draw is 7.5 amps to turn on + 1 amp for each 200 psi you ask it to push.
Example 500 psi uses 10 amps @ 120 volts

Current or past OEM Associations:

CWS-HDS1200

80346

20-0640

AS1200

Cross American Shock-Wave

>

Pressure washer motor information below:

Parts list

Brochure

Start Up Procedures

PumpTec Warranty Info .Options:

Add an extended Warranty to your cleaning equipment;

<http://www.steam-brite.com/extended-warranties-equipment-valued-749999-available-p-10663.html>

717510409055

>



>

Four (4) Way Faucet Key J40-005

Note Pumptec Dealers do not receive the faucet adapter, connection hose, or free sipping. Just the pump at dealer prices + shipping

Compare to other tile and carpet cleaning pump systems:

<http://www.steam-bright.net/showthread.php?2048-Tile-cleaning-pump-options-to-add-to-my-flood-pumper-or-carpet-cleaning-machine&highlight=tile+cleaning+pump>

Rotovac \$795
used to be \$685.78 our of CO
-->

Availability: This product was added to our catalog on Tuesday 31 January, 2017