

>



Model Number: 20170822

20170822, Pressure Washer Double QD, to Rust Bleeder, to Filtered Insulated Carpet Cleaners QD, (Male Plug as first Piece)

Manufacturer: Clean Storm

Clean Storm 20170822 Pressure Washer Double QD to Rust Bleeder to Filtered Insulated Carpet Cleaners QD (Male Plug as first Piece)

Description

Problem: Pressure washing water heaters/burners are made of steel so small particles of rust can clog the finer jets used for tile, carpet, and upholstery cleaning.

Solution: This Snaps into pressure washers QD that has female 3/8" QD connections(horizontal) into tee fitting to bleed out rust from burner (faces downward/ vertical) > to high pressure filter (horizontal) and insulated carpet and tile cleaning female quick disconnect. Now you will have an easy to to bleed out the rust while filtering it out at the same time. The insulated carpet cleaners QD makes it easy to remove you carpet cleaning hoses. When you start the job run the first 2 minutes of water out the ball valve to clear out as much rust as possible. Installed filter and carpet cleaning QD are slightly elevated. Tee fitting is vertical with the hose downward and carpet QD and filter on top. As the water leaves the burner the rust will hit the "T" and lets the rust fall into the 60" long hose. Only the cleaner water will flow up hill through the high pressure filter and out the QDs.

Quick connection let you easily toggle between using tile and carpet cleaning hose or remove and use your pressure washing hoses.

IMPORTANT INFORMATION

Please note that the ball valve is only rated for 600 psi and depending on the heat and pressure you use, you might wear it out. We have installed the ball valve at the end of the 60" long hose so it will not be roasted by the heater.

We want you to point the back hose vertical (downward) so any rust that comes out of the heater will flow to the hose and valve while the cleaner water will travel upwards through the high pressure filter and insulated QD.

Northern Tool pressure washers need Female

BE Pressure need Male

Hydrotek do not include couplers so you typically purchase an extra male plug X male pipe and then purchase the standard female socket rust bleeder. Then also purchase an additional 3/8 female socket X 3/8" female pipe coupler for your hose. Then you can toggle between pressure washing and carpet and tile cleaning.

Please note for shipping reasons we will not completely tighten all fittings so please tape and retighten as need to ensure it will not leak for you.

Video

Made with the following parts

>

Truckmount 3/8" Brass Ball Valve 8.709-217.0 [87092170] AH51 B097

AS56A 1/4in Fip Insulated Safety Female Quick Disconnect Foster QD Samdx
With Nipple Stop Carpet Cleaning Style Samdx

2 units in this build



High Pressure Water Filter 1/4in Fip (In) X 1/4in Mip (Out) Water 8.709-978.0 -
5000 psi

Brass Union Tee 3/8in Fip X 3/8in Fip X 3/8in Fip Brass BR244 28026

Clean Storm Truckmount Repair Hose 3/8in Mip X 3/8in Mip X 60in L 4000psi
Double Wire 3/8in ID

AH54 Ball Valve 1/4in Male X Female Pipe 1000 psi Chrome Plated AH57
PMV60804 1692-2484

2 units in this build

1/4in Mip X 3/8in Mip Hex Reducing Nipple Brass 8.705-227.0 - BR132

>

Brass Union Tee 1/4in Fip X 1/4in Fip X 1/4in Fip Brass BR242 28025 Buy
More Save More

1/4 Mip X 1/4 Mip Brass 90 Elbow 28267 BR267 [28-267]

2 units in this build

Male Nipple Plug 3/8 in Stainless Steel Quick Coupler 87071520 QD

One unit in this build

Brass Elbow, 3/8in Street, 45 Degree 8.706-834.0 [28-232]

Do its yourself build is about \$125 in parts.
Optional

About 20% of a roll of
Teflon Tape Plumber's Pipe Thread and Sealing Tape 118905 [TFLNTP]
Will be needed.

Upgrade ball valve to high pressure
Clean Storm 3/8" Fip Full Port High Pressure Ball Valve Steel 7250 psi

Availability: This product was added to our catalog on Tuesday 22 August, 2017