

>



Model Number: RAM1000DBL

Abatement Technologies RAM1000DBL Carpet Flood Restoration Air Mover Raptor 1000 W/ GFCI

Manufacturer: Abatement Technologies

Abatement Technologies: RAPTOR High-Velocity Centrifugal Air Mover- 1,125 cfm

...

RAPTOR® High-Velocity Centrifugal Air Movers for Water Damage Restoration Professional

Contractor benefits of utilizing the RAPTOR Centrifugal Air Movers include:

- Faster drying time
- Improved employee productivity
- Reduced clean-up time
- Reduced maintenance costs with heavy-duty components
- Lightweight and easy to carry

Advanced Centrifugal Technology Creates Exceptional Airflow to Dry Wet Areas Faster

The highly portable RAPTOR Centrifugal Air Movers (CAM) provide high-speed 2,850 fpm airflow using less than three amps. Up to four RAPTOR CAM units (deluxe model) can be daisy-chained together to operate on a typical 15 amp household circuit. More units in the wet area create greater airflow and faster, higher-quality drying results.

Lightweight and Easy to Move

It's easy to hand carry one or two of the lightweight (25 lbs.), perfectly balanced RAPTOR air movers using the ergonomically-designed handle

Operates at Multiple Angles

The RAPTOR can be set to operate horizontally, at 45-degrees and straight-up 90-degrees to the ceiling

Secure Stacking

>

Up to three RAPTOR units stack  
and interlock securely to save space in  
a warehouse or van during transport.

#### GFCI-Protected Receptacles and Circuit Breaker

The deluxe RAPTOR Air Mover includes a dual, GFCI-protected receptacle  
and circuit breaker for daisy-chain operation of up to four units on a single 15 amp  
circuit.

g

Technical Specifications:

>

## RAPTOR Centrifugal Air Mover

Airflow - 2,850 fpm @ high speed. Tested actual output of 1,125 cfm @ high speed  
Net Weight - 25 pounds  
Power Supply Requirements - 120 volts AC, 60Hz, 15 amps  
Normal Operating Amps - 2.8 amps or less. (Four units draw only 11 amps combined on a 15 amp circuit)  
Circuit Breaker - 10 amps  
Cabinet Material - UL94HB flame retardant resin with EPA-Registered microbial inhibitor  
Transportability - Built-in ergonomic carry-handle distributes weight evenly to create a perfect balance for superior portability  
Non-Marking Rubber Feet - Attached rubber feet protect surfaces, eliminate vibration and secure the RAPTOR firmly in place during operation

### Safety-Certified by ETL

Abatement RAPTOR Air Movers have been tested by Environmental Testing Laboratories (ETL), a Nationally Recognized Testing Laboratory (NRTL), and carry the ETL (U.S.) and ETLC (Canada) marks certifying that they comply with applicable OSHA and CSA electrical safety standards. Learn more about the importance of product safety certification.

---

*Availability: This product was added to our catalog on Tuesday 04 January, 2011*