

>



Model Number: GPE-75EH-3-3

Gillette Generator GPE75EH-3-3 13hp Industrial Portable Generator 6000watts 240 volt, electric start, triple phase

Manufacturer: Gillette Generator

Gillette Generator GPE75EH Industrial Portable Generator 7500watts 120volts electric start

Powered By Honda's GX390 Commercial Grade OHV Engine
•A compact, fuel efficient engine which provides plenty of torque
•Cast iron cylinder sleeve provides long engine life

Electric Starting System w/ Recoil Backup (Battery Not Included)
•Start your generator by flipping a switch (Min 200 CCA Battery)

Oil Alert® Warning System
•Alerts you or shuts engine down if oil reaches an unsafe level

Exclusive Kleen-Power® (Only 6% THD) & Exclusive Power-Assist™
•Provides clean, smooth operation of sensitive electronics
•Provides extra power for hard starting electric motor loads

Full Panel GFCI Protection - OSHA & UL Compliant
•Must use GFI type manual transfer switch for panel connection
•Interlock kits are not compatible with this generator

4-Gallon Metal Fuel Tank w/ Gauge, Twist-Cap & Slosh Valve
•Provides extended run times of 4.2 hours @ 3/4 load

Rugged 1.25" Steel Round Roll Frame
•Provides total generator protection on the jobsite

Built-In Hour Meter w/ Maintenance Alerts
•Reminds you when it is time to change the oil & air filter

2 Year/1000 Hour Limited Warranty

GENERATOR MODEL

>

GPE-75EH

MAX. KW @ 3 PH.
6

PRIME KW @ 3 PH.
5.5

PRIME AMPS @ 208 V.
18

PRIME AMPS @ 240 V.
16

PRIME AMPS @ 480 V.
8

GENERATOR REGULATION
5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS.

FREQUENCY REGULATION
5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING

“KLEEN-POWER”
ELECTRICAL WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL
GEN- PRO GEN-SETS

ENGINE MODEL (WARRANTY)
HONDA GX390 O.H.V. (3 YEARS)

ENGINE START METHOD
12VDC ELECTRIC & ROPE RECOIL

ENGINE HP @ 3600 RPM
13 HP

>

ENGINE DISPLACEMENT
1 CYLINDER, 23.7 CU. IN. (390 CC)

ENGINE AIR CLEANER
HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS

ENGINE FUEL TANK
8 GAL. (30.2 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE

ENGINE OIL SYSTEM
FORCED SPLASH

LOW OIL PROTECTION
AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL

db(A) AT 7 METERS
78

3/4 LOAD RUN TIME (HRS)
8.4

FUEL USE, GAL/LTR/HR
0.95 / 3.56

MOTOR START POWER
2 1/2 HP, CODE G ELECTRIC MOTOR

CRANE PICK-UP HOOK
OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET

2-WHEEL DOLLY KIT
OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND
"NEVER GO FLAT" WHEELS

MAINLINE CB
STANDARD 3 POLE MAG CIRCUIT BREAKER & 20A @ 208V &
240V & 10A @ 480V

>

HOUR METER
RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE
OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER

POWER TAKE OFF
POWER TAKE OFF 4 POSITION TERMINAL STRIP

PROTECTIVE ROLL FRAME
RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE
GEN-SET

LENGTH, INCHES
31

WIDTH, INCHES
25

HEIGHT, INCHES
27.5

SHIP WEIGHT, LBS.
277

CU. FEET SHIP BOX
20

Optional

Generator Grounding Kit Bonding Parts 18012017 Self Install

>

BE Pressure 85.508.003 Champion Power 48036 L14-30P X Four 5-20R
Generator Power Cord Adapter

Availability: This product was added to our catalog on Monday 13 April, 2020