

>



Model Number: PA-CH740-0101

Kohler PA-CH740-0101, Command Pro Propane Horizontal Engine, 1-1/8in x 4in Crank Shaft, 22hp 725cc, No Muffler

Manufacturer: Kohler

Kohler PA-CH740-0101, Command Pro Propane Horizontal Engine, 1-1/8in x 4in Crank Shaft, 22hp 725cc, No Muffler, Freight Included  
Details

PA-CH740-0101 but without a muffler

740cc,

Key Switch engine mounted controls and ignition,

1.25 X 4.0" keyed crankshaft,

Flat air cleaner

Wire Harness 24 176 163

two stage regulator,

Propane vaporizer for liquid withdrawal,

Lock off solenoid w/filter,

15 amp charging system

CH730LP BASIC-WITH PANEL-KEYSWITCH

Open Loop Propane Fuel System

Kohler Command 25 HP Twin OHV Horizontal

Cylinder Type: Cast Iron Sleeves

Crankshaft: (24014381-S) 1"(25.4) x 3"(76)

Drilled & Tapped 3/8-24 UNF

.25"(6 mm) Key way

12 Volt Electric Starter: (2509811-S) Shift Style Solenoid

Key Switch: (2509930-S) Kit

Alternator: (237878-S) 15/20 Amp

Regulator: (2540320-S)

Oil Filter: (Oil Pump)

Air Cleaner: (2408302-S) Standard Duty

Liquid Fuel Withdrawal (4846501-S Vaporizer included)

>

Engine Weight: 106 lbs

Sales Notes: LPG, Propane

optional: Canister muffler: (2406806-S) Starter side outlet

Panel mounted Ignition Switch

Regulator: (2440304-S)

LPG, Propane

BASIC W/PANEL KEYS LP

Open Loop engines have the same components as closed loop, except the ECU and oxygen sensor and muffler are not included.

Closed Loop - This system relies upon two critical parts: an analog Electronic Control Unit (ECU) and an oxygen sensor. The system's fuel metering valve, installed in the fuel line, is activated by the ECU to provide either less or more fuel. The ECU engages when the oxygen sensor, installed in the exhaust, signals a change in oxygen levels. In this way, the ECU maintains a consistent air to fuel ratio at all loads and speeds

Replaces CH640-3003

Overhead Valve Design

- Hydraulic Valve Lifters
- Cast-Iron Cylinder Liners
- PTO Sleeve Bearing (Side Load) (25 & 27 HP)
- Electronic Ignition
- Large Capacity Dual Element Air Cleaner
- High Efficiency Grass Screen and Fan
- Closed Breather System
- Stellite® Exhaust Valves
- Full Pressure Lubrication
- Large Capacity In-Line Fuel Filter
- Easy Access Valve Cover Oil Fill-Yellow
- Oil Level Dipstick-Yellow
- Large Capacity Oil Filter, Dual Oil Drain

>

- Oil Sentry® (Switch Installed and Wired but Unconnected)
- Variable Speed Governor
- High Performance Accelerator Pump Carburetor (25 & 27 HP)
- Fuel Shutdown Solenoid, Smart-Choke® Carburetor
- Mechanical Fuel Pump
- High Performance Spark Plugs
- 12 Volt Solenoid Shift Starter
- 15 Amp Alternator, Regulated

- PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep
- 7" (178 mm) Diameter Pilot
- Color-Black with Cast Aluminum

#### Standard Features Plus:

- Engine Controls-Key Switch, Throttle and Choke Controls
  - Fixed Grass Screen Guard (25 & 27 HP)
  - 3/16" Evaporative emissions connection
- A common replacement engine for truck mounted carpet cleaning machines and pressure washers.

#### Owners Manual

\$2,890.11 <https://salempwr.com/pa-ch740-0101-ch740lp-ng-e3-mark/>  
-->

*Availability: This product was added to our catalog on Thursday 09 November, 2023*