

Equipment: Restoration > Dehumidifier > Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

## Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)



Model : 2HNR7

Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

Manufacturer : Dayton

Industrial Dehumidifier, Cap 60 Pints

Industrial Dehumidifier, Capacity 60 Pints 24 Hours, Voltage 115, 60 Hz, 11 Operating Amps, Humidity Range 30 To 90 % RH, Ambient Temp Range 42 To 95 F, 1 Fan Speed, Height 35 In, Width 16 1/8 In, Depth 15 3/8 In, Painted Steel Cabinet Material, Gray And Black Color, Includes 2 Large Wheels, Condensate Pump, 20 Feet Of Drain Hose And Handle

Item

Industrial Dehumidifier

Capacity (24 Hours)

60 Pints

Voltage

115

Hz

60

Operating Amps

7.3

Fan CFM

680

Humidity Range (% RH)

30 To 90

Equipment: Restoration > Dehumidifier > Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

## Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

Ambient Temp. Range

42 To 95 F

Fan Speed

1

Height (In.)

35

Width (In.)

16 1/8

Depth (In.)

15 3/8

Cabinet Material

Painted Steel

Color

Gray And Black

Refrigerant Type

R22

Refrigerant Charge (Oz.)

21.9

Max. Lift (Ft.)

10

Filter

Dust Filter

Equipment: Restoration > Dehumidifier > Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

## Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

### Application

Helps Prevent Humidity and Moisture Damage in Enclosed Areas, Problem Industrial Use Such as Sewage Lift Stations, Telephone Relay Rooms, Fire and Flood Cleanup

### Agency Compliance

CETL

### Includes

2 Casters, 20 Ft Drain Hose, Collapsible Handle

### Industrial Dehumidifiers

High-capacity units provide quick, efficient dehumidification in extreme conditions of flooding and moisture problems.

Nos. 5E821, 5E822, and 1PJJ7 have automatic condensate pumps with 15-ft. vertical lift. On-demand pump purge switch, illuminated On/Off switch, and hour meter. Louvered front panel and rear power cord storage compartment. 20-ft. pump drain hose is included. Washable air filter and access panel for cleaning coils. Dual large handles, additional lower handle, and nonmarking wheels make units maneuverable and easy to transport. Tough painted steel cabinet. No. 5E821 has a reciprocating compressor and timed defrost. Nos. 5E822 and 1PJJ7 have rotary compressors and automatic, temperature-sensed, hot gas defrost with hot gas defrost on-demand switch. No. 1PJJ7 has a stainless steel cabinet for long durability of finish. CSA Certified. Nos. 2HNR6 and 2HNR7 feature touch pad controls with hour timer, rotary compressor, auto hot gas defrost cycle, auto operation with humidistat, removable air filter, storage compartment with 20-ft. drain hose for direct drain option, ergonomic handle, wheeled cart style design for easy portability, and 12-ft. power cord. CETL listed. No. 2HNR6 has a 9-pint collection bucket with overflow indicator. No. 2HNR7 features a collection pump that evacuates water up to 10 ft. of lift.

Uses: Help prevent humidity and moisture damage in enclosed areas. Ideal for problem industrial applications such as fire and flood cleanup, water treatment plants, sewage lift stations, and telephone relay rooms.

Equipment: Restoration > Dehumidifier > Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

## Dayton: 60 Pint Dehumidifier 2HNR7 (W/Condensate Pump)

- Ambient temperature range: 40 Degree to 95 DegreeF
- IPX2-rated

**Price : \$1,079.00**

---

Availability: This product was added to our catalog on Friday 07 March, 2008