



PRE-SPRAY

RTU pH 11.3 - 11.9

1-2 oz. : gal

Heavily Soiled &
Restaurant Carpets

SoilBreak™

High Powered Powder Enzyme Carpet Pre-Spray

SoilBreak an ultra-concentrated powder that is ideal for prespraying of restaurant carpets, automotive repair centers, and other carpets that are subjected to massive amounts of oil and grease based soiling. **SoilBreak** is a synergistic concentration of enzymes, solvents, surfactants and builders that work together to tackle the most stubborn build-up of caked on oil, grease, protein and sticky soils in the most challenging environments.



If for any reason you are not thrilled with the performance of **SoilBreak** return it to your distributor and we'll get you a product that does.

Net Contents:
40 Pounds (18.143 Kg)

Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.

Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in conjunction therewith. The user should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.

SoilBreak is a synergistic concentration of enzymes, solvents, surfactants and builders that work together to tackle the most stubborn build-up of caked on oil, grease, protein and sticky soils in the most challenging environments.

SoilBreak is an ultra-concentrated powder that is ideal for the prespraying of restaurant carpets, automotive repair centers, and other carpets that are subjected to massive amounts of oil and grease based soiling. Unlike some enzyme presprays that are sensitive to alkalinity and extremely hot water, **SoilBreak** contains a combination of enzymes that can be used in conjunction with your truckmount and/or high performance portable extraction equipment. This unique combination of enzymes works to accomplish the task in less time than with conventional enzyme presprays. **SoilBreak** breaks down surface tension fast, allowing detergents and rinse agents to clean deep down.

It has an In-use pH of 11.3-11.9, depending on dilution with a pleasing lemon fragrance. One pound of **SoilBreak** can clean up to 8,000 square feet of carpet.

Contents: Sodium tripolyphosphate (7758-29-4), sodium carbonate (9497-19-8), sodium metasilicate (6834-92-0), proprietary surfactants, glycol ether DPM (34590-94-8), EDTA Na4 (64-02-8), enzyme (9014-01-1), fragrance.

Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **SoilBreak** with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Mix **SoilBreak** at a rate of 2 oz. per gallon of hot tap water in a pump-up sprayer. In a standard injection type sprayer, mix 10 oz. into 5 qts. of hot tap water.
4. Pre-spray **SoilBreak** on the traffic areas and let dwell for 5-10 minutes.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution** cleaning wand.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

www.HydraMaster.com

Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
2. Para una mayor eficiencia, se aplican rotura del suelo con un pulverizador de inyección para tomar ventaja de presión de la solución y el calor creado por su alto rendimiento portátil extractor o Truckmount. También puede usar una "bomba-up" pulverizador o rociador accionado eléctrica o batería. Aplicar incluso superposición de patrones.
3. Mezclar Quiebre de suelo a una tasa de 2 oz por galón de agua caliente en un pulverizador de bomba. En un pulverizador de inyección de tipo estándar, mezclar 10 oz en 5 cuartos de galón. de agua caliente del grifo.
4. Pre-spray rotura del suelo en las áreas de tráfico para que habite durante 5-10 minutos.
5. Extraer con un detergente compatible extracción alcalina o ácido / neutralización de enjuague. Para una limpieza más rápida, reduce la fatiga y la eliminación de la suciedad más eficaz, se extrae con el RX-20 Herramienta de extracción de Rotary. En muebles ambientes densos utilizar la varita de limpieza Evolution.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, el aire centrífugo o de corriente descendente después de la limpieza.

GHS U.S. – CLASSIFICATION: WARNING

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.



PRECAUTIONARY STATEMENTS (GHS-US)

The product is classified and labeled according to the Globally Harmonized System (GHS). If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Wash skin and contaminated clothing thoroughly after handling. Do not eat, drink or smoke when using this product. Wear suitable protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/national/international regulations.

OSHA HAZARDS: Target Organ Effect (Glycol Ether DPM)
TARGET ORGANS: Kidney, Liver, Nerves (Glycol Ether DPM).
CLASSIFICATION SYSTEM: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.
NFPA RATINGS (SCALE 0-4): Health = 2, Fire = 0, Reactivity = 0
HMIS RATINGS (SCALE 0-5): Health = 2, Fire = 0, Reactivity = 0



See Safety Data Sheet (SDS): scan here or visit www.hydramaster.com for additional safety and regulatory information.

Lot:
Part # 950-120-C Art 950-120-C R2

HydraMaster
11015 47th Avenue West
Mukilteo, WA 98275
425.775.7272

