



PRE-SPRAY

RTU pH 9.5 - 9.9

1:32-64

Synthetic
Residential Carpets
Commercial Carpets

with
TRITANOL
1+1=3

FastBreak HD™

High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner

FastBreak HD is a VOC compliant formula that contains the industry exclusive component Tritanol™ an integrated blend of specialized polymers, organic synthesizers, and surfactants. With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition. It just works better!



If for any reason you are not thrilled with the performance of **FastBreak HD** return it to your distributor and we'll get you a product that does.

HydraMaster

Important notice to purchaser: The manufacturer and seller warrant that the chemical contained herein conforms to its standard specifications. Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The product contains oxidizers and may alter or remove the original color of the carpet it is being applied to. Use only as a last resort and with the customer's permission and understanding of this risk.

Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **FastBreak HD** with an injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. For medium to heavy soiling, mix one part solution with 32 parts water (four ounces to a gallon/.12 liters to 3.785 liters). For lighter soiling mix one part solution with 64 parts water (2 ounces to a gallon/.06 liters to 3.785 liters) For standard injection sprayer, mix one quart solution with four quarts of water into five quart container.
4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding two ounces of **GreaseBreaker** with each mixed gallon of **FastBreak HD**.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution cleaning wand**.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área poco visible la estabilidad del color antes de la aplicación.
2. Para una mayor eficacia, aplicar **FastBreak HD** con un pulverizador de inyección para tomar ventaja de la presión y solución calor creado por su alto rendimiento extractor portátil o Truckmount. También puede utilizar una "bomba-up" pulverizador o rociador potencia eléctrica o la batería. Aplicar en la superposición de patrones, incluso.
3. Para medianas y están muy sucios, mezcle una solución parcial con 32 partes de agua (cuatro onzas a un galón / litros a 3.785 liters .12). Para más ligera solución de mezcla de suciedad por una parte con 64 partes de agua (2 onzas a un gallon/.06 litros a 3.785 litros) para el pulverizador de inyección estándar, mezcle una solución de cuarto con cuatro litros de agua en el recipiente de cinco cuartos.
4. Para las alfombras con altos niveles de apelmazar-en la grasa y la contaminación por petróleo, considere aumentar mediante la adición de dos onzas de **GreaseBreaker** con cada galón de mezcla de **FastBreak HD**.
5. Se extrae con un detergente compatible extracción alcalina o ácida / neutralizar enjuague. Para una limpieza más rápida, reducción de la fatiga y la eliminación de la suciedad más efectivo, el extracto con el **RX-20 Herramienta de extracción de Rotary**. En muebles de ambientes densos utilizar la varita de **limpieza Evolución**.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, aire centrifugo, o corriente descendente después de la limpieza.

GHS U.S. – CLASSIFICATION: WARNING

Harmful if swallowed. Causes skin irritation
Causes serious eye irritation.



PRECAUTIONARY STATEMENTS (GHS-US)

Harmful if swallowed. Causes skin irritation.
Causes serious eye irritation.

The product is classified and labeled according to the Globally Harmonized System (GHS)

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wash skin and contaminated clothing thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear suitable protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions:

0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4): Health = 2, Fire = 0, Reactivity = 0

HMIS RATINGS (SCALE 0-5): Health = 2, Fire = 0, Reactivity = 0



See Safety Data Sheet (SDS): scan here or visit www.hydramaster.com/sds for additional safety and regulatory information.

Lot:

Part # 950-132-A Art 950-132-A R4

HydraMaster

11015 47th Avenue West

Mukilteo, WA 98275

425.775.7272

Net Contents: One U.S. Quart (.9463 liters)



8 10149 01084 2