



PRE-SPRAY

RTU pH 11.0 – 11.5

1:16-32

Olefin, Polyester, & Triexta Carpeting

Olefin, Polyester, and Triexta Carpet Prespray and Preconditioning Agent

with
TRITANOL
1+1=3

PolyBreak is specially formulated to effectively clean heavily soiled olefin, polyester, and triexta carpets with a specialized blend of surfactants, solvents, and emulsifiers that are designed to suspend, dissolve, dislodge, and emulsify, and lift oily soils. This is so important with these types of carpet fibers because they are oil-loving fibers and allow spilled, tracked, and airborne oils and greases to soak into and penetrate the carpet fiber.



If for any reason you are not thrilled with the performance of **PolyBreak** return it to your distributor and we'll get you a product that does.

Net Contents:
One U.S. Gallon (3.78 liters)



Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in conjunction therewith. The user should thoroughly review the material safety data sheet for this product and follow recommendations for mixing, application, disposal, and the use of any applicable personal protective equipment (PPE). The manufacturer, distributor, and seller of this product warrant that the chemical contained herein conforms to its standard specifications.

Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. The manufacturer and seller make no representation or warranty, including merchantability or any other kind, expressed or implied. The foregoing may not be altered except by written agreement by officers of the manufacturer.

PolyBreak is specially formulated to effectively clean heavily soiled olefin, polyester, and triexta carpets with a specialized blend of surfactants, solvents, and emulsifiers that are designed to suspend, dissolve, dislodge, and emulsify, and lift oily soils. This is so important with these types of carpet fibers because they are oil-loving fibers and allow spilled, tracked, and airborne oils and greases to soak into and penetrate the carpet fiber. **PolyBreak** meets and exceeds the exacting requirements for cleaning heavily soiled olefin carpeting. You can restore the appearance level of most lightly colored olefin carpets with this solution, including olefin berbers. It will often effectively remove the yellow traffic lane discoloration that tends to appear on these types of carpeting. Its synergistic blend of specialized surfactants penetrates that water repelling characteristic of olefin for more effective removal of ground-in soiling. **PolyBreak** is a VOC compliant formula that contains the industry exclusive component **Tritanol™** - an integrated blend of specialized encapsulating polymers, organic sequestrants, and specialty surfactants. With the unprecedented cleaning power and performance of **Tritanol™**, you will experience deep restorative cleaning in high definition. It just works better! **PolyBreak** is a super-concentrated formula (16-32:1) making it more economical for you. The high pH formula (11.0 – 11.5) makes it effective for filthy and neglected carpets, but should not be used on warranted, stain resistant nylon carpeting. **PolyBreak** is also excellent at breaking down and effectively removing filtration soil lines, and in removing soot and other contamination in carpeting on fire damage restoration jobs.

Contents: Glycol ether DB (112-34-5), sodium xylene sulfonate (1300-72-7), EDTANa4 (64-02-8), sodium metasilicate (6834-92-0), proprietary surfactants, polymers, and fragrance.

Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **PolyBreak** with an injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Prespray with 1 part **PolyBreak** mixed with 32 parts hot water (4 ounces of solution mixed with one gallon of hot water). For extreme soiling and filtration soiling, mix 1 part solution to 16 parts water (8 ounces of solution with one gallon of hot water). For standard injection sprayer, mix one quart water with four quarts of Quake into 5 quart container.
4. Allow to dwell for 3 -5 minutes.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution** cleaning wand.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

www.hydrmaster.com

Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área oculta la estabilidad del color antes de la aplicación.
2. Para una mayor eficiencia, se aplican **PolyBreak** con un pulverizador de inyección para tomar ventaja de presión de la solución y el calor creado por su alto rendimiento portátil extractor o Truckmount. También puede usar una "bomba-up" pulverizador o rociador accionado eléctrica o batería. Aplicar incluso superposición de patrones.
3. Prespray con **PolyBreak** parte 1 mezclada con 32 partes de agua caliente (4 onzas de solución mezclada con un galón de agua caliente). En caso de suciedad extrema y la suciedad filtración, mezcle 1 parte de solución de 16 partes de agua (8 onzas de solución con un galón de agua caliente). Para pulverizador de inyección estándar, mezclar un litro de agua con cuatro cuartos de galón de Quake en un contenedor cuarto 5.
4. Permitir a morar para 3 -5 minutos.
5. Extraer con un detergente compatible extracción alcalina o ácido / neutralización de enjuague. Para una limpieza más rápida, reduce la fatiga y la eliminación de la suciedad más eficaz, se extrae con el RX-20 Herramienta de extracción de Rotary. En muebles ambientes densos utilizar la varita de limpieza Evolution.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, el aire centrífugo o de corriente descendente después de la limpieza.

GHS U.S. – CLASSIFICATION: WARNING
Harmful if swallowed. Causes skin irritation
Causes serious eye irritation.

PRECAUTIONARY STATEMENTS (GHS-US)
Harmful if swallowed. Causes skin irritation.
Causes serious eye irritation.
The product is classified and labeled according to the Globally Harmonized System (GHS)

If medical advice is needed, have product container or label at hand.
Keep out of reach of children. Read label before use.
Wash skin and contaminated clothing thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear suitable protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Dispose of contents/container in accordance with local / regional / national / international regulations.

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4): Health = 2, Fire = 0, Reactivity = 0
HMIS RATINGS (SCALE 0-5): Health = 2, Fire = 0, Reactivity = 0

See Safety Data Sheet (SDS): scan here or visit www.hydrmaster.com for additional safety and regulatory information.

Lot:
Part # 950-135-S Art 950-135-S R4



HydraMaster
11015 47th Avenue West
Mukilteo, WA 98275
425.775.7272

