

Triple Strength Low Moisture Encapsulation Carpet Cleaning Solution

with TRITANOL 1+1=3 ZipDri Encap TS is the only encapsulation cleaner that contains **Tritanol**<sup>™</sup> - an integrated blend of specialized encapsulating polymers, organic sequestrants, and specialty surfactants. **Tritanol**<sup>™</sup> helps separate ground in soiling from the carpet fiber, encapsulates soil and holds it in suspension, and makes it easier for subsequent vacuuming to extract more soil than conventional encapsulation cleaners.





to your distributor and we'll get you a product that does.

Net Contents One U.S. Gallon (3.78 liters) 말들

e e gib a bilitique

ZipDri Encap TS allows the carpet cleaning professional to take advantage of the many strengths of a low moisture soil encapsulation system such as eliminating wicking and reoccurring spills; tripled cleaning productivity rates; extending the carpet life-cycle, greatly reduced area downtime: and positive appearance management. ZipDri Encap TS keeps carpet looking its very best with less effort and increased productivity. ZipDri Encap TS is the most ultra-concentrated encapsulation cleaner on the market, utilizing only 2 to 4 ounces of solution per gallon of water. ZipDri Encap TS is the only encapsulation cleaner that contains Tritanol<sup>™</sup> - an integrated blend of specialized encapsulating polymers, organic sequestrants, and specialty surfactants. Tritanol helps separate ground in soiling from the carpet fiber, encapsulates soil and holds it in suspension, and makes it easier for subsequent vacuuming to extract more soil than conventional encapsulation cleaners. ZipDri Encap TS does so much more than dry down to a brittle, non-resoiling residue. It cleans better. Lasts longer, and helps carpet stay cleaner longer. ZipDri Encap TS can be effectively used with virtually any low moisture agitation system - CRCB (Counter-rotating cylindrical brush); triple planetary rotary brush; oscillating or orbital brush or pad; and with absorbent bonnet pads. When carpets are cleaned according to directions with ZipDri Encap TS, you will experience drying times between 10 minutes and an hour. There is no faster, easier way to make carpet look better and stay cleaner longer. ZipDri Encap TS will work wonders on commercial glue down carpets, but can be safely and effectively used on synthetic and wool commercial and residential carpet. Best of all, ZipDri Encap TS leaves the room smelling clean and refreshed and qualifies as a SafeClean formula. With ZipDri Encap **TS**S and the right solution applicator and agitation machine, you can experience cleaning rates of up to 5000 square feet per hour.

## Directions:

- As a low moisture encapsulation cleaner:
- Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
- For normal soiling, mix one part ZipDri Encap TS with 32-64 parts hot water (2-4 ounces of solution with a gallon of water) into a pump-up, electric, or battery powered pressure sprayer. For heavily soiling, mix one part solution with 16 parts water.
- Apply the ready-to-use solution as a mist in a consistent. overlapping pattern. Use more solution in heavily soiled areas. For best results, apply with electric or battery powered spraver.
- Agitate the solution into the carpet with a counter rotating cylindrical brush machine, triple planetary rotary brush machine, oscillating or orbital agitation machine, or rotary shampoo brush.
- If using **ZipDri Encap TS** with a bonnet pad system, mix solution 8 ounces to a gallon, and apply to carpet and both sides of bonnet pad. Proceed to clean in normal manner rotating or changing bonnets when the pad stops absorbing soil.
- Allow the solution to completely dry. To accelerate drying, consider the use of an axial, centrifugal, or downdraft air mover.
- Vacuum the carpet thoroughly after the carpet dries or at the next scheduled interval.



Contents: Diethylene glycol monobutyl ether (CAS#112 34-5), Lauramine oxide (CAS#1673-20-5), proprietary polymers-trade secret, preservative and fragrance

## For absorbent bonnet pad cleaning system:

If using **ZipDri Encap TS** with a bonnet pad system, mix 8 ounces of solution with a gallon of water into a pump-up, electric, or battery powered pressure sprayer.

Apply mixed solution to carpet and both sides of bonnet pad. Proceed to clean in normal manner rotating or changing bonnets when the pad stops absorbing soil.


Rinse off dirty bonnet in the mop bucket containing the clean water. Wring pad as dry as possible.

Switch to new bonnet as needed and continue process

To speed dry the carpet, buff with clean dry bonnets, turning and changing the bonnet often. Allow the solution to completely dry. To accelerate drying, consider the use of an axial, centrifugal, or

downdraft air mover.

Vacuum the carpet thoroughly after the carpet dries or at the next scheduled interval.



Precautions and First Aid: Keep out of reach of children. Contact may cause skin and eye irritation. Wear gloves and safety glasses when handling to avoid any contact with eyes and contact with skin in concentrate form. Use only in well ventilated areas. In case of eye contact, immediately flush with plenty of water. If irritation persists, seek medical attention. In case of skin irritation, flush with plenty of water. If ingested, drink large ■ guantities of water and seek medical attention. Re-■ move to fresh air in case of inhalation. See Material Safety Data Sheet (MSDS): www.hydramaster.com/ msds for additional safety and regulatory information.

Precauciones y Primeros Auxilios:

Mantener fuera del alcance de los niños.

El contacto puede causar irritación cutánea y ocular. Use guantes y gafas de

seguridad cuando manipule para evitar cualquier contacto con los ojos y el contacto con la piel en forma de concentrado. Usar sólo en áreas bien ventiladas. En caso de contacto con los ojos, lávelos inmediatamente con abundante aqua. Si la irritación persiste, busque atención médica. En caso de irritación de la piel. lavar con abundante agua. Si se ingiere, beba grandes cantidades de aqua y buscar atención médica. Trasladar al aire fresco en caso de inhalación. Ver Hoja de Seguridad (MSDS): www.hydramaster.com / MSDS para mayor seguridad y normativas.

HydraMaster/U.S. Products www.hydramaster.com 425.775.7272 Part # 950-152-S Art 950-152-S-R1

