

AQUATEC TRIPLEX DIAPHRAGM PUMPS WITH PRESSURE SWITCH. AVAILABLE IN 60, 120 170 & 220 PSI MODELS. VOLTAGE: 120 , 230 & 12



STOCK MODELS
DISTRIBUTOR COST:

120 PSI W/ SWITCH = 220 PSI W/ SWITCH =

FEATURED PRODUCT: AQUATEC 200 PSI INTERNAL BYPASS, 1.3 GPM OPEN FLOW, 1.2 AMP MAX, 120 V 1000 + HRS. BRUSH LIFE



DISTRIBUTOR COST:
120 VOLT MODEL =

230 VOLT MODEL =

SELF PRIMING & CAPABLE OF BEING RUN DRY.

SHURFLO 8000-812-288



COMPARE SHURFLO 100 PSI TO AQUATEC 120 PSI PUMP. IT HAS AN IDENTICAL REPLACEMENT FOOTPRINT.

SPECIFICATION:

- Nylon housing . Viton valves
- Santoprene diaphragm
- Liquid temperature: 170 deg F max
- 3/8" FPT ports
- Permanent magnet non – ventilated total enclosed DC motor. 230 Volt motors are RFI/EMI filtered. Motor is thermally protected @ 150 deg F on models up to 170 psi & 212 deg F on 220 psi models.
- UL, CSA & CE approvals.



200 PSI model can be used to replace PUMP TEC 200 psi pumps w/ basic fitting changes.