




Husqvarna CRT 36

The Husqvarna CRT 36, 36-inch, ride-on trowel offers high quality results, productivity and operator comfort. One person can easily raise and lower the integrated wheel set from one jack at the rear of machine allowing easy manoeuvrability around the job site. During use, the wheel kit does not block the operator's line of sight. CRT 36 is ideal to finish surfaces from 3,000 sq ft up to 10,000 sq ft. Thanks to the CVT clutch, CRT 36 can be used at low engine speed with pans for the first passes to reach a high level of floor flatness, and can be used also with finishing blades at higher engine speed to burnish the concrete.



Smooth automatic operation

A special variable clutch offers proper torque and speed range to match concrete conditions without mechanical adjustments. Since the clutch helps to keep constant torque the belt life is prolonged.



Ideal floating and high production

Sensitive, ergonomically designed twin-lever controls reduces amount of force needed to control the unit but still provides feedback from concrete conditions.

Optimum manoeuvrability

Thanks to its balanced power-to-weight ratio and ergonomic twin lever controls.



Good visibility

Front and rear lights as standard lets you perform in dim light and during night operations.



FEATURES

- Optimum manoeuvrability
- Ideal floating and high production
- Smooth automatic operation
- Good visibility

Technical Specifications

ENGINE

Motor/engine manufacturer	Honda
Motor/engine model	GX690
Output power (As rated by the engine/motor manufacturer)	22.9 hp
Exhaust emissions (CO2 EU V)	751 g/kWh
Fuel tank volume	6.39 gal (US)

SPECIFICATIONS

Blades	8 pcs
Vibration value	1.8 m/s ²

SOUND AND NOISE

Sound pressure level at operators ear	91.2 dB(A)
Sound power level, measured	104.7 dB(A)

PACKAGING

Packaging length	2185 mm
Packaging width	1143 mm
Packaging height	1613 mm