

FastBreak HD



EXTRACTION

RTU pH 9.5 - 9.9

1:32-64

Synthetic

Residential Carpets

Commercial Carpets

High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner

FastBreak HD is a VOC compliant formula that contains the industry exclusive component Tritanol™ an integrated blend of specialized polymers, organic synthesizers, and surfactants.

With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition. It just works better at 32-64:1 dilution!

- Fast Break HD is a concentrated VOC compliant formula that contains the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition. It just works better!
- Fast Break HD is a special blend of surfactants, and is packed with soil busting, grease cutting and dissolving ingredients with an unbeatable cleaning power that out-cleans competitive products.
- Highly effective on all synthetic fibers and commercial wool carpets

Mixing Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply FastBreak HD with an injection sprayer to take advantage of solution pressure and heat created by your high-performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even, overlapping patterns.
3. For medium-to-heavy soiling, mix 1 part solution with 32 parts water (4 ounces to 1 gallon/.12 liters to 3.785 liters). For lighter soiling, mix 1 part solution with 64 parts water (2 ounces to 1 gallon/.06 liters to 3.785 liters) For standard injection sprayer, mix 1 quart solution with 4 quarts of water into 5 quart container.
4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding 2 ounces of Grease-Breaker with each mixed gallon of Fast Break HD.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the RX-20 Rotary Extraction Tool.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.



Available in: 1 Gallon; Case of 4 x 1 gallon; 5 gallon pail
Part # 850-132

HydraMaster
We've Got Your Back

www.hydramaster.com | 800.426.1301 | 425.775.7272
sales@hydramaster.com

