

TAKE CHARGE OF YOUR ENVIRONMENT.

TOOLS TO MAKE IT SAFER,
FASTER AND EASIER.



DRYING

StudeBaker AirPath™

- Lightweight and portable with locking casters for drying hard surfaces
- Easy 2-speed switch
- Patented 360° outlet grill design
- High velocity 40 MPH airflow
- Uniformly directs air across the floor
- Durable rotomolded housing

ODORS

ActivO Ozone Generator

- Safer and more powerful odor removal.
- Rapidly clear areas of ozone automatically.
- Perform fast deodorization easily.

AIR QUALITY

HEPA 500 Air Scrubber

- Effectively remove airborne particles.
- Restore healthy indoor air quality—safely and efficiently removing contaminants.
- Achieve the highest Clean Air Delivery Rate to exceed AHAM standards

TEMPERATURE AND HUMIDITY

EB1400

- 1 Ton cooling with 450 CFM.
- Dehumidification, focused heating and ventilation.
- Ductable for spot cooling, directing conditioned air or heat into specific spaces.

DRI-EAZ®

PORTABLE ENVIRONMENTAL CONTROL

866.932.3233 | FACILITIES.DRI-EAZ.COM | DRI-EAZ.COM

TAKE CHARGE OF YOUR ENVIRONMENT.



EB1400

Split-stream Airflow	Warm Output (Condenser) - 750 CFM Cool Output (Evaporator) - 470 CFM
Cooling	1 Ton cooling effectiveness* (10,120 BTU/HR rated)
Water Removal Capabilities	110* pints/day
Operating Conditions	60° - 105°F
Controls	Digital thermostat
Power	115V 11.7* amps
Safety Approval	ETL listed to UL 474 Standard
Dimensions (HxWxD)	45" x 25" x 31" (114.3 cm x 63.5 cm x 78.7 cm)
Weight	185 lbs (83.9 kg)
Pump/Hose	Built-in condensate pump with 40 ft. hose *at 95 / 60% RH



ACTIVO

Dimensions HxWxD	39.37" x 19.69" x 15.75" (100 x 50 x 40 cm)
Output	12 grams/hr (12,000mg/hr) 265 CFM
Weight	88.18 lbs (40 kg)
Wheels	Rubber
Ozone Post Treatment System	Inbuilt catalytic converter
Maximum Cubic Feet	17,000 cu ft (about 480 cu m)



AIRPATH™

Weight	38 lbs (17.3 kg)
Dimensions HxWxD	14.7" x 25.4" x 26" (37.3 x 64.5 x 66 cm)
Amp Draw	7.5 amps
Speed	2 speed switch
Power	746 W (1.0 HP)
Cord Length	25 ft. (7.62 m)
Fan	8 Blades
Construction	Rotomolded Housing
Casters	Plastic (Locking)
Safety	ETL approved to UL standards



HEPA 500

Dimensions HxWxD	24.6 x 26.2 x 18.2 in (62.5 x 66.5 x 46.2 cm)
Use Weight	44 lb (20 kg)
Frequency	60 hz
CFM Rating (Min)	250 CFM (424.8 CMH)
CFM Rating (Max)	500 CFM (849.5 CMH)
Filter System	2-stage with optional carbon filter
Primary Filters	HEPA filtration technology
Power	115v 3 amps



PORTABLE ENVIRONMENTAL CONTROL
866.932.3233 | FACILITIES.DRI-EAZ.COM