

The Windshear™ Downdraft

Simple innovation in an economic package.

Spaces are dry, safe and ready for immediate use.



Whole Room Drying in Just Minutes

Dry an average size room in just minutes with the new Tornado® Windshear™ Downdraft drying technology. This new air mover from Tornado® pulls drier, warmer air from above, driving it down and out across the entire surface of the floor. One Downdraft will dry an entire room in as little as 15 minutes. Drying rooms one section at a time is a thing of the past with the Windshear™ Downdraft.

Three Angle Operation

Angle adjustment is a built-in feature of the Downdraft. The unit's contours are designed to permit operation at three angles. You have the flexibility to place the Downdraft flat for drying floors or at 15, 30, or 90-degree angles for drying walls or to provide general air circulation. What's more is the easy-to-see yellow housing helps identify potential physical hazards, such as falling or tripping, as recommended by ANSI Standards Z53.1.

Versatility

The Windshear™ Downdraft provides easy operation, versatility, and durability for use in many different environments including:

- · Hospitals and Healthcare Facilities
- Schools and Universities
- · Hotels and Resorts
- Restaurants
- · Commercial Office Buildings
- · Retail Stores and Shopping Malls
- · Industrial Facilities, large and small
- · Restoration Cleaning

The Windshear™ Downdraft. Whole room drying innovation.

Key Features

- 6-blade precision pitched fan with high velocity motor for fast drying
- 3500 CFM 2 speed motor rated for continuos duty
- · Variable angle operation
- 360-degree directed air flow
- · Built-in cord wrap
- · Durable and rugged design
- Stackable up to 4 high for easy transport and space-efficient storage
- Expandable transport handle and built in wheels for easy transportation come standard



Versatile Variable angle operation and 360-degree directed air flow.









Whole Room Drying in Just Minutes The Downdraft fan pulls warmer, drier air down from the ceiling, blowing it across the entire floor for fast, complete drying.



PRODUCT SPECIFICATIONS	
MODEL	WINDSHEAR™ DOWNDRAFT
CATALOG NUMBER	98784
LXWXH	22" x 18" x 23"
NET WEIGHT	52 lbs.
POWER	115V/60 Hz
SPEEDS	2
AIR-FLOW (CFM)	2500 - 3500 CFM
AIR-FLOW DIRECTION	360 degree
MOTOR	.25 HP
HOUSING	Polyethylene
HANDLE	Molded in / Telescoping
STACKABLE	Yes
POWER CORD	20′ (18/3)

