SAFETY DATA SHEET FABRICMASTER FF

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME FABRIC MASTER FF

SYNONYMS Product is a mixture: No synonyms are available.

PRODUCT USE Moderately Alkaline Material

Hydramaster Corp. **SUPPLIER**

SUPPLIER'S ADDRESS 1500 Industry St. Suite 300

Everett, WA 98203 (425) 775-7272

PERS: 1-800-633-8253

EMERGENCY RESPONSE PHONE

NUMBER

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS U.S. – CLASSIFICATION : H302 Harmful if swallowed.

H315 Causes skin irritation

H319 Causes serious eye irritation

LABEL ELEMENTS GHS – US HAZARD PICTOGRAMS The product is classified and labeled according

to the Globally Harmonized System (GHS).

HAZARD PICTOGRAMS

H302

P101

P102

:

SIGNAL WORD WARNING

HAZARD STATEMENTS

(GHS-US)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

PRECAUTIONARY STATEMENTS

(GHS-US)

Harmful if swallowed.

Keep out of reach of children. P103 Read label before use.

Wash skin and contaminated clothing thoroughly after handling. P264

P270 Do not eat, drink, or smoke when using this product.

P280 Wear suitable protective gloves / protective clothing / eye protection /

If medical advice is needed, have product container or label at hand.

face protection.

P301+ IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

P312 unwell.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+351+ IF IN EYES: Rinse cautiously with water for several minutes. Remove

P338 contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations

CLASSIFICATION SYSTEM NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4) : Health = 2, Fire = 0, Reactivity = 0 Health = 2, Fire = 0, Reactivity = 0 HMIS RATINGS (SCALE 0-5)

SAFETY DATA SHEET FABRICMASTER FF

SECTION 3 - COMPOSITON/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTIC: Mixtures

DESCRIPTION: Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS#	EC#	GHS CLASS	
Ethylene Glycol Monobutyl Ether	5-10	111-76-2	203-905-3	Eye Irrit Cat 2B	
Alcohols Ethoxylated	1-5	68439-46-3	Not Found	Eye Irrit Cat 2B	
Sodium Octane Sulfonate	1-5	5324-84-5	226-195-4	Skin Irrit Cat 2, Eye Irrit Cat 2A	
				STOT SE Cat 3	
Sodium Thiosulfate	0.1-1	7772-98-7	231-867-5	Eye Irrit Cat 2B	

Irrit. = Irritation, Corr. = Corrosion, Cat. = Category, Dam = Damage, Tox = Toxic, STOT SE = Single Target Organ Toxicity Single exposure.

SECTION 4 - FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL : Never give anything by mouth to an unconscious person. If you feel unwell, seek

medical advice. Show the label where possible.

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to

ensure adequate flushing. Remove contact lenses, if present and easy to do so.

Continue rinsing. If irritation persists, get immediate medical attention.

SKIN CONTACT: Remove contaminated clothing and shoes. Wash affected skin area with soap and

water. If irritation persists, get immediate medical attention.

SWALLOWING (INGESTION) : If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING.

If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate

medical attention.

INHALATION : Remove to fresh air. Get immediate medical attention.

OTHER INSTRUCTIONS : Rescue personnel must wear appropriate protective equipment during removal of

victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

SPECIAL PROTECTIVE EQUIPMENT AND

PRECAUTIONS FOR FIRE

FIGHTERS

UNUSUAL FIRE AND EXPLOSION HAZARDS

: Dry chemical, foam, water, or carbon dioxide.

In the event of a fire, wear a NIOSH (USA) or CEN (EU) approved, positive pressure, self-contained breathing apparatus (SCUBA) and full protective clothing. Evacuate all

non-essential personnel from the danger area.

: No further relevant information is available.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES : Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.

ENVIRONMENTAL PROCEDURES
METHODS AND MATERIALS

FOR CONTAINMENT AND
CLEAN-UP

: Keep spilled material away from sewage/drainage systems and waterways.

All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an

SAFETY DATA SHEET FABRICMASTER FF

appropriate absorbent material such as clay or vermiculite. Place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS FOR SAFE

HANDLING

: Use with adequate ventilation. Wear proper protective equipment. Do not mix with water or acids without proper dilution and agitation to prevent a potentially violent reaction.

CONDITIONS FOR SAFE

STORAGE

: Store in closed, properly labeled containers. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.





SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

TLV (THRESHOLD LIMIT VALUE)

The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH – TLV	ACGIH – STEL
Ethylene Glycol Monobutyl Ether	50 ppm	20 ppm	Not Established
Alcohols Ethoxylated	Not Established	Not Established	Not Established
Sodium Octane Sulfonate	Not Established	Not Established	Not Established
Sodium Thiosulfate	Not Established	Not Established	Not Established

EYE PROTECTION : Wear chemical splash goggles or face shield.

SKIN PROTECTION : Minimize contact with product. Wear chemical resistant coveralls, boots, gloves,

apron and/or suitable long-sleeved clothing.

RESPIRATORY PROTECTION : In case of brief exposure use respiratory filter device. In case of intensive or longer

exposure, use respiratory protective device that is independent of circulating air.

VENTILATION : Ensure adequate ventilation.

ADDITIONAL MEASURES : Emergency eyewash and safety shower facilities should be available in the

immediate work area.

REQUIRED WORK/HYGIENE: Wash hands thoroughly after handling. Keep away from all food stuffs, beverages,

and feed. Do not eat, drink, or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE : Clear light amber liquid with mild odor

ODOR : Mild odor
ODOR THRESHOLD : Not available
PH : 7.75 ± 0.25 AS IS
MELTING POINT/FREEZING : Not available

POINT

BOILING POINT : Approx. 212° F.

FLASH POINT : Nonflammable, Noncombustible

EVAPORATION RATE : Not available

FLAMMABILITY : Nonflammable, Noncombustible

SAFETY DATA SHEET FABRICMASTER FF

LOWER FLAMMABILITY LIMIT Not available **UPPER FLAMMABILITY LIMIT** Not available **VAPOR PRESSURE** Not available **VAPOR DENSITY (AIR=1)** Not available **RELATIVE DESNITY** 1.0

SOLUBILITY IN WATER

PARTITION COEFFICIENT n-

OCTANOL/WATER

AUTOIGNITION TEMPERATURE

DECOMPOSITION TEMPERATURE

Soluble in water Not available

: Not available Not available

SECTION 10 – STABILITY AND REACTIVITY

STABILITY Stable under recommended storage conditions. HAZARDOUS CONDITONS TO No decomposition if used according to specifications

AVOID INCOMPATIBLE MATERIALS Keep away from strong acids.

HAZARDOUS DECOMPOSITION

PRODUCTS

No dangerous decomposition products known.

SECTION 11 – TOXICOLOGICAL INFORMATION

Ethylene Glycol Monobutyl Ether TOXICOLOGICAL INFORMATION

Oral LD50 Oral (rat): 5560 mg/kg. LC50 dermal and inhalation: Not listed. **ACUTE TOXICITY**

CHRONIC EFFECTS Prolonged absorption causes liver and kidney damage, and red cell hemolysis (blood

in urine) in laboratory animals; no such effects have been seen in humans.

SENSITISATION Not a sensitizer.

CARCINOGENICITY No component of this product present at levels greater than or equal to 0.1% is

identified as probable or confirmed human carcinogen by IARC, ACGIH, NTP, and

OSHA.

TOXICOLOGICAL INFORMATION : Alcohols Ethoxylated

ACUTE TOXICITY : LD50 Oral (rat): 1,378 mg/kg,

INHALATION LC50 No data available.

DERMAL LD50 LD50 Dermal (rat): > 5,000 mg/kg. **PRIMARY SKIN IRRITATION** (Rabbit) Moderate to severely irritating.

PRIMARY EYE IRRITATION (Rabbit) Severely irritating.

TOXICOLOGICAL INFORMATION **Sodium Octane Sulfonate**

ACUTE TOXICITY IRRITATION

INHALATION

Inhalation may cause pain in respiratory system, sneezing coughing and difficulty in

CARCINOGENICITY : This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

TOXICOLOGICAL INFORMATION : **Sodium Thiosulfate**

ACUTE TOXICITY LD50: Not available. May cause irritation to Eyes, skin and Respiratory tract. This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA. CARCINOGENICITY

MUTAGENICITY No data available. **SENSITISATION** Not a sensitizer.

SECTION 12 – ECOLOGICAL INFORMATION

SAFETY DATA SHEET **FABRICMASTER FF**

ECOLOGICAL INFORMATION

ECOTOXICITY

Ethylene Glycol Monobutyl Ether

This product cannot accumulate in living tissue; diluted, this product is readily and rapidly in a wastewater treatment facility; in BOD test, 88% degraded in 28 says;

half-life in air estimated as 10 hours.

ECOLOGICAL INFORMATION

ECOTOXICITY

Alcohols Ethoxylated

LC50 Rainbow Trout: 1-10 mg/l, 96hr. Value estimated from tests on similar

products.

LC50 Fathead Minow: 6 mg/l, 96hr. Value estimated from tests on similar products.

BIODEGRADABILITY PERSISTENCE AND

No data available.

Readily biodegradable.

DEGRADABILITY

BIOACCUMULATIVE POTENTIAL

No data available.

ECOLOGICAL INFORMATION

ACUTE TOXICITY FISH, DAPHNIA, BACTERIA

Sodium Octane Sulfonate

No ecological data available for this material.

ECOLOGICAL INFORMATION ECOTOXICITY PERSISTENCE AND **DEGRADABILITY**

No data available.

Sodium Thiosulfate

No data available.

MOBILITY

: No data available.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

: This product must be disposed of in accordance with Federal, state, and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.

SECTION 14 – TRANSPORTATION INFORMATION

DOT/IMDG/ IATA PROPER

SHIPPING NAME

: Not Hazardous

HAZARD CLASS AND LABEL

Not Applicable. **UN NUMBER** Not Applicable. **PACKAGING GROUP** Not Applicable. **EPA REPORTABLE QUANTITY** Not Applicable.

(RQ)

MARINE POLLUTANT Not listed. **EMERGENCY RESPONSE GUIDE** : Not Applicable.

SECTION 15 - REGULATORY INFORMATION

U.N. GHS CLASSIFICATION & LABELING INFORMATION: See Section 2 for GHS Hazard Information.

U.S. FEDERAL REGULATORY INFORMATION:

LISTED CARCINOGEN

TSCA STATUS The ingredients of this product are listed in TSCA inventory (40CFR 710.)

SARA SECTION 302 No chemicals in this material are subject to the reporting requirements of SARA Title

III, Section 302.

SAFETY DATA SHEET FABRICMASTER FF

SARA SECTION 312 : N/A

SARA SECTION 313 : This material does not contain any chemical components with known CAS numbers

that exceed the threshold (De Minimis) reporting levels established by SARA Title III,

Section 313.

NFPA HEALTH : 2 NFPA FLAMMABILITY : 0 NFPA REACTIVITY : 0

CANADIAN REGULATORY INFORMATION:

WHMIS CATEGORY : D2B: Materials that cause other toxic effects (TOXIC).

: Listed



DOMESTIC SUBSTANCES LIST

(DSL)

INGREDIENT DISCLOSURE LIST : Listed

SECTION 16 – OTHER INFORMATION

DISCLAIMER : The information contained herein has been compiled from sources believed to be

realiable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Hydramaster Corp. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and

recommendations in the specific context of their intended use.

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act.

EINECS : European Inventory of Existing Commercial Chemical Substances

IMDG
 International Maritime Code for Dangerous Goods
 IARC
 International Agency for Research on Cancer
 IATA
 International Air Transportation Association

ACGIH : American Conference of Governmental Industrial Hygienists

NFPA : National Fire Protection Association (USA)

NTP : National Toxicology Program

SARA : Superfund Amendments and Reauthorization Act

TSCA : Toxic Substances Control Act

HMIS : Hazardous Materials Identification System (USA)WHMIS : Workplace Hazardous Materials Information System

LC50 : Lethal concentration, 50 percent

LD50 : Lethal dose, 50 percent

STOT : Systemic Target Organ Toxicity

DATE PREPARED : APR 9, 2018 **DATE REVISED** : NOV 7, 2022