













Focus II Mid-Size How To

Prepare for use

1		2		3	
	This is how the machine should look when you enter the room.		Unplug battery charger. Wrap cord accordingly.		Inspect recovery tank, empty debris catch cage then lower the lid.
4		5		6	
	Fill solution tank with water (do not exceed 130°F). Add appropriate cleaning chemical.		Add clean water to tank. Lift lid and add detergent cartridge. Do not mix detergent in the tank (<i>machines with chemical mixing system only</i>).		Inspect squeegee blade, install squeegee on machine and attach recovery hose to the squeegee inlet.
7		8		9	
	Inspect brush or pad.		Install brush or pad-holder under the deck.		Install brush for Cylindrical models.
10		11		12	
	Turn on machine. Verify there is enough battery power to complete job.		Use yellow palm switches to move forward and white button for reverse. Adjust speed of machine as needed.		Review operator controls. Prepare for use.





Focus II Mid-Size How To

Scrubbing



1	 <p>Adjust speed if needed. Lower squeegee.</p>	2	 <p>While in motion, press the one touch scrub button then adjust the solution flow rate.</p>	3	 <p>Release palm switches to pause. Press reverse button for backward motion. Press one scrub button to stop scrubbing.</p>
4	 <p>Use the extra pressure button for heavy soiled areas (disc and Boost machines only).</p>	5	 <p>Vacuum on/off. Vacuum only to pick up water. Turn vacuum off for double scrubbing.</p>	6	 <p>Install red pad and maroon pad for chemical free stripping. Add plain water to the solution tank.</p>
7	 <p>Pre-wet stripping pad. Adjust to slow speed</p>	8	 <p>Lower squeegee and engage extra pressure to begin scrubbing</p>	9	 <p>Flip pad when it becomes worn. Scrub floor before laying down new finish.</p>

Focus II Mid-Size How To




Storing the Machine & Daily Maintenance

<p>1</p>  <p>Empty recovery tank and solution tank. Empty water in suitable drain or bucket. Rinse recovery tank. Empty and rinse debris catch cage. Check gasket cover.</p>	<p>2</p>  <p>Remove, inspect and rinse squeegee blades. Remove, inspect and rinse pads. Hang to dry.</p>	<p>3</p>  <p>Remove, inspect and rinse cylindrical brush. Empty debris hopper. Charge batteries and wipe down exterior.</p> 
---	--	--

Weekly Maintenance

<p>1</p>  <p>Inspect water level in batteries <i>(add distilled water if needed – do not overfill)</i>.</p>	<p>2</p>  <p>Remove and rinse solution filter.</p>	<p>3</p>  <p>Purge the chemical mixing system <i>(if equipped)</i>.</p>
---	---	---

Occasional Maintenance

<p>1</p>  <p>Lubricate machine; equalize batteries – charge fully then recharge two or more times.</p>	<p>2</p>  <p>Annually or after 300 hours inspect carbon brushes on the vacuum motor <i>(performed by Authorized Clarke Service Center)</i>.</p>	<p>3</p>  <p>Annually or after 500 hours inspect carbon brushes on the drive and brush motors <i>(performed by Authorized Clarke Service Center)</i>.</p>
---	--	---