SAFETY DATA SHEET

GreaseBreaker

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME SYNONYMS PRODUCT USE SUPPLIER	Product is a mixture: No synonyms are available. Flammable Material
SUPPLIER'S ADDRESS EMERGENCY RESPONSE PHONE NUMBER	1500 Industry St. Suite 300 Everett, WA 98203 (425) 775-7272 PERS: 1-800-633-8253

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS U.S. – CLASSIFICATION	:	H302	Harmful if swallowed.
	:	H315	Causes skin irritation
	:	H319	Causes serious eye irritation

LABEL ELEMENTS	:	GHS – US HAZARD	The product is classified and labeled according to the
		PICTOGRAMS	Globally Harmonized System (GHS).
HAZARD PICTOGRAMS	:		¥2

SIGNAL WORD	:	WARNING	
HAZARD STATEMENTS (GHS-US)			
	:	H226	Flammable liquid and vapor
	:	H303	May be harmful if swallowed.
	:	H315	Causes skin irritation.

•	H317	May cause an allergic skin reaction
•	11317	way cause an anergic skin reaction

		-
H319	Causes seriou	is eve irritation.

: Very toxic to aquatic life. : H400

PRECAUTIONARY STATEM	/IENTS (SGS-US)	
PREVENTION	: P101	If medical advice is needed, have product container or label at hand.
	: P102	Keep out of reach of children.
	: P103	Read label before use.
	: P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking.
	: P233	Keep container tightly closed.
	: P240	Ground/bond container and receiving equipment.
	: P241	Use explosion proof electrical/ventilation/lightequipment
	: P242	Use only non-sparking tools.
	: P243	Take precautionary measures against static discharge.
	: P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
	: P264	Wash skin and contaminated clothing thoroughly after handling.
	: P270	Do not eat, drink, or smoke when using this product.
	: P271	Use only outdoors or in a well-ventilated area.
	: P280	Wear suitable protective gloves / protective clothing / eye protection /
		face protection.
RESPONSE	: P305+P351 +P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
	: P337+P313	If eye irritation persists, get medical attention.

STORAGE	 P303+P361 +351 P304+P340 P337+P313 P403+P233 P403+P235 	Rinse skin with water/shower. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable to breathing. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed.
	: P405	Store locked up.
DISPOSAL	: P501	Dispose of contents/container in accordance with local/regional/national/international regulations
OSHA HAZARDS	: D-Limonen	e: Combustible Liquid, Target Organ Effect, Skin Sensitizer, Irritant
TARGET ORGANS	: Not applica	
	: Not applica	ble.
CLASSIFICATION SYSTEM	: NFPA/HMIS	S Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.
NFPA RATINGS (SCALE 0-4)	: Health = 2,	Fire = 0, Reactivity = 0
HMIS RATINGS (SCALE 0-5)	: Health = 2,	Fire = 0, Reactivity = 0

SECTION 3 – COMPOSITON/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTIC DESCRIPTION

MixturesMixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EC #	GHS CLASS
D-Limonene (Citrus Terpenes)	40-50	5989-27-5	227-813-5	Flam Liq Cat 3, Acute Tox Oral Cat 5,
				Skin Irrit Cat 2, Eye Irrit Cat 2A,
				Skin Sens Cat 1, Acute Tox Aquatic Cat 1
Mineral Spirits Odorless	40-50	64741-65-7	265-067-2	Flam Liq Cat 3, Acute Tox Inhal Cat 4,
		64742-48-9	265-150-3	Skin Irrit Cat 2, Eye Dam Cat 2B, STOT-SE
				Cat 3, Aspiration Haz Cat 1
Alcohols Ethoxylated	1-5	68439-46-3	Not Found	Eye Irrit Cat 2B

Irrit = Irritation, Cor = Corrosive, Dam = Damage, Cat = Category, Tox = Toxic, Sens = Sensitization, Flam = Flammable, STOT-SE = Specific Target Organ Toxicity-Single Exposure, Inhal = Inhalation.

SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES						
GENERAL	: If you feel unwell, seek medical advice. Show the label where possible. Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area					
EYE CONTACT	: Immediately flush eyes with low pressure water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, get immediate medical attention.					
SKIN CONTACT	: Remove contaminated clothing and shoes. Wash affected skin area with soap and water. If irritation persists, get immediate medical attention. Wash contaminated clothing before reuse.					
SWALLOWING (INGESTION)	: If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep airway clear and have victim lean forward to prevent aspiration. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate medical attention.					
INHALATION	: Remove to fresh air. If signs/symptoms continue, get medical attention. Give oxygen					

GreaseBreaker					
OTHER INSTRUCTIONS	or artificial respiration as needed. Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.				
	SECTION 5 – FIRE FIGHTING MEASURES				
EXTINGUISHING MEDIA CONDITIONS OF FLAMMABILITY SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS	Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide. Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water				
FURTHER INFORMATION HAZARDOUS COMBUSTION PRODUCTS	Use water spray to cool unopened containers. Carbon oxides				
	SECTION 6 – ACCIDENTAL RELEASE MEASURES				
PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES ENVIRONMENTAL PROCEDURES METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP	Do not inhale vapors, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact. Keep spilled material away from sewage/drainage systems and waterways. All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Collect with an electrically protected vacuum cleaner or by wet-brushing and place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.				
	SECTION 7 – HANDLING AND STORAGE				
<u> </u>					
PRECAUTIONS FOR SAFE HANDLING ENVIRONMENTAL PRECAUTIONS CONDITIONS FOR SAFE STORAGE	Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains. Keep container tightly closed in a cool, dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.				



SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

TLV (THRESHOLD LIMIT VALUE)

: The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short

term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH – TLV	ACGIH – STEL
D-Limonene (Citrus Terpenes)	Not Established	Not Established	Not Established
Odorless Mineral Spirits	400 ppm	Not Established	Not Established
Alcohols Ethoxylated	Not Established	Not Established	Not Established

EYE PROTECTION	:	Use chemical safety goggles and/or a full face-shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.
SKIN PROTECTION	:	Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron, or coveralls, as appropriate, to prevent skin contact.
RESPIRATORY PROTECTION	:	Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
HAND PROTECTION	:	Handle with gloves. Gloves must be inspected prior to use. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
APPROPRIATE ENGINEERING CONTROLS	:	General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.
ADDITIONAL MEASURES	:	Emergency eyewash and safety shower facilities should be available in the immediate work area.
REQUIRED WORK/HYGIENE	:	Wash hands thoroughly after handling. Keep away from all food stuffs, beverages, and feed. Do not eat, drink, or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Mostly clear colorless gel with citrus odor.ODOR: Mild odorODOR THRESHOLD: Not availablePH: N/AMELTING POINT/FREEZING: Not availablePOINT: Approx. 212° F.BOILING POINT: 118° F (48°C) closed cup.EVAPORATION RATE: Not availableFLAMMABILITY: Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT: 0.7 % (V)UPPER FLAMMABILITY LIMIT: 6.1 % (V)VAPOR DENSITY (AIR=1): Not availableRELATIVE DESNITY: 0.84SOLUBILITY IN WATER: Soluble in waterPARTITION COEFFICIENT n-: Not available
ODOR THRESHOLD:Not availablePH:N/AMELTING POINT/FREEZING:Not availablePOINT:Approx. 212° F.BOILING POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLASH POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
PH:N/AMELTING POINT/FREEZING:Not availablePOINT:Approx. 212° F.BOILING POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableSOLUBILITY IN WATER:Soluble in water
MELTING POINT/FREEZING POINT:Not availableBOILING POINT:Approx. 212° F.FLASH POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
POINTApprox. 212° F.BOILING POINT:118°F (48°C) closed cup.FLASH POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
BOILING POINT:Approx. 212° F.FLASH POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
FLASH POINT:118°F (48°C) closed cup.EVAPORATION RATE:Not availableFLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
EVAPORATION RATE: Not availableFLAMMABILITY: Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT: 0.7 % (V)UPPER FLAMMABILITY LIMIT: 6.1 % (V)VAPOR PRESSURE: Not availableVAPOR DENSITY (AIR=1): Not availableRELATIVE DESNITY: 0.84SOLUBILITY IN WATER: Soluble in water
FLAMMABILITY:Combustible liquid. By air or international: Flammable Liquid.LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
LOWER FLAMMABILITY LIMIT:0.7 % (V)UPPER FLAMMABILITY LIMIT:6.1 % (V)VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
UPPER FLAMMABILITY LIMIT : 6.1 % (V) VAPOR PRESSURE : Not available VAPOR DENSITY (AIR=1) : Not available RELATIVE DESNITY : 0.84 SOLUBILITY IN WATER : Soluble in water
VAPOR PRESSURE:Not availableVAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
VAPOR DENSITY (AIR=1):Not availableRELATIVE DESNITY:0.84SOLUBILITY IN WATER:Soluble in water
RELATIVE DESNITY : 0.84 SOLUBILITY IN WATER : Soluble in water
SOLUBILITY IN WATER : Soluble in water
PARTITION COEFFICIENT n- : Not available
OCTANOL/WATER
AUTOIGNITION TEMPERATURE : Not available
DECOMPOSITION : Not available
TEMPERATURE

SECTION 10 – STABILITY AND REACTIVITY

STABILITY HAZARDOUS CONDITONS TO AVOID INCOMPATIBLE MATERIALS HAZARDOUS DECOMPOSITION PRODUCTS	 Stable under recommended storage conditions. Heat, flames, and sparks. Extreme temperatures and direct sunlight. Strong oxidizing agents. Carbon oxides are expected to be, under fire conditions, the primary hazardous decomposition products.
	SECTION 11 – TOXICOLOGICAL INFORMATION
TOXICOLOGICAL INFORMATION ACUTE TOXICITY IRRITATION BIOACCUMULATION CARCINOGENICITY	 D-Limonene (Citrus Terpenes) LD50 Oral (rat): >5000 mg/kg. LD50 Dermal (rabbit): >5,000 mg/kg, RD50 Inhalation (mice): > 1,000 mg/kg. Prolonged or repeated exposure can cause drying or dermatitis of skin. No appreciable bio-concentration is expected in the environment. This product is not classified as a carcinogen by OSHA, IARC, ACGIH or NTP.
TOXICOLOGICAL INFORMATION ACUTE TOXICITY	 Odorless Mineral Spirits LD50 Oral (rat): > 2,000 mg/kg. LD50 Dermal (rabbit): > 2,000 mg/kg. LC50 Inhalation
IRRITATION EFFECTS	 (rat): Near saturated vapor concentration: 1 hr. EYE EFFECTS: Essentially non-irritating to eyes. SKIN EFFECTS: May cause moderate irritation to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. REPEATED DOSE EFFECTS: Cardiovascular system: chronic abuse of similar materials has been associated with irregular heart rhythms and cardiac arrest. Central nervous system: repeated exposure affects the nervous system. Kidney: caused kidney effects in male rats which are not considered relevant to humans.
BIOACCUMULATION CARCINOGENICITY	No appreciable bio-concentration is expected in the environment.This product is not classified as a carcinogen by OSHA, IARC, ACGIH or NTP.
TOXICOLOGICAL INFORMATION ACUTE TOXICITY INHALATION LC50 DERMAL LD50 PRIMARY SKIN IRRITATION PRIMARY EYE IRRITATION	 Alcohols Ethoxylated LD50 Oral (rat): 1,378 mg/kg, No data available. LD50 Dermal (rat): > 5,000 mg/kg. (Rabbit) Moderate to severely irritating. (Rabbit) Severely irritating.
	SECTION 12 – ECOLOGICAL INFORMATION
ECOLOGICAL INFORMATION ECOTOXICITY MOBILITY PERSISTENCE AND DEGRADABILITY	 D-Limonene (Citrus Terpenes) There is no information available currently for this product. However, a spill may produce significant toxicity to aquatic organisms and ecosystems. Some studies have shown that certain bacteria and fungi can degrade citrus terpenes, decreasing their toxicity to fish. When spilled, this product may act as an oil, causing a film, sheen, emulsion, or sludge at or beneath the surface of a body of water Citrus Terpenes volatize rapidly. Readily biodegradable.

BIOACCUMULATIVE POTENTIAL : Bio-concentration is not expected to occur.

ECOLOGICAL INFORMATION:Odorless Mineral SpiritsACUTE TOXICITY:Acute Toxicity for Naphthat

: Acute Toxicity for Naphtha (Petroleum), Heavy Alkylate:

	Fish: Low toxicity: LC/EC/IC50 greater than 1000 mg/l		
	Aquatic Invertebrates: Low toxicity: LC/EC/IC50 greater than 1000 mg/I		
	Algae: Low toxicity: LC/EC/IC50 greater than 1000 mg/l		
	Microorganisms: Low toxicity: LC/EC/IC50 greater than 1000 mg/l		
ENVIRONMENTAL DATA	: Oxidizes rapidly by photo-chemical reactions in air. Expected to be not inherently biodegradable.		
ECOTOXICOLOGICAL INFORMATION	: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.		
BIOACCUMULATIVE POTENTIAL	: Has potential to bio-accumulate.		
ECOLOGICAL INFORMATION	: Alcohols Ethoxylated		
ECOTOXICITY	: LC50 Rainbow Trout: 1-10 mg/l, 96hr. Value estimated from tests on similar products.		
	LC50 Fathead Minow: 6 mg/l, 96hr. Value estimated from tests on similar products.		
BIODEGRADABILITY PERSISTENCE AND	 Readily biodegradable. No data available. 		
DEGRADABILITY	: No data available.		
BIOACCUMULATIVE POTENTIAL	: No data available.		
SECTION 13 – DISPOSAL CONSIDERATIONS			
WASTE DISPOSAL	: This product must be disposed of in accordance with Federal, state, and local environmental regulations. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.		
	SECTION 14 – TRANSPORTATION INFORMATION		
DOT/IMDG/ IATA PROPER SHIPPING NAME	: UN1993, Combustible Liquids, N.O.S. (Petroleum Distillates, Terpene Hydrocarbons) 3, PGIII		
	(When shipped by air or international)		
HAZARD CLASS AND LABEL	: 3 (Flammable Liquid) (When shipped by air or international)		
UN NUMBER	: UN1993 (When shipped by air or international)		
PACKAGING GROUP	: PG III (when shipped air or international)		
EPA REPORTABLE QUANTITY (RQ)	: Not Applicable.		
MARINE POLLUTANT	: D-limonene: Dipentene,		
EMERGENCY RESPONSE GUIDE	: ERG-128		
	SECTION 15 – REGULATORY INFORMATION		

SECTION 15 – REGULATORY INFORMATION

U.N. GHS CLASSIFICATION & LABELING INFORMATION: See Section 2 for GHS Hazard Information.

U.S. FEDERAL REGULATORY INFORMATION:		
LISTED CARCINOGEN	: Not listed.	
TSCA STATUS	: The ingredients of this product are listed in TSCA inventory (40CFR 710.)	
SARA SECTION 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA SECTION 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
CERCLA	: No chemicals in this material with known CAS numbers are subject to the reporting requirements of CERCLA.	
NFPA HEALTH	: 2	

NFPA FLAMMABILITY	2	
NFPA REACTIVITY	0	
CANADIAN REGULATORY INFORM	TION:	
WHMIS CATEGORY	B3: Combustible Liquid (D-Limonene & Mineral Odorless).	Spirits
	D2B: Materials that cause other toxic effects (TOXI Limonene	C). D-
DOMESTIC SUBSTANCES LIST (DSL)	Listed	\mathbf{O}
INGREDIENT DISCLOSURE LIST	Listed	

SECTION 16 – OTHER INFORMATION

DISCLAIMER	:	The information contained herein has been compiled from sources believed to be realiable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Hydramaster Corp. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.
CERCLA	:	Comprehensive Environmental Response, Compensation, and Liability Act.
EINECS	:	European Inventory of Existing Commercial Chemical Substances
IMDG	:	International Maritime Code for Dangerous Goods
IARC	:	International Agency for Research on Cancer
ΙΑΤΑ	:	International Air Transportation Association
ACGIH	:	American Conference of Governmental Industrial Hygienists
NFPA	:	National Fire Protection Association (USA)
NTP	:	National Toxicology Program
SARA	:	Superfund Amendments and Reauthorization Act
TSCA	:	Toxic Substances Control Act
HMIS	:	Hazardous Materials Identification System (USA)
WHMIS	:	Workplace Hazardous Materials Information System
LC50	:	Lethal concentration, 50 percent
LD50	:	Lethal dose, 50 percent
STOT	:	Systemic Target Organ Toxicity
DATE PREPARED	:	JAN 12, 2018
DATE REVISED	:	NOV 7, 2022