

Important notice to purchaser: The manufacturer and seller warrant that the chemical contained herein conforms to its standard specifications. Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The product contains oxidizers and may alter or remove the original color of the carpet it is being applied to. Use only as a last resort and with the customer's permission and understanding of this risk.

www.HydraMaster.com
Please Rinse and Recycle this Container

GHS U.S. – CLASSIFICATION: WARNING

Harmful if swallowed. Causes skin irritation
Causes serious eye irritation.



PRECAUTIONARY STATEMENTS (GHS-US)

The product is classified and labeled according to the Globally Harmonized System (GHS)
If medical advice is needed, have product container or label at hand. Keep out of reach of children.
Prolonged skin contact causes severe skin burns.
Eye contact causes severe eye damage.
May cause respiratory irritation.
Wear gloves and safety glasses when handling to avoid any contact with eyes and contact with skin in concentrate form.
Use only in well ventilated areas.
In case of eye contact, immediately flush with plenty of water and seek immediate medical attention.
In case of skin irritation, flush with plenty of water.
If ingested, drink large quantities of water and seek medical attention.
Remove to fresh air in case of inhalation.

Before using, read materials safety data sheet for this product.

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions:

0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4): Health = 2, Fire = 0, Reactivity = 0

HMIS RATINGS (SCALE 0-5): Health = 2, Fire = 0, Reactivity = 0

Visit www.hydramaster.com/sds for additional safety and regulatory information.

Part #

950-156-A 1-6.5 # jar
950-156-B case of 4X6.5#

HydraMaster

11015 47th Avenue West
Mukilteo, WA 98275
425.775.7272

Net Contents: 6.5 Pounds (2.95 Kg)



Cleaning Agent for Trashed and Grungy Tile and Concrete Floors

GRUNGESLAYER is a powder prespray agent to be applied prior to cleaning with a hard surface extraction wand or tool on neglected tile and concrete floors that have a high level of grunge, soil and grease build-up. It slays the grime and restores the floor to a clean and shiny condition.

GRUNGE SLAYER™



Directions:

1. Read entire label before using. Use only as directed. Always pretest surface with cleaning solution for color-fastness prior to cleaning. Ensure work area is well-ventilated during application. Keep children and pets out of the area during application and drying. GRUNGESLAYER is not recommended for cleaning natural stone floors.
2. This product is ultra-concentrated. For normal soiling, mix 2 ounces of GRUNGESLAYER powder with one gallon of warm or hot water into a professional sprayer. For extreme soiling, mix three to four ounces of powder with a gallon of warm or hot water into a professional sprayer. For application through a Inline Injection Sprayer, mix 12 oz. of powder and fill container with water. Use 4:1 dilution.
3. Apply mixed solution with sprayer evenly and liberally across surface to be cleaned. You can use a pump-up sprayer or a battery powered sprayer. If preferred, you can apply mixed solution with a damp mop, sponge, or other appropriate professional equipment. If using a mop for solution application and surface cleaning, change your mop water often to make sure that soil is not re-deposited.
4. Allow for 3-5 minutes of dwell time. For concrete, if stains have been deeply absorbed, allow longer dwell time so the solution has time to reach into the concrete pores and crevices.
5. For best results, agitate and extract cleaning solution using warm or hot water and a rotary agitation hard surface cleaner such as the EVOLUTION RX12 Rotary Hard Surface Extraction Tool, the RX-20 Rotary Jet Extraction Tool with

- hard floor attachments, or rotary or stationary hard surface cleaning extraction wands For tight spaces or especially sensitive surfaces, use a hard surface cleaning wand, or simply mop to rinse with clean warm or hot water.
6. When area has been rinsed thoroughly. Allow floor to dry.
7. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

For use as a carpet cleaning solution booster/additive

1. Mix two ounces of GRUNGESLAYER with each gallon of mixed prespray (traffic lane cleaner, preconditioner) solution. This mixture is not recommended for wool carpeting or residential nylon carpets that are being properly maintained.
2. Always pretest surface with boosted cleaning solution for color-fastness prior to cleaning.
3. Proceed to apply the prespray and continue cleaning in accordance with the directions of the prespray.

Direcciones:

1. Este producto es ultraconcentrado. Para una suciedad normal, mezcle 2 onzas de polvo GRUNGESLAYER con un galón de agua tibia o caliente en un rociador profesional. Para suciedad extrema, mezcle de tres a cuatro onzas de polvo con un galón de agua tibia en un rociador profesional. Para la aplicación a través de un pulverizador de inyección en línea, mezcle 12 oz. de polvo y llenar el recipiente con agua. Use dilución 4: 1.

2. Aplique una solución mixta con el rociador de manera uniforme y abundante sobre la superficie a limpiar. Puede usar un rociador de bombeo o un rociador a batería. Si lo prefiere, puede aplicar una solución mixta con un trapeador húmedo, una esponja u otro equipo profesional apropiado. Si usa un trapeador para la aplicación de la solución y la limpieza de la superficie, cambie el agua del trapeador con frecuencia para asegurarse de que el suelo no se vuelva a depositar.
3. Permita de 3 a 5 minutos de tiempo de permanencia. Para el concreto, si las manchas se han absorbido profundamente, espere más tiempo para que la solución tenga tiempo de penetrar en los poros y grietas del concreto.
4. Para obtener los mejores resultados, agite y extraiga la solución de limpieza con agua tibia o caliente y un limpiador de superficies duras de agitación rotativa, como la Herramienta de extracción de superficie dura rotativa EVOLUTION RX12, la Herramienta de extracción de chorro rotativo RX-20 con accesorios para pisos duros, o Varillas de extracción de limpieza de superficies duras estacionarias Para espacios reducidos o superficies especialmente sensibles, utilice una varilla de limpieza de superficies duras o simplemente trapee para enjuagar con agua tibia o caliente limpia.
5. Cuando el área ha sido enjuagada completamente. Permita que el piso se seque.
6. Para un secado más rápido, especialmente en ambientes húmedos, considere el uso de un motor de aire axial, centrifugo o descendente después de la limpieza.

