KARCHER

makes a difference





RUGGED AND POWERFUL COLD WATER CLEANING.

Roll cage, gas/diesel-powered, cold water pressure washers.

BR SHARK SERIES AND D CAGE



Extra rugged and powerful.

Our roll cage models are the most powerful units in our cold water line, with cleaning power of up to 5000 PSI. Protected by either a rugged powder coated roll cage built of 1-1/4" steel or a corrosion-resistant stainless steel cage, these units feature powerful Vanguard, Honda or Kohler engines, tri-plunger oil bath Kärcher pumps, flat-free tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys.







1 Powerful and durable

- Safety thermal pump saver valve protects against hot-water damage by venting recirculated water.
- Rugged roll cage and chassis made of 1 1/4-inch steel and powder coated with an epoxy finish for all-weather protection for BR models.
- Corrosion-resistant stainless steel frame for D cage model only.
- Reliable Honda, Vanguard or new Kohler engine model HD 3.4/30 D Cage (Shown above)
- Industrial-grade, tri-plunger, oil-bath Kärcher high pressure pump with forged brass head and ceramic pistons; backed by 7-year warranty.
- Notched V-belts and cast-iron pulleys reduce belt slippage and provide longer pump life.
- 50' durable wire-braid hose rated for 3000 or 5000 PSI; with hose guard for burst protection
- Inlet strainer protects pump from debris in the water source.

2 Smart features

- Five conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Totally enclosed, OSHA-compliant, high-impact polyethylene belt guard and easy-to-adjust belt tension device.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

3 Outstanding mobility

- Heavy-duty lifting beam for ease in loading and transporting.
- Flat-free tires on all models for easy maneuvering on any surface, especially surfaces with nails and sharp debris.

TECHNICAL DATA AND EQUIPMENT

Features

Belt-drive

- Rugged steel chassis & roll cage
- Honda, Vanguard or new Kohler engine model HD 3.4/30 D Cage
- Cleaning power up to 5000 PSI
- Electric start on dual-axle models*
- Industrial crankcase pump with U-Seal technology
- Flat-free tires

Technical data

Model	Part No.	GPM	PSI	Drive	cc	Engine	Pump	Ship Weight (Ibs)	Ship Dimensions (L x W x H) inches
BR-373537	1.107-150.0	3.7	3500	Belt	389	Honda GX 390	KM Crankcase	350	42 x 26 x 30
BR-404027	1.107-151.0	4.0	4000	Belt	479	Vanguard 16	KT Crankcase	470	42 x 26 x 30
BR-405037E*	1.107-147.0	4.0	5000	Belt	688E	Honda GX 630	KX Crankcase	495	42 x 26 x 30
BR-455037E*	1.107-148.0	4.5	5000	Belt	688E	Honda GX 690	KX Crankcase	500	42 x 26 x 30
HD 3.4/30 D Cage	1.107-373.0	3.4	3000	Belt	442	Kohler KD440	KX Crankcase	195	50 x 40 x 50

Options (field installed)							
Order No.	Description						
9.801-028.0	100' EZEE Hose Reel kit, single axle (hose not included)						
9.801-029.0	100' Hose Reel kit, 5000 psi, double axle (hose not included)						
8.750-682.0	100' Capacity Hose Reel fixed base (for HD 3.4/30 D Cage model only)						
8.929-070.0	Skid Feet (for HD 3.4/30 D Cage model only)						

Please contact us for more information:

North America

4555 Airport Way Denver, CO 80239 U.S.A. Phone 888-805-9852

Fax 800-248-8409

www.karcher.com/us

Kärcher Canada

275 Pendant Drive Mississauga, ON L5T 2W9 Canada

Tel.905-364-5006Fax905-672-3155

www.karcher.ca