

A cost-efficient cleaning solution

Enhance cleaning productivity with our brand new stand-up automatic scrubber, the Advance SC1500™. Designed to deliver superior cleaning performance, the SC1500 stand-up scrubber provides a flexible, extremely maneuverable and compact solution for small to medium-sized areas. Plus, with a high-capacity tank and high scrub speed capabilities, the SC1500 covers more surface faster while maximizing your bottom line. To satisfy both daily and deep scrubbing applications, the SC1500 is available in a 20 inch disc model. Spend more time on the floor with the SC1500's large 12 gallon solution tank and low flow rate, which can provide up to 75 minutes of scrub time without refilling. Increased down pressure at 75 pounds enables one pass cleaning for efficient cleaning results.

The SC1500 ensures consistent, reliable cleaning with solution flow rate control right at your fingertips. Select from low, medium or high to match the job at hand without stopping the machine. This not only minimizes chemical and water waste but also reduces time spent on dump and refills. For simple operation, all scrubbing parameters—detergent strength, brush pressure, solution flow and vacuum—are all controlled with a single button and are clearly displayed on the easy-to-read, LCD graphical display. Clean green and still meet the highest expectations for clean floors with the standard, onboard EcoFlex System™.




The EcoFlex System controls the consumption of water, detergent and energy so effectively that real savings can be gained without compromising performance. With a single button, effortlessly switch between water-only cleaning or select from weak to strong cleaning intensities to match cleaning performance to the soil on the floor and the required level of clean. More soil? No problem. Activate the “burst of power” for extra cleaning performance and easily return to the original settings for minimum usage of water, detergent and power.



Picture shown may not represent model quoted

- Simple, intuitive controls minimize operator training
- Safety dead-man switch and GO pedal provides easy-to-control operation
- Quiet mode for daytime cleaning and cleaning of noise-sensitive areas
- EcoFlex™ onboard detergent system provides flexible cleaning performance
- Large recovery tank opening, complete draining and smooth interior for easy cleaning




● Standard equipment

Included accessories		Ref. no.	Min. required	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
Ecoflex System						
	ECOFLEX BOTTLE ASSY	56104190	0	●	●	●
Pad Holder						
	PAD HOLDER-20 3 LUG	56505790	0	●	●	
Disc Brush 510 mm						
	DISC BRUSH-20 MIDLITE 3 LUG	56505798	0			
Battery						

A cost-efficient cleaning solution

Included accessories	Ref. no.	Min. required	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
BATTERY 12V 140AH AGM	56380239	0		•	

• Standard equipment

Included accessories	Ref. no.	Min. required	SC1500 20R ECOFLEX A150 OBC PH	SC1500 20D ECOFLEX W208 OBC MGB	SC1500 20D ECOFLEX A150 OBC MGB
Ecoflex System					
 ECOFLEX BOTTLE ASSY	56104190	0	•	•	•
Pad Holder					
 PAD HOLDER-20 3 LUG	56505790	0			
Disc Brush 510 mm					
 DISC BRUSH-20 MIDLITE 3 LUG	56505798	0		•	•
Battery					
BATTERY 12V 140AH AGM	56380239	0	•		•

Model	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
Ref. no.	56104010	56104011	56104012

PRODUCT FEATURES

Polyurethane front & rear wheels	•	•	•
Tilting recovery tank	•	•	•
Ecoflex installed	•	•	•
Silent mode	•	•	•
Safety Dead-man Switch	•	•	•
Wrap-around Squeegee	•	•	•
Rear-fill solution tank	•	•	•
Front Solution fillport	•	•	•
Large recovery tank opening	•	•	•

A cost-efficient cleaning solution

Model	SC1500 20R ECOFLEX A150 OBC PH	SC1500 20D ECOFLE W208 OBC MGB	SC1500 20D ECOFLE A150 OBC MGB
Ref. no.	56104013	56104014	56104015
PRODUCT FEATURES			
Polyurethane front & rear wheels	•	•	•
Tilting recovery tank	•	•	•
Ecoflex installed	•	•	•
Silent mode	•	•	•
Safety Dead-man Switch	•	•	•
Wrap-around Squeegee	•	•	•
Rear-fill solution tank	•	•	•
Front Solution fillport	•	•	•
Large recovery tank opening	•	•	•
Technical specifications			
	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
Drive motor hp (W)	0.375 hp (280 W)	0.375 hp (280 W)	0.375 hp (280 W)
Max. transport speed mph (km/h)	3 mph (4.8 kph)	3 mph (4.8 kph)	3 mph (4.8 kph)
Voltage (V)	24 V	24 V	24 V
Sound pressure level (dB(A))	63 db A/ .029344 μ Pa	63 db A/ .029344 μ Pa	63 db A/ .029344 μ Pa
Solution tank capacity gal (l)	12 gal (45 L)	12 gal (45 L)	12 gal (45 L)
Min. aisle turn (cm)	59.5 in (151 cm)	59.5 in (151 cm)	59.5 in (151 cm)
Recovery tank capacity gal (l)	12.5 gal (47 L)	12.5 gal (47 L)	12.5 gal (47 L)
Gross vehicle weight lbs (kg)	718 lb (326 kg)	718 lb (326 kg)	719 lb (326 kg)
Length	48.5 in (123.2 cm)	48.5 in (123.2 cm)	48.5 in (123.2 cm)
Width	24 in (61 cm)	24 in (61 cm)	24 in (61 cm)
Height	52.5 in (133.4 cm)	52.5 in (133.4 cm)	52.5 in (133.4 cm)
Scrub head	Disc	Disc	REV™
Vacuum motor	0.66 hp (492 W) 3- stage	0.66 hp (492 W) 3- stage	0.66 hp (492 W) 3- stage
Scrub path	20 in (51 cm)	20 in (51 cm)	20 in (51 cm)
Squeegee width	26.5 (67.3 cm)	26.5 (67.3 cm)	26.5 (67.3 cm)
Scrub motor	0.51 hp (380 W)	0.51 hp (380 W)	0.75 hp (559 W)
Scrub motor RPM	140	140	2,250
Low Scrub Pressure Max	51 lb (23 kg)	51 lb (23 kg)	64 lb (29 kg)
High scrub pressure max.	75 lb (34 kg)	75 lb (34 kg)	88 lb (40 kg)
Max. scrub speed	2.6 mph (4.2 kph)	2.6 mph (4.2 kph)	2.6 mph (4.2 kph)
Max. coverage	26,400 sq ft (2,453 sq m)	26,400 sq ft (2,453 sq m)	26,400 sq ft (2,453 sq m)








A cost-efficient cleaning solution

Technical specifications	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
Low flow rate	0.16 gal/min (0.6 L/min) or 75 minutes per solution tank	0.16 gal/min (0.6 L/min) or 75 minutes per solution tank	0.11 gal/min (0.4 L/min) or 109 minutes per solution tank
Medium flow rate	0.35 gal/min (1.3 L/min) or 34 minutes per solution tank	0.35 gal/min (1.3 L/min) or 34 minutes per solution tank	0.16 gal/min (0.6 L/min) or 75 minutes per solution tank
High flow rate	0.5 gal/min (1.9 L/min) or 24 minutes per solution tank	0.5 gal/min (1.9 L/min) or 24 minutes per solution tank	0.23 gal/min (0.9 L/min) or 52 minutes per solution tank







Technical specifications	SC1500 20R ECOFLEX A150 OBC PH	SC1500 20D ECOFLE W208 OBC MGB	SC1500 20D ECOFLE A150 OBC MGB
Drive motor hp (W)	0.375 hp (280 W)	0.375 hp (280 W)	0.375 hp (280 W)
Max. transport speed mph (km/h)	3 mph (4.8 kph)	3 mph (4.8 kph)	3 mph (4.8 kph)
Voltage (V)	24 V	24 V	24 V
Sound pressure level (dB(A))	63 db A/ .029344 μ Pa	63 db A/ .029344 μ Pa	63 db A/ .029344 μ Pa
Solution tank capacity gal (l)	12 gal (45 L)	12 gal (45 L)	12 gal (45 L)
Min. aisle turn (cm)	59.5 in (151 cm)	59.5 in (151 cm)	59.5 in (151 cm)
Recovery tank capacity gal (l)	12.5 gal (47 L)	12.5 gal (47 L)	12.5 gal (47 L)
Gross vehicle weight lbs (kg)	719 lb (326 kg)	718 lb (326 kg)	718 lb (326 kg)
Length	48.5 in (123.2 cm)	48.5 in (123.2 cm)	48.5 in (123.2 cm)
Width	24 in (61 cm)	24 in (61 cm)	24 in (61 cm)
Height	52.5 in (133.4 cm)	52.5 in (133.4 cm)	52.5 in (133.4 cm)
Scrub head	REV™	Disc	Disc
Vacuum motor	0.66 hp (492 W) 3-stage	0.66 hp (492 W) 3-stage	0.66 hp (492 W) 3-stage
Scrub path	20 in (51 cm)	20 in (51 cm)	20 in (51 cm)
Squeegee width	26.5 (67.3 cm)	26.5 (67.3 cm)	26.5 (67.3 cm)
Scrub motor	0.75 hp (559 W)	0.51 hp (380 W)	0.51 hp (380 W)
Scrub motor RPM	2,250	140	140
Low Scrub Pressure Max	64 lb (29 kg)	51 lb (23 kg)	51 lb (23 kg)
High scrub pressure max.	88 lb (40 kg)	75 lb (34 kg)	75 lb (34 kg)
Max. scrub speed	2.6 mph (4.2 kph)	2.6 mph (4.2 kph)	2.6 mph (4.2 kph)
Max. coverage	26,400 sq ft (2,453 sq m)	26,400 sq ft (2,453 sq m)	26,400 sq ft (2,453 sq m)
Low flow rate	0.11 gal/min (0.4 L/min) or 109 minutes per solution tank	0.16 gal/min (0.6 L/min) or 75 minutes per solution tank	0.16 gal/min (0.6 L/min) or 75 minutes per solution tank
Medium flow rate	0.16 gal/min (0.6 L/min) or 75 minutes per solution tank	0.35 gal/min (1.3 L/min) or 34 minutes per solution tank	0.35 gal/min (1.3 L/min) or 34 minutes per solution tank
High flow rate	0.23 gal/min (0.9 L/min) or 52 minutes per solution tank	0.5 gal/min (1.9 L/min) or 24 minutes per solution tank	0.5 gal/min (1.9 L/min) or 24 minutes per solution tank

A cost-efficient cleaning solution



● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories		Ref. no.	Min. required	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
Pad 20" / 508 mm						
	PAD 20-IN RED 5100 CS/5EA	976068	0	○	○	○
	PAD-MAROON-20-10/CS	56390046	0			○
	PAD-WHITE-20-5/CS	976067	0	○	○	○
	VELCRO 2 SIDED 20	56390045	0			○
Ecoflex System						
	ECOFLEX BOTTLE ASSY	56104190	0	●	●	●
Squeegee Blade						
	BLADE SQUEEGEE 510MM 20 RED GUM KIT	56104326	0	○	○	○
	SQUEEGEE KIT-BLADE-PU	56104325	0	○	○	○
Battery						
	BATTERY 12V 140AH AGM	56380239	0		●	
Pad						
	PAD MICRO FIBER	56390079	0	○	○	○
Pad Holder						
	PAD HOLDER-20 3 LUG	56505790	0	●	●	
Disc Brush 510 mm						
	DISC BRUSH-20 AGLITE 3 LUG	56505793	0	○	○	
	DISC BRUSH-20 DYNA GRIT 3 LUG	56505792	0	○	○	











A cost-efficient cleaning solution

Accessories		Ref. no.	Min. required	SC1500 20D ECOFLEX W208 OBC PH	SC1500 20D ECOFLEX A150 OBC PH	SC1500 20R ECOFLEX W208 OBC PH
	DISC BRUSH-20 MAGNAGRIT 3 LUG	56505791	0	○	○	
	DISC BRUSH-20 MIDGRIT 3 LUG	56505797	0	○	○	
	DISC BRUSH-20 MIDLITE 3 LUG	56505798	0	○	○	
	DISC BRUSH-20 PROLENE 3 LUG	56505794	0	○	○	
	DISC BRUSH-20 PROLITE 3 LUG	56505795	0	○	○	
	DISC BRUSH-20 UNION MIX 3 LUG	56505796	0	○	○	


● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories		Ref. no.	Min. required	SC1500 20R ECOFLEX A150 OBC PH	SC1500 20D ECOFLE W208 OBC MGB	SC1500 20D ECOFLE A150 OBC MGB
Pad 20" / 508 mm						
	PAD 20-IN RED 5100 CS/5EA	976068	0	○		
	PAD-MAROON-20-10/CS	56390046	0	○		
	PAD-WHITE-20-5/CS	976067	0	○		
	VELCRO 2 SIDED 20	56390045	0	○		
Ecoflex System						
	ECOFLEX BOTTLE ASSY	56104190	0	●	●	●
Squeegee Blade						
	BLADE SQUEEGEE 510MM 20 RED GUM KIT	56104326	0	○	○	○

A cost-efficient cleaning solution

Accessories		Ref. no.	Min. required	SC1500 20R ECOFLEX A150 OBC PH	SC1500 20D ECOFLE W208 OBC MGB	SC1500 20D ECOFLE A150 OBC MGB
	SQUEEGEE KIT-BLADE-PU	56104325	0	○	○	○
Battery						
	BATTERY 12V 140AH AGM	56380239	0	●		●
Pad						
	PAD MICRO FIBER	56390079	0	○		
Pad Holder						
	PAD HOLDER-20 3 LUG	56505790	0			
Disc Brush 510 mm						
	DISC BRUSH-20 AGLITE 3 LUG	56505793	0		○	○
	DISC BRUSH-20 DYNA GRIT 3 LUG	56505792	0		○	○
	DISC BRUSH-20 MAGNAGRIT 3 LUG	56505791	0		○	○
	DISC BRUSH-20 MIDGRIT 3 LUG	56505797	0		○	○
	DISC BRUSH-20 MIDLITE 3 LUG	56505798	0		●	●
	DISC BRUSH-20 PROLENE 3 LUG	56505794	0		○	○
	DISC BRUSH-20 PROLITE 3 LUG	56505795	0		○	○

A cost-efficient cleaning solution

Accessories		Ref. no.	Min. required	SC1500 20R ECOFLEX A150 OBC PH	SC1500 20D ECOFLE W208 OBC MGB	SC1500 20D ECOFLE A150 OBC MGB
	DISC BRUSH-20 UNION MIX 3 LUG	56505796	0		○	○