Walk-Behind Floor Scrubbers

Simple operation, flexible performance Advance's rugged, low-maintenance SC800TM scrubbers deliver incredible value on a walk-behind platform. High productivity per tankful allows for 84 minutes of continuous scrubbing, which reduces dump/refill cycles and helps provide fast ROI. The optional EcoFlexTM System offers the flexibility to clean across the entire cleaning spectrum from green to clean. At the touch of a button one can switch from chemical free cleaning to using an ultra low dilution ratio, and of course detergent can be used at full strength for the toughest of soils. The burst of power feature lets you easily apply more pressure, more solution and more detergent at the touch of a single button. With the flexibility to easily apply the right scrubbing performance for the job, you'll use less detergent, minimize water use and save on cleaning costs. Benefits of SC800 scrubbers

Available in 26, 28, or 34 inch disc and 28 inch cylindrical scrub paths Smart Solutions or EcoFlex System on all machines Green cleaning and high productivity technology 25 gallon solution and recovery tanks Self adjusting skirt on disc machines Heavy duty scrubbing performance



Picture shown may not represent model quoted

	Included accessories		Min. required	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
Brush Cylind	rical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
Ecoflex Syste	em					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			•
Pad Holder						
	PAD HOLDER-17 3 LUG	56505780	0			
Disc Brush 3	70 mm	,	,			
	BRUSH MIDLITE 14	56505808	0			•
Disc Brush 4	30 mm					
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			



	Included accessories	Ref. no.	Min. required	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•
Standard equipmen	nt					
	Included accessories	Ref. no.	Min. required	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Brush Cylind	rical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
Ecoflex Syst	em					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	
Pad Holder						
	PAD HOLDER-17 3 LUG	56505780	0			
Disc Brush 3	70 mm					
	BRUSH MIDLITE 14	56505808	0	•	•	
Disc Brush 4	30 mm					
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			
Standard equipmen	nt					
	Included accessories	Ref. no.	Min. required	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
Brush Cylind	rical	1				
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			•



Walk-Behind Floor Scrubbers

	Included accessories	Ref. no.	Min. required	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
Ecoflex Syst	em					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			•
Pad Holder		·				
	PAD HOLDER-17 3 LUG	56505780	0			
Disc Brush 3	70 mm					
	BRUSH MIDLITE 14	56505808	0			
Disc Brush 4	30 mm					
	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•

Included accessories		Ref. no.	Min. required	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
Brush Cylindi	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0	•	•	
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	
Pad Holder		'				
	PAD HOLDER-17 3 LUG	56505780	0			•
Disc Brush 37	70 mm					



Walk-Behind Floor Scrubbers

	Included accessories	Ref. no.	Min. required	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH	
	BRUSH MIDLITE 14	56505808	0				
Disc Brush 43	30 mm						
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0				
Battery Wet	Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•	

	Included accessories	Ref. no.	Min. required	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			
Pad Holder						
	PAD HOLDER-17 3 LUG	56505780	0	•	•	•
Disc Brush 37	70 mm					
9	BRUSH MIDLITE 14	56505808	0			
Disc Brush 43	90 mm					
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			



Walk-Behind Floor Scrubbers

Standard equipment

Standard equipmer	·					
	Included accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
Brush Cylind	rical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
Ecoflex System	em					
-	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	
Pad Holder						
	PAD HOLDER-17 3 LUG	56505780	0	•	•	
Disc Brush 3	70 mm					
	BRUSH MIDLITE 14	56505808	0			
Disc Brush 4	30 mm					
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			

Included accessories		Ref. no.	Min. required	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB		
Brush Cylind	Brush Cylindrical							
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0					
Ecoflex Syste	em							
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			•		
Pad Holder	Pad Holder							



Walk-Behind Floor Scrubbers

Included accessories		Ref. no.	Min. required	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB	
	PAD HOLDER-17 3 LUG	56505780	0				
Disc Brush 3	70 mm						
0	BRUSH MIDLITE 14	56505808	0				
Disc Brush 4	30 mm						
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			•	
Battery Wet	Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•	

Included accessories		Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	
Pad Holder						
	PAD HOLDER-17 3 LUG	56505780	0			
Disc Brush 37	0 mm					
	BRUSH MIDLITE 14	56505808	0			
Disc Brush 43	0 mm					



Walk-Behind Floor Scrubbers

Included accessories		Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB		
	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	•		•		
Battery Wet	Battery Wet							
	BATTERY 6V 242AH WET	56206079	0			•		

Standard equipment									
	Included accessories	Ref. no.	Min. required	SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB				
Brush Cylindr	Brush Cylindrical								
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0						
Ecoflex Syste	m								
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0						
Pad Holder									
	PAD HOLDER-17 3 LUG	56505780	0						
Disc Brush 37	70 mm								
	BRUSH MIDLITE 14	56505808	0						
Disc Brush 43	80 mm								
	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	•					
Battery Wet									
	BATTERY 6V 242AH WET	56206079	0						



Model	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
Ref. no.	56112434	56112436	56112437
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared	•	•	•
Built-in squeegee hanger	•	•	•
Ecoflex installed			
Non-marking Wheels	•	•	•
Model	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Ref. no.	56112438	56112439	56112440
PRODUCT FEATURES			
Low working sound level	•	•	
One touch control panel	•	•	
Ecoflex prepared	•	•	
Built-in squeegee hanger	•	•	
Ecoflex installed			
Non-marking Wheels	•	•	
Model	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
Ref. no.	56112441	56112442	56112443
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared	•	•	•
Built-in squeegee hanger	•	•	•
Ecoflex installed			
Non-marking Wheels	•	•	•



Model	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
Ref. no.	56112444	56112445	56112456
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared	•	•	
Built-in squeegee hanger	•	•	•
Ecoflex installed			•
Non-marking Wheels	•	•	•
Model	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
Ref. no.	56112457	56112465	56112466
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared		•	•
Built-in squeegee hanger	•	•	•
Ecoflex installed	•		
Non-marking Wheels	•	•	•
Model	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
Ref. no.	56112468	56112469	56112474
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared			•
Built-in squeegee hanger	•	•	•
Ecoflex installed	•	•	
Non-marking Wheels	•	•	•



Model	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB
Ref. no.	56112475	56112476	56112477
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared	•	•	
Built-in squeegee hanger	•	•	•
Ecoflex installed			•
Non-marking Wheels	•	•	•
Model	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB
Ref. no.	56112478	56112479	56112040
PRODUCT FEATURES			
Low working sound level	•	•	•
One touch control panel	•	•	•
Ecoflex prepared			
Built-in squeegee hanger	•	•	•
Ecoflex installed	•	•	•
Non-marking Wheels	•	•	•
Model		SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
Ref. no.		56112041	56112435
PRODUCT FEATURES			
Low working sound level		•	•
One touch control panel		•	•
Ecoflex prepared			•
Built-in squeegee hanger		•	•
Ecoflex installed		•	
Non-marking Wheels		•	•



Technical specifications	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
Sound level	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position
Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane
Batteries	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)
Scrub head type	Disc	Disc	Disc
Scrub path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Battery charger	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)	170 lb (77.1 kg)
Solution control	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
Vacuum fan	3-Stage	3-Stage	3-Stage
Productivity rate theoretical/actual	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)
Low flow rate	0.25 gal/min (0.98 L/ min) - 91 mins	0.25 gal/min (0.98 L/ min) - 91 mins	0.25 gal/min (0.98 L/ min) - 91 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 42 mins	0.50 gal/min (1.93 L/ min) - 42 mins	0.50 gal/min (1.93 L/ min) - 42 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 32 mins	0.65 gal/min (2.46 L/ min) - 32 mins	0.65 gal/min (2.46 L/ min) - 32 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings



Technical specifications	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 14 in (35.5 cm)	(2) 14 in (35.5 cm)	(2) 14 in (35.5 cm)
Scrub disc/brush speed	270 rpm	270 rpm	270 rpm
Onboard detergent	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)
Length standard model	59.9 in (152 cm)	59.9 in (152 cm)	59.9 in (152 cm)
Length ST Model	58.1 in (148 cm)	58.1 in (148 cm)	58.1 in (148 cm)
Width without squeeegee	30.8 in (78 cm)	30.8 in (78 cm)	30.8 in (78 cm)
Width with squeegee	35.5 (90 cm)	35.5 (90 cm)	35.5 (90 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	347 lb (158 kg)	347 lb (158 kg)	347 lb (158 kg)
Max. dry weight including std. batteries	615 lb (280 kg)	615 lb (280 kg)	615 lb (280 kg)
Gradeability	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%
Technical specifications	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Sound level	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position
Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane
Batteries	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)
Scrub head type	Disc	Disc	Cylindrical
Scrub path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Battery charger	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)



Technical specifications	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)	-
Solution control	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
Vacuum fan	3-Stage	3-Stage	3-Stage
Productivity rate theoretical/actual	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)
Low flow rate	0.25 gal/min (0.98 L/ min) - 91 mins	0.25 gal/min (0.98 L/ min) - 91 mins	0.25 gal/min (0.98 L/ min) - 101 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 42 mins	0.50 gal/min (1.93 L/ min) - 42 mins	0.50 gal/min (1.93 L/ min) - 54 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 32 mins	0.65 gal/min (2.46 L/ min) - 32 mins	0.65 gal/min (2.46 L/ min) - 40 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 14 in (35.5 cm)	(2) 14 in (35.5 cm)	(2) 27 in (68.6 cm)
Scrub disc/brush speed	270 rpm	270 rpm	840 rpm
Onboard detergent	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)
Length standard model	59.9 in (152 cm)	59.9 in (152 cm)	58.5 in (149 cm)
Length ST Model	58.1 in (148 cm)	58.1 in (148 cm)	56.8 in (144 cm)
Width without squeeegee	30.8 in (78 cm)	30.8 in (78 cm)	30.8 in (78 cm)
Width with squeegee	35.5 (90 cm)	35.5 (90 cm)	35.5 (90 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	347 lb (158 kg)	347 lb (158 kg)	347 lb (158 kg)
Max. dry weight including std. batteries	615 lb (280 kg)	615 lb (280 kg)	615 lb (280 kg)



Scrubbing & Scru	Technical specifications	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Technical specifications	Gradeability	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -
Min. aisle turn (cm) 65 in (1.65 m)	Technical specifications			ECOFLEX W242
Solution tank (L)	Sound level			
Peccovery tank (L)	Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Drive wheels (cm) C2 10 in (25.4 cm) diameter solid, gray polyurethane (24 V System) (4) 6 (25 V Sys	Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)	Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Standard Models - Charger Only	Drive wheels (cm)	diámeter solid, gráy - non-marking	diameter solid, gray - non-marking	diameter solid, gray - non-marking
Scrub path 28 in (71 cm) 51.2 in (130 cm	Batteries	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free
Vacuum waterlift	Scrub head type	Cylindrical	Cylindrical	Cylindrical
Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only on Charger / ST Models - Shelf Charger Only on Scrub pressure - regular scrub 80 lb (36.3 kg) 80 lb (3	Scrub path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Battery charger 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only ST Models	Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Scrub pressure - extreme scrub Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST M	Battery charger	24 Volt Shelf or Onboard Charger / ST Models - Shelf	24 Volt Shelf or Onboard Charger / ST Models - Shelf	24 Volt Shelf or Onboard Charger / ST Models - Shelf
Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and for the models of the models of the models of the models of th	Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid techno	Scrub pressure - extreme scrub	-	-	-
Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr) Low flow rate Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr) (2,635 sq m/hr) (2,635 sq m/hr) Low flow rate D.25 gal/min (0.98 L/ min) - 101 mins (0.98 L/ min) - 101 mins (0.98 L/ min) - 101 mins (0.98 L/ min) - 54 mins (0.98 L/ min	Solution control	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation
3.4 mph (5.5 kph) - 41,900 sq ft/hr 41,900 sq ft/hr 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr) 28,366 s	Vacuum fan	3-Stage	3-Stage	3-Stage
Medium flow rate min) - 101 mins 0.50 gal/min (1.93 L/min) - 54 mins 0.50 gal/min (2.94 L/min) - 54 mins 0.50 gal/min (2.94 L/min) - 54 mins min) - 54 mins min) - 54 mins 0.65 gal/min (2.46 L/min) - 54 mins 0.65 gal/min (2.46 L/min) - 101 mins min) - 101 mins min) - 101 mins min) - 101 mins min) - 101 mins 0.50 gal/min (1.93 L/min) - 101 mins 0.50 gal/min (2.94 L/min) - 101 mins<	Productivity rate theoretical/actual	3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr	3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr	3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr
Min) - 54 mins min	Low flow rate			
	Medium flow rate			
	High flow rate			



Speed control Slandard Models - Safety paddle system infinity maximum speed limiter settings (ST Models - ONLOFF maximum speed limiter settings (ST Models - ONLOFF maximum speed limiter settings (ST Models - ONLOFF maximum speed limiter settings) Vacuum fan motor Vacuum fan mot	Technical specifications	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
Brush Pad/Driver Assembly (2) 27 in (88.6 cm) (2) 27 in (88.	Speed control	Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed	Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed	Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed
Scrub disc/brush speed S40 rpm	Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Contact Con	Brush Pad/Driver Assembly	(2) 27 in (68.6 cm)	(2) 27 in (68.6 cm)	(2) 27 in (68.6 cm)
Ni	Scrub disc/brush speed	840 rpm	840 rpm	840 rpm
Propel speed mph (5.8 km/hr) Scrubbing - 3.4 mph (5.5 km/hr) mph (5.6 km/hr) Scrubbing - 3.4 mph (5.5 km/hr) mph (5.5 km/hr) scrubbing - 3.4 mph (5.5 km/hr) crubbing - 3.4 mph (5.5 km/hr) crubbing - 3.4 mph (5.5 km/hr) mph (5.5 km/hr) scrubbing - 3.4 mph (5.5 km/hr) crubbing - 5.8 sin (149 cm) 58.5 in (144 cm) 30.8 in (78 cm) 30.5 in (18 cm)	Onboard detergent			
Length ST Model 56.8 in (144 cm) 56.8 in (144 cm) 56.8 in (144 cm) Width without squeegee 30.8 in (78 cm) 30.5 in (78 cm) 45.1 in (115 cm) 44.5 in (113	Propel speed	mph (5.8 km/hr) / Scrubbing - 3.4 mph	mph (5.8 km/hr) / Scrubbing - 3.4 mph	mph (5.8 km/hr) / Scrubbing - 3.4 mph
Width without squeegee 30.8 in (78 cm) 35.5 (90 cm) 45.1 in (115 cm) 44.5 in (113 cm) 45.1 in (115 cm) 45.1 in (115 cm) 45.1 in (115 cm) 615 lb (280 kg) 615 lb (280 kg) <td>Length standard model</td> <td>58.5 in (149 cm)</td> <td>58.5 in (149 cm)</td> <td>58.5 in (149 cm)</td>	Length standard model	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)
Width with squeegee 35.5 (90 cm) 45.1 in (115 cm) 44.5 in (113 cm) 45.5 in (18 dm) 45.5 in (18 dm) 65 in (1.68 m) 65 in (1.68 m) 85 cmblander 85 cmbla	Length ST Model	56.8 in (144 cm)	56.8 in (144 cm)	56.8 in (144 cm)
Height Standard Model	Width without squeeegee	30.8 in (78 cm)	30.8 in (78 cm)	30.8 in (78 cm)
Height ST Model	Width with squeegee	35.5 (90 cm)	35.5 (90 cm)	35.5 (90 cm)
Max. dry weight without batteries 347 lb (158 kg) 661 lb (280 kg) 615 lb (280 kg) 62	Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Max. dry weight including std. batteries 615 lb (280 kg) 62 lb (280 kg) 615 lb (280 kg) 62 lb (280 kg) 61 lb (280 kg) 61 lb (280 kg) 61 lb (280 kg) 62 lb (280 k	Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Gradeability Scrubbing & Transport (Full) - 8.5 /14.9 %; Trailer Ramp (Empty) - 10.0 /17.6 % Scrubbing & Transport (Full) - 8.5 /14.9 %; Trailer Ramp (Empty) - 10.0 /17.6 % Scrubbing & Transport (Full) - 8.5 /14.9 %; Trailer Ramp (Empty) - 10.0 /17.6 % Scrubbing & Transport (Full) - 8.5 /14.9 %; Trailer Ramp (Empty) - 10.0 /17.6 % Scrubbing & Transport (Full) - 8.5 /14.9 %; Trailer Ramp (Empty) - 10.0 /17.6 % Technical specifications SC800 28C ECOFLEX W310 OBC MGB SC800 28C ECOFLEX A312 OBC MGB SC800 28C ECOFLEX A312 OBC MGB SC800 MGB SC800 MGB SC800 MGB G61 dB (A) @ Operator's position Operator's position Operator's position Operator's position Operator's position	Max. dry weight without batteries	347 lb (158 kg)	347 lb (158 kg)	347 lb (158 kg)
Transport (Full) - 8.5 /14.9%; Trailer Ramp (Empty) - 10.0 /17.6% S.5 /14.9%; Trai	Max. dry weight including std. batteries	615 lb (280 kg)	615 lb (280 kg)	615 lb (280 kg)
Sound level G1 dB (A) @ Operator's position Operator's posit	Gradeability	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -
Sound level Operator's position Operator's positi	Technical specifications	ECOFLEX W310	ECOFLEX A312	
Solution tank (L) Recovery tank (L) 25 gal (95 L) (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	Sound level			
Recovery tank (L) 25 gal (95 L) 25 gal (95 L) (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Drive wheels (cm) (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) diameter solid, gray - non-marking polyurethane (24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Batteries V batteries: 242 Åh Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) V batteries: 242 Åh Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (AGM) V batteries: 242 Åh Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM) (AGM) (AGM)	Drive wheels (cm)	diameter solid, gray - non-marking	diameter solid, gray - non-marking	diameter solid, gray - non-marking
Scrub head type Cylindrical Cylindrical Disc	Batteries	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free
	Scrub head type	Cylindrical	Cylindrical	Disc



Scrub path	Technical specifications	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
Standard Models	Scrub path	28 in (71 cm)	28 in (71 cm)	34 in (86 cm)
Sattery charger 24 Voll Shelf or Onboard Charger or Shodes - Shelf Charger Onboard Charger ST Models - Shelf	Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Strub pressure - extreme scrub Standard Models Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity Sed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity ST Models - G	Battery charger	24 Volt Shelf or Onboard Charger / ST Models - Shelf	24 Volt Shelf or Onboard Charger / ST Models - Shelf	24 Volt Shelf or Onboard Charger / ST Models - Shelf
Standard Models Gravity feed with technology and liquid level sensing / ST Models - Gravity feed with technology and liquid level sensing / ST Models - Gravity feed with pulsation scientification of the property of the pulsation scientification of the pulsation	Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Solution control Caravity feed with pulsating solenoid technology and fluid level sensing of the ded with pulsation solenoid technology and fluid level sensing of the ded with pulsation solenoid technology and fluid level sensing of the ded with pulsation solenoid technology and fluid level sensing of the ded with pulsation solenoid technology and fluid level sensing of the pulsation of the pulsatio	Scrub pressure - extreme scrub	-	-	170 lb (77.1 kg)
Theoretical Max. @ 3.4 mph (6.5 kph) - 41.900 sq fthr (3.890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (3.890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq fthr (2.655 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 29.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 29.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 29.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 29.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 29.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 29.365 sq m/hr) / Est. Coverage @ 2.3 mph (3.8 kph) / Es	Solution control	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation
Productivity rate theoretical/actual 3.4 mph (5.5 kph) 41,900 sq fthr (3.890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) 3.4 mph (3.5 km/hr) 3.4 mph (3.	Vacuum fan	3-Stage	3-Stage	3-Stage
Medium flow rate min) - 101 mins min) - 54 mins 0.50 gal/min (1.93 L/min) - 54 mins 0.50 gal/min (2.46 L/min) - 54 mins min) - 101 mins min) - 54 mins min) - 54 mins min) - 54 mins min) - 40 mins Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings Models - ON/OFF palm switches with maximum speed limiter settings Models -	Productivity rate theoretical/actual	3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr	3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr	3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr
High flow rate min) - 54 mins min) - 40 mins min) - 50.85 galmin 2.46 L/ min) - 40 mins Standard Models Standard	Low flow rate			
Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switche	Medium flow rate			
Speed control Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings Vacuum fan motor 0.66 hp (490 W) 0.66 hp (490 W) 0.66 hp (490 W) Brush Pad/Driver Assembly (2) 27 in (68.6 cm) (2) 27 in (68.6 cm) (2) 27 in (68.6 cm) (2) 17 in (43.0 cm) Scrub disc/brush speed 840 rpm 840 rpm 270 rpm Onboard detergent EcoFlex™ Optional (N/A on ST Models Mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.8 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.5 km/hr) Scrubbing - 3.4 mph (5.5 k	High flow rate			
Brush Pad/Driver Assembly (2) 27 in (68.6 cm) (2) 27 in (68.6 cm) (2) 17 in (43.0 cm) Scrub disc/brush speed 840 rpm 840 rpm 270 rpm Onboard detergent EcoFlex™ Optional (N/A on ST Models (N/A on ST Models) EcoFlex™ Optional (N/A on ST Models) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Scrubbing - 3	Speed control	Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed	Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed	Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed
Scrub disc/brush speed 840 rpm 840 rpm 270 rpm Onboard detergent EcoFlex™ Optional (N/A on ST Models (N/A on ST Models)) EcoFlex™ Optional (N/A on ST Models) EcoFlex™ Optional (N/A on ST Models) Propel speed Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Scrubbing - 3.4 mph	Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Conboard detergent EcoFlex™ Optional (N/A on ST Models Propel speed Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Scrubbing	Brush Pad/Driver Assembly	(2) 27 in (68.6 cm)	(2) 27 in (68.6 cm)	(2) 17 in (43.0 cm)
Chibolati detergent	Scrub disc/brush speed	840 rpm	840 rpm	270 rpm
Propel speed mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr) Length standard model 58.5 in (149 cm) 58.5 in (149 cm) 63.3 in (161 cm) Length ST Model 56.8 in (144 cm) 56.8 in (144 cm) 61.5 in (156 cm) Width without squeeegee 30.8 in (78 cm) 30.8 in (78 cm) 36.8 in (93 cm)	Onboard detergent			EcoFlex™ Optional (N/A on ST Models
Length ST Model 56.8 in (144 cm) 56.8 in (144 cm) 61.5 in (156 cm) Width without squeeegee 30.8 in (78 cm) 30.8 in (78 cm) 36.8 in (93 cm)	Propel speed	mph (5.8 km/hr) / Scrubbing - 3.4 mph	mph (5.8 km/hr) / Scrubbing - 3.4 mph	mph (5.8 km/hr) / Scrubbing - 3.4 mph
Width without squeeegee 30.8 in (78 cm) 36.8 in (93 cm)	Length standard model	58.5 in (149 cm)	58.5 in (149 cm)	63.3 in (161 cm)
	Length ST Model	56.8 in (144 cm)	56.8 in (144 cm)	61.5 in (156 cm)
Width with squeegee 35.5 (90 cm) 35.5 (90 cm) 41.5 in (105 cm)	Width without squeeegee	30.8 in (78 cm)	30.8 in (78 cm)	36.8 in (93 cm)
	Width with squeegee	35.5 (90 cm)	35.5 (90 cm)	41.5 in (105 cm)



Height ST Model	Technical specifications	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
Max. dry weight without batteries 347 lb (158 kg) 347 lb (158 kg) 375 lb (170 kg) Max. dry weight including std. batteries 615 lb (280 kg) 615 lb (280 kg) 615 lb (280 kg) 643 lb (292 kg) Gradeability Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrubbing & Transport (Full) - 8.5 r1.4.9%; Trailer Ramp (Empty) - 10.0 r1.7.6 w Scrub load In (1.6.5 m)	Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Max. dry weight including std. batteries 615 lb (280 kg) 615 lb (280 kg) 615 lb (280 kg) 643 lb (292 kg) Gradeability Scrubbing & Transport (Eull) - 8.57/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrubbing & Transport (Eull) - 8.57/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrubbing & Transport (Eull) - 8.77/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrubing & Transport (Eull) - 8.77/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrubing & Transport (Eull) - 8.77/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrubing & Transport (Eull) - 8.77/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrubing & Transport (Eull) - 8.77/4.9%, Trailer Ramp (Empty) - 10.07/17.8% Scrub in (A.0.00 Mp) - 10.07/17.8% <td>Height ST Model</td> <td>44.5 in (113 cm)</td> <td>44.5 in (113 cm)</td> <td>44.5 in (113 cm)</td>	Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Scrubbing & Scrubping &	Max. dry weight without batteries	347 lb (158 kg)	347 lb (158 kg)	375 lb (170 kg)
	Max. dry weight including std. batteries	615 lb (280 kg)	615 lb (280 kg)	643 lb (292 kg)
Sound level OBC PH OBC P	Gradeability	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -	Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) -
Solution tank (L) 25 gal (95 L) 25 gal (Technical specifications			SC800 34D A312 OBC PH
Solution tank (L) 25 gal (95 L) 25 gal (Sound level			61 dB (A) @ Operator's position
Recovery tank (L)	Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Drive wheels (cm) Canal Ca	Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm) diameter solid, gray - non-marking polyurethane 24 V System) (4) 6 V batteries: 242 h	Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Batteries Valetries 242 Ån Wet or 310 Ah Wet or 312 Åh maintenance-free (AGM) Vateries 242 Ån maintenance-free (AGM) Wet or 312 Åh maintenance-free (AGM) Vateries 242 Ån maintenance-free (AGM) Vateries 242 Ån maintenance-free (AGM) Vateries	Drive wheels (cm)	diámeter solid, gráy - non-marking	diameter solid, gray - non-marking	
Scrub path 34 in (86 cm)	Batteries	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free	V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free	maintenance-free
Vacuum waterlift 51.2 in (130 cm) 54 Volt Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Onboard Charger / ST Models - Sheth on Shelf or Shelf or Shelf or Shelf or Onboard Charger / ST Models - Sheth on Shelf or Shelf o	Scrub head type	Disc	Disc	Disc
Battery charger Batter	Scrub path	34 in (86 cm)	34 in (86 cm)	34 in (86 cm)
Battery charger Battery charger Battery charger Chobard Charger / ST Models - Shelf Charger Only Scrub pressure - regular scrub Bolt (36.3 kg) Scrub pressure - extreme scrub Bolt (36.3 kg) Scrub pressure - extreme scrub Bolt (36.3 kg) Scrub pressure - extreme scrub Bolt (36.3 kg) Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Mode	Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Scrub pressure - extreme scrub 170 lb (77.1 kg) 181 lb (71 lb (1) kg 181 lb (1) kg	Battery charger	24 Volt Shelf or Onboard Charger / ST Models - Shelf	24 Volt Shelf or Onboard Charger / ST Models - Shelf	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology and liquid level sensing / ST Models - Gravity	Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Solution control Solution technology Solution techno	Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)	170 lb (77.1 kg)
Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr Productivity rate theoretical/actual Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr 34,400 sq ft/hr 34,400 sq ft/hr 34,400 sq ft/hr	Solution control	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation	Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
3.4 mph (5.5 kph) - 50,900 sq ft/hr 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr 34,400 sq ft/hr 34,400 sq ft/hr (2,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr 34,400 sq ft/hr 34,400 sq ft/hr	Vacuum fan	3-Stage	3-Stage	3-Stage
(4,000 Sq III/III) (4,000 Sq III/III) (4,000 Sq III/III)	Productivity rate theoretical/actual	3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) -	3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) -	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)



Technical specifications	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
Low flow rate	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)
Scrub disc/brush speed	270 rpm	270 rpm	270 rpm
Onboard detergent	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models	EcoFlex [™] Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)
Length standard model	63.3 in (161 cm)	63.3 in (161 cm)	63.3 in (161 cm)
Length ST Model	61.5 in (156 cm)	61.5 in (156 cm)	61.5 in (156 cm)
Width without squeeegee	36.8 in (93 cm)	36.8 in (93 cm)	36.8 in (93 cm)
Width with squeegee	41.5 in (105 cm)	41.5 in (105 cm)	41.5 in (105 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	375 lb (170 kg)	375 lb (170 kg)	375 lb (170 kg)
Max. dry weight including std. batteries	643 lb (292 kg)	643 lb (292 kg)	643 lb (292 kg)
Gradeability	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%
Technical specifications	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
Sound level	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position
Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane



Technical specifications	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
Batteries	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)
Scrub head type	Disc	Disc	Disc
Scrub path	34 in (86 cm)	34 in (86 cm)	34 in (86 cm)
Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Battery charger	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)	170 lb (77.1 kg)
Solution control	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
Vacuum fan	3-Stage	3-Stage	3-Stage
Productivity rate theoretical/actual	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)
Low flow rate	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)
Scrub disc/brush speed	270 rpm	270 rpm	270 rpm
Onboard detergent	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)



Technical specifications	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
Length standard model	63.3 in (161 cm)	63.3 in (161 cm)	63.3 in (161 cm)
Length ST Model	61.5 in (156 cm)	61.5 in (156 cm)	61.5 in (156 cm)
Width without squeeegee	36.8 in (93 cm)	36.8 in (93 cm)	36.8 in (93 cm)
Width with squeegee	41.5 in (105 cm)	41.5 in (105 cm)	41.5 in (105 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	375 lb (170 kg)	375 lb (170 kg)	375 lb (170 kg)
Max. dry weight including std. batteries	643 lb (292 kg)	643 lb (292 kg)	643 lb (292 kg)
Gradeability	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%
Technical specifications	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB
Sound level	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position
Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane
Batteries	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)
Scrub head type	Disc	Disc	Disc
Scrub path	34 in (86 cm)	34 in (86 cm)	34 in (86 cm)
Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Battery charger	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)	170 lb (77.1 kg)
Solution control	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
Vacuum fan	3-Stage	3-Stage	3-Stage



Technical specifications	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB
Productivity rate theoretical/actual	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)
Low flow rate	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)
Scrub disc/brush speed	270 rpm	270 rpm	270 rpm
Onboard detergent	EcoFlex [™] Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)
Length standard model	63.3 in (161 cm)	63.3 in (161 cm)	63.3 in (161 cm)
Length ST Model	61.5 in (156 cm)	61.5 in (156 cm)	61.5 in (156 cm)
Width without squeeegee	36.8 in (93 cm)	36.8 in (93 cm)	36.8 in (93 cm)
Width with squeegee	41.5 in (105 cm)	41.5 in (105 cm)	41.5 in (105 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	375 lb (170 kg)	375 lb (170 kg)	375 lb (170 kg)
Max. dry weight including std. batteries	643 lb (292 kg)	643 lb (292 kg)	643 lb (292 kg)
Gradeability	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5"/14.9%; Trailer Ramp (Empty) - 10.0"/17.6%



Technical specifications	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB
Sound level	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position	61 dB (A) @ Operator's position
Min. aisle turn (cm)	65 in (1.65 m)	65 in (1.65 m)	65 in (1.65 m)
Solution tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Recovery tank (L)	25 gal (95 L)	25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane
Batteries	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)
Scrub head type	Disc	Disc	Disc
Scrub path	34 in (86 cm)	34 in (86 cm)	34 in (86 cm)
Vacuum waterlift	51.2 in (130 cm)	51.2 in (130 cm)	51.2 in (130 cm)
Battery charger	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Scrub pressure - regular scrub	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)
Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)	170 lb (77.1 kg)
Solution control	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
Vacuum fan	3-Stage	3-Stage	3-Stage
Productivity rate theoretical/actual	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)
Low flow rate	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 101 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 54 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 40 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings



Technical specifications	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)	(2) 17 in (43.0 cm)
Scrub disc/brush speed	270 rpm	270 rpm	270 rpm
Onboard detergent	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)
Length standard model	63.3 in (161 cm)	63.3 in (161 cm)	63.3 in (161 cm)
Length ST Model	61.5 in (156 cm)	61.5 in (156 cm)	61.5 in (156 cm)
Width without squeeegee	36.8 in (93 cm)	36.8 in (93 cm)	36.8 in (93 cm)
Width with squeegee	41.5 in (105 cm)	41.5 in (105 cm)	41.5 in (105 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	375 lb (170 kg)	375 lb (170 kg)	375 lb (170 kg)
Max. dry weight including std. batteries	643 lb (292 kg)	643 lb (292 kg)	643 lb (292 kg)
Gradeability	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5'/14.9%; Trailer Ramp (Empty) - 10.0'/17.6%
Technical specifications		SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
Sound level		61 dB (A) @ Operator's position	61 dB (A) @ Operator's position
Min. aisle turn (cm)		65 in (1.65 m)	65 in (1.65 m)
Solution tank (L)		25 gal (95 L)	25 gal (95 L)
Recovery tank (L)		25 gal (95 L)	25 gal (95 L)
Drive wheels (cm)		(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane	(2) 10 in (25.4 cm) diameter solid, gray - non-marking polyurethane
Batteries		(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)	(24 V System) (4) 6 V batteries: 242 Ah Wet or 310 Ah Wet or 312 Ah maintenance-free (AGM)
Scrub head type		Disc	Disc
Scrub path		34 in (86 cm)	28 in (71 cm)
Vacuum waterlift		51.2 in (130 cm)	51.2 in (130 cm)
Battery charger		Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only	Standard Models - 24 Volt Shelf or Onboard Charger / ST Models - Shelf Charger Only
Scrub pressure - regular scrub		80 lb (36.3 kg)	80 lb (36.3 kg)



Technical specifications	SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
Scrub pressure - extreme scrub	170 lb (77.1 kg)	170 lb (77.1 kg)
Solution control	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology	Standard Models - Gravity feed with pulsating solenoid technology and liquid level sensing / ST Models - Gravity feed with pulsation solenoid technology
Vacuum fan	3-Stage	3-Stage
Productivity rate theoretical/actual	Theoretical Max. @ 3.4 mph (5.5 kph) - 50,900 sq ft/hr (4,730 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 34,400 sq ft/hr (4,000 sq m/hr)	Theoretical Max. @ 3.4 mph (5.5 kph) - 41,900 sq ft/hr (3,890 sq m/hr) / Est. Coverage @ 2.3 mph (3.7 kph) - 28,366 sq ft/hr (2,635 sq m/hr)
Low flow rate	0.25 gal/min (0.98 L/ min) - 101 mins	0.25 gal/min (0.98 L/ min) - 91 mins
Medium flow rate	0.50 gal/min (1.93 L/ min) - 54 mins	0.50 gal/min (1.93 L/ min) - 42 mins
High flow rate	0.65 gal/min (2.46 L/ min) - 40 mins	0.65 gal/min (2.46 L/ min) - 32 mins
Speed control	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings	Standard Models - Safety paddle system infinity variable with maximum speed limiter settings / ST Models - ON/OFF palm switches with maximum speed limiter settings
Vacuum fan motor	0.66 hp (490 W)	0.66 hp (490 W)
Brush Pad/Driver Assembly	(2) 17 in (43.0 cm)	(2) 14 in (35.5 cm)
Scrub disc/brush speed	270 rpm	270 rpm
Onboard detergent	EcoFlex™ Optional (N/A on ST Models	EcoFlex™ Optional (N/A on ST Models
Propel speed	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)	Transporting - 3.6 mph (5.8 km/hr) / Scrubbing - 3.4 mph (5.5 km/hr)
Length standard model	63.3 in (161 cm)	59.9 in (152 cm)
Length ST Model	61.5 in (156 cm)	58.1 in (148 cm)
Width without squeeegee	36.8 in (93 cm)	30.8 in (78 cm)
Width with squeegee	41.5 in (105 cm)	35.5 (90 cm)
Height Standard Model	45.1 in (115 cm)	45.1 in (115 cm)
Height ST Model	44.5 in (113 cm)	44.5 in (113 cm)
Max. dry weight without batteries	375 lb (170 kg)	347 lb (158 kg)
Max. dry weight including std. batteries	643 lb (292 kg)	615 lb (280 kg)
Gradeability	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%	Scrubbing & Transport (Full) - 8.5°/14.9%; Trailer Ramp (Empty) - 10.0°/17.6%



Walk-Behind Floor Scrubbers

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
Other						
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0
	PAD RETAINER	56505195	0			
	UTILITY CADDY	56112222	0	0	0	0
Battery and C	harger					
	HOUR METER KIT	56302198	0	0	0	0
	PROGRAMMER WITH CABLE	56112255	0	0	0	0
Flap and Skirt						
پي	KIT-BRISTLE SKIRT 28	56112306	0	0	0	0
	KIT-BRISTLE SKIRT 34	56112307	0			
Accessory Kit						
	SQUEEGEE ASSY	56112313	0			
	SQUEEGEE ASSY	56112315	0			
Squeegee Bla	de					
	BLADE KIT-SQUEEGEE GUM	56112330	0			
	BLADE KIT-SQUEEGEE GUM	56112333	0			
	BLADE KIT-SQUEEGEE LINATEX	56112331	0			
	BLADE KIT-SQUEEGEE PU	56112332	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•
Brush Cylindri	ical					



	Accessories	Ref. no.	Min. required	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0			
	BRUSH 80 GRIT 28-BLACK	56412194	0			
	BRUSH HARD NYLON 28-NATURAL	56412192	0			
	BRUSH POLYPROPYLENE 28-RED	56412046	0			
	BRUSH SOFT NYLON 28-YELLOW	56412191	0			
Pad Holder						
9	PAD HOLDER-14 3 LUG	56505800	0	0	0	0
	PAD HOLDER-17 3 LUG	56505780	0			
Disc Brush 43	30 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0			
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0			
0	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0			
0	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0			



	Accessories	Ref. no.	Min. required	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0			
9	DISC BRUSH-17 PROLITE 3 LUG	56505785	0			
1	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0			
Disc Brush 37	70 mm					
0	BRUSH AGLITE 14	56505803	0	0	0	0
0	BRUSH DYNA GRIT 14	56505802	0	0	0	0
0	BRUSH MAGNAGRIT 14	56505801	0	0	0	0
	BRUSH MIDGRIT 14	56505807	0	0	0	0
	BRUSH MIDLITE 14	56505808	0	0	0	•
	BRUSH PROLENE 14	56505804	0	0	0	0
0	BRUSH PROLITE 14	56505805	0	0	0	0



Walk-Behind Floor Scrubbers

	Accessories	Ref. no.	Min. required	SC800 28D W242 OBC MGB	SC800 28D A312 OBC MGB	SC800 28D ECOFLEX W242 OBC MGB
	BRUSH UNION MIX 14	56505806	0	0	0	0
Battery		'			'	
	KIT BATTERY WATERING	56601527	0	0	0	0
Ecoflex Syste	em					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			•

ullet Standard equipment, ${}^\bigcirc$ Supplementary accessories, ${}^\square$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Other						
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	
	PAD RETAINER	56505195	0			
	UTILITY CADDY	56112222	0	0	0	
Battery and C	harger					
	HOUR METER KIT	56302198	0	0	0	
	PROGRAMMER WITH CABLE	56112255	0	0	0	
Flap and Skir						
پ	KIT-BRISTLE SKIRT 28	56112306	0	0	0	
	KIT-BRISTLE SKIRT 34	56112307	0			
Accessory Kit						
	SQUEEGEE ASSY	56112313	0			
	SQUEEGEE ASSY	56112315	0			
Squeegee Bla	de					



	Accessories	Ref. no.	Min. required	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
	BLADE KIT-SQUEEGEE GUM	56112330	0			
	BLADE KIT-SQUEEGEE GUM	56112333	0			
	BLADE KIT-SQUEEGEE LINATEX	56112331	0			
	BLADE KIT-SQUEEGEE PU	56112332	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0			
	BRUSH 80 GRIT 28-BLACK	56412194	0			
	BRUSH HARD NYLON 28-NATURAL	56412192	0			
	BRUSH POLYPROPYLENE 28-RED	56412046	0			
	BRUSH SOFT NYLON 28-YELLOW	56412191	0			
Pad Holder						
0	PAD HOLDER-14 3 LUG	56505800	0	0	0	
	PAD HOLDER-17 3 LUG	56505780	0			



	Accessories	Ref. no.	Min. required	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
Disc Brush 43	30 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0			
	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0			
9	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0			
9	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0			
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0			
9	DISC BRUSH-17 PROLITE 3 LUG	56505785	0			
	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0			
Disc Brush 37	70 mm					
9	BRUSH AGLITE 14	56505803	0	0	0	
	BRUSH DYNA GRIT 14	56505802	0	0	0	
	BRUSH MAGNAGRIT 14	56505801	0	0	0	



Accessories		Ref. no.	Min. required	SC800 28D ECOFLEX W310 OBC MGB	SC800 28D ECOFLEX A312 OBC MGB	SC800 28C W242 OBC MGB
	BRUSH MIDGRIT 14	56505807	0	0	0	
	BRUSH MIDLITE 14	56505808	0	•	•	
	BRUSH PROLENE 14	56505804	0	0	0	
9	BRUSH PROLITE 14	56505805	0	0	0	
	BRUSH UNION MIX 14	56505806	0	0	0	
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	
Ecoflex Syste	Ecoflex System					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	

 $[\]bullet$ Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

Accessories		Ref. no.	Min. required	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
Other						
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0
420	PAD RETAINER	56505195	0			
	UTILITY CADDY	56112222	0	0	0	0
Battery and C	harger					



	Accessories	Ref. no.	Min. required	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
	HOUR METER KIT	56302198	0	0	0	0
	PROGRAMMER WITH CABLE	56112255	0	0	0	0
Flap and Skir						
پ	KIT-BRISTLE SKIRT 28	56112306	0			
	KIT-BRISTLE SKIRT 34	56112307	0			
Accessory Kit						
	SQUEEGEE ASSY	56112313	0	0	0	0
	SQUEEGEE ASSY	56112315	0			
Squeegee Bla	ade					
	BLADE KIT-SQUEEGEE GUM	56112330	0	0	0	0
	BLADE KIT-SQUEEGEE GUM	56112333	0			
	BLADE KIT-SQUEEGEE LINATEX	56112331	0	0	0	0
	BLADE KIT-SQUEEGEE PU	56112332	0	0	0	0
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0	0	٥	•
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0	0	0	0
	BRUSH 80 GRIT 28-BLACK	56412194	0	0	0	0
	BRUSH HARD NYLON 28-NATURAL	56412192	0	0	٥	0



	Accessories	Ref. no.	Min. required	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
	BRUSH POLYPROPYLENE 28-RED	56412046	0	0	0	0
	BRUSH SOFT NYLON 28-YELLOW	56412191	0	0	0	0
Pad Holder						
	PAD HOLDER-14 3 LUG	56505800	0			
	PAD HOLDER-17 3 LUG	56505780	0			
Disc Brush 43	30 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0			
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0			
0	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0			
9	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0			
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0			
0	DISC BRUSH-17 PROLITE 3 LUG	56505785	0			



	Accessories	Ref. no.	Min. required	SC800 28C W310 OBC MGB	SC800 28C A312 OBC MGB	SC800 28C ECOFLEX W242 OBC MGB
	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0			
Disc Brush 37	70 mm					
0	BRUSH AGLITE 14	56505803	0			
0	BRUSH DYNA GRIT 14	56505802	0			
0	BRUSH MAGNAGRIT 14	56505801	0			
	BRUSH MIDGRIT 14	56505807	0			
	BRUSH MIDLITE 14	56505808	0			
	BRUSH PROLENE 14	56505804	0			
0	BRUSH PROLITE 14	56505805	0			
	BRUSH UNION MIX 14	56505806	0			
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	0
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			•



Walk-Behind Floor Scrubbers

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
Other						
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0
	PAD RETAINER	56505195	0			0
	UTILITY CADDY	56112222	0	0	0	0
Battery and C	harger					
	HOUR METER KIT	56302198	0	0	0	0
	PROGRAMMER WITH CABLE	56112255	0	0	0	0
Flap and Skirt						
پي	KIT-BRISTLE SKIRT 28	56112306	0			
	KIT-BRISTLE SKIRT 34	56112307	0			0
Accessory Kit						
	SQUEEGEE ASSY	56112313	0	0	0	
	SQUEEGEE ASSY	56112315	0			0
Squeegee Bla	de					
	BLADE KIT-SQUEEGEE GUM	56112330	0	0	0	
	BLADE KIT-SQUEEGEE GUM	56112333	0			0
	BLADE KIT-SQUEEGEE LINATEX	56112331	0	0	0	
	BLADE KIT-SQUEEGEE PU	56112332	0	0	0	
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•
Brush Cylindri	cal					



	Accessories	Ref. no.	Min. required	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0	•	•	
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0	0	0	
	BRUSH 80 GRIT 28-BLACK	56412194	0	0	0	
	BRUSH HARD NYLON 28-NATURAL	56412192	0	0	0	
	BRUSH POLYPROPYLENE 28-RED	56412046	0	0	0	
	BRUSH SOFT NYLON 28-YELLOW	56412191	0	0	0	
Pad Holder						
0	PAD HOLDER-14 3 LUG	56505800	0			
	PAD HOLDER-17 3 LUG	56505780	0			•
Disc Brush 43	80 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0			0
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0			0
0	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0			0
9	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0			0



	Accessories	Ref. no.	Min. required	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0			0
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0			0
9	DISC BRUSH-17 PROLITE 3 LUG	56505785	0			0
	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0			0
Disc Brush 37	70 mm					
0	BRUSH AGLITE 14	56505803	0			
9	BRUSH DYNA GRIT 14	56505802	0			
	BRUSH MAGNAGRIT 14	56505801	0			
	BRUSH MIDGRIT 14	56505807	0			
	BRUSH MIDLITE 14	56505808	0			
	BRUSH PROLENE 14	56505804	0			
0	BRUSH PROLITE 14	56505805	0			



Walk-Behind Floor Scrubbers

	Accessories	Ref. no.	Min. required	SC800 28C ECOFLEX W310 OBC MGB	SC800 28C ECOFLEX A312 OBC MGB	SC800 ST 34D ST W242 SC PH
	BRUSH UNION MIX 14	56505806	0			
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	0
Ecoflex Syste	em					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	0

ullet Standard equipment, ${}^\bigcirc$ Supplementary accessories, ${}^\square$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
Other						
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0
	PAD RETAINER	56505195	0	0	0	0
	UTILITY CADDY	56112222	0	0	0	0
Battery and C	harger					
	HOUR METER KIT	56302198	0	0	0	0
	PROGRAMMER WITH CABLE	56112255	0	0	0	0
Flap and Skirt						
پ	KIT-BRISTLE SKIRT 28	56112306	0			
	KIT-BRISTLE SKIRT 34	56112307	0	0	0	0
Accessory Kit						
	SQUEEGEE ASSY	56112313	0			
	SQUEEGEE ASSY	56112315	0	0	0	0
Squeegee Bla	de					



	Accessories	Ref. no.	Min. required	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
	BLADE KIT-SQUEEGEE GUM	56112330	0			
	BLADE KIT-SQUEEGEE GUM	56112333	0	0	0	0
	BLADE KIT-SQUEEGEE LINATEX	56112331	0			
	BLADE KIT-SQUEEGEE PU	56112332	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0			
	BRUSH 80 GRIT 28-BLACK	56412194	0			
	BRUSH HARD NYLON 28-NATURAL	56412192	0			
	BRUSH POLYPROPYLENE 28-RED	56412046	0			
	BRUSH SOFT NYLON 28-YELLOW	56412191	0			
Pad Holder						
(6)	PAD HOLDER-14 3 LUG	56505800	0			
	PAD HOLDER-17 3 LUG	56505780	0	•	•	•



	Accessories	Ref. no.	Min. required	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
Disc Brush 43	00 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0	0	0	0
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0	0	0	0
	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0	0	0	0
0	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0	0	0	0
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	0	0	0
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0	0	0	0
9	DISC BRUSH-17 PROLITE 3 LUG	56505785	0	0	0	0
1	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0	0	0	0
Disc Brush 37	70 mm					
9	BRUSH AGLITE 14	56505803	0			
9	BRUSH DYNA GRIT 14	56505802	0			
0	BRUSH MAGNAGRIT 14	56505801	0			



Walk-Behind Floor Scrubbers

	Accessories	Ref. no.	Min. required	SC800 ST 34D ST W310 SC PH	SC800 34D W310 OBC PH	SC800 34D A312 OBC PH
	BRUSH MIDGRIT 14	56505807	0			
9	BRUSH MIDLITE 14	56505808	0			
	BRUSH PROLENE 14	56505804	0			
9	BRUSH PROLITE 14	56505805	0			
	BRUSH UNION MIX 14	56505806	0			
Battery		,			,	
	KIT BATTERY WATERING	56601527	0	0	0	0
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	0	0	0

ullet Standard equipment, ullet Supplementary accessories, ullet Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB	
Other							
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0	
420	PAD RETAINER	56505195	0	0	0	0	
	UTILITY CADDY	56112222	0	0	0	0	
Battery and C	Battery and Charger						
	HOUR METER KIT	56302198	0	0	0	0	



	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
	PROGRAMMER WITH CABLE	56112255	0	0	0	0
Flap and Skir	t	'				
پي	KIT-BRISTLE SKIRT 28	56112306	0			
	KIT-BRISTLE SKIRT 34	56112307	0	0	0	0
Accessory Kit	<u> </u>					
	SQUEEGEE ASSY	56112313	0			
	SQUEEGEE ASSY	56112315	0	0	0	0
Squeegee Bla	ade					
	BLADE KIT-SQUEEGEE GUM	56112330	0			
	BLADE KIT-SQUEEGEE GUM	56112333	0	0	0	0
O ::	BLADE KIT-SQUEEGEE LINATEX	56112331	0			
	BLADE KIT-SQUEEGEE PU	56112332	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0			
	BRUSH 80 GRIT 28-BLACK	56412194	0			
	BRUSH HARD NYLON 28-NATURAL	56412192	0			
	BRUSH POLYPROPYLENE 28-RED	56412046	0			



	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
	BRUSH SOFT NYLON 28-YELLOW	56412191	0			
Pad Holder						
	PAD HOLDER-14 3 LUG	56505800	0			
	PAD HOLDER-17 3 LUG	56505780	0	•	•	0
Disc Brush 43	00 mm					
0	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0	0	0	0
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0	0	0	0
	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0	0	0	0
9	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0	0	0	0
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	0	0	0
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0	0	0	0
0	DISC BRUSH-17 PROLITE 3 LUG	56505785	0	0	0	0
7	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0	0	0	0
Disc Brush 37	70 mm					



	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC PH	SC800 34D ECOFLEX A312 OBC PH	SC800 34D W242 OBC MGB
0	BRUSH AGLITE 14	56505803	0			
	BRUSH DYNA GRIT 14	56505802	0			
0	BRUSH MAGNAGRIT 14	56505801	0			
	BRUSH MIDGRIT 14	56505807	0			
	BRUSH MIDLITE 14	56505808	0			
	BRUSH PROLENE 14	56505804	0			
0	BRUSH PROLITE 14	56505805	0			
	BRUSH UNION MIX 14	56505806	0			
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	0
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	



Walk-Behind Floor Scrubbers

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB
Other						
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0
	PAD RETAINER	56505195	0	0	0	0
	UTILITY CADDY	56112222	0	0	0	0
Battery and C	harger	'				
	HOUR METER KIT	56302198	0	0	0	0
	PROGRAMMER WITH CABLE	56112255	0	0	0	0
Flap and Skirt						
پي	KIT-BRISTLE SKIRT 28	56112306	0			
	KIT-BRISTLE SKIRT 34	56112307	0	0	0	0
Accessory Kit						
	SQUEEGEE ASSY	56112313	0			
	SQUEEGEE ASSY	56112315	0	0	0	0
Squeegee Bla	de	'				
	BLADE KIT-SQUEEGEE GUM	56112330	0			
	BLADE KIT-SQUEEGEE GUM	56112333	0	0	0	0
	BLADE KIT-SQUEEGEE LINATEX	56112331	0			
	BLADE KIT-SQUEEGEE PU	56112332	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•
Brush Cylindri	cal					



	Accessories	Ref. no.	Min. required	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0			
	BRUSH 80 GRIT 28-BLACK	56412194	0			
	BRUSH HARD NYLON 28-NATURAL	56412192	0			
	BRUSH POLYPROPYLENE 28-RED	56412046	0			
	BRUSH SOFT NYLON 28-YELLOW	56412191	0			
Pad Holder						
0	PAD HOLDER-14 3 LUG	56505800	0			
	PAD HOLDER-17 3 LUG	56505780	0	0	0	0
Disc Brush 43	30 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0	0	0	0
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0	0	0	0
9	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0	0	0	0
0	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0	0	0	0



	Accessories	Ref. no.	Min. required	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	0	0	•
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0	0	0	0
9	DISC BRUSH-17 PROLITE 3 LUG	56505785	0	0	0	0
1	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0	0	0	0
Disc Brush 37	70 mm					
0	BRUSH AGLITE 14	56505803	0			
0	BRUSH DYNA GRIT 14	56505802	0			
0	BRUSH MAGNAGRIT 14	56505801	0			
	BRUSH MIDGRIT 14	56505807	0			
	BRUSH MIDLITE 14	56505808	0			
	BRUSH PROLENE 14	56505804	0			
9	BRUSH PROLITE 14	56505805	0			_



	Accessories	Ref. no.	Min. required	SC800 34D W310 OBC MGB	SC800 34D A312 OBC MGB	SC800 34D ECOFLEX W242 OBC MGB		
	BRUSH UNION MIX 14	56505806	0					
Battery	Battery							
	KIT BATTERY WATERING	56601527	0	0	0	0		
Ecoflex Syste	em							
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0			•		

ullet Standard equipment, ${}^\bigcirc$ Supplementary accessories, ${}^\square$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB		
Other	Other							
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0	0		
43	PAD RETAINER	56505195	0	0	0	0		
	UTILITY CADDY	56112222	0	0	٥	0		
Battery and C	harger							
	HOUR METER KIT	56302198	0	0	0	0		
	PROGRAMMER WITH CABLE	56112255	0	0	0	0		
Flap and Skin	t .							
پ	KIT-BRISTLE SKIRT 28	56112306	0					
	KIT-BRISTLE SKIRT 34	56112307	0	0	0	0		
Accessory Kit								
	SQUEEGEE ASSY	56112313	0					
	SQUEEGEE ASSY	56112315	0	0	0	0		
Squeegee Bla	ade							



	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB
	BLADE KIT-SQUEEGEE GUM	56112330	0			
	BLADE KIT-SQUEEGEE GUM	56112333	0	0	0	0
	BLADE KIT-SQUEEGEE LINATEX	56112331	0			
9)	BLADE KIT-SQUEEGEE PU	56112332	0			
Battery Wet						
	BATTERY 6V 242AH WET	56206079	0			•
Brush Cylindr	ical					
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0			
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0			
	BRUSH 80 GRIT 28-BLACK	56412194	0			
	BRUSH HARD NYLON 28-NATURAL	56412192	0			
	BRUSH POLYPROPYLENE 28-RED	56412046	0			
	BRUSH SOFT NYLON 28-YELLOW	56412191	0			
Pad Holder						
(0)	PAD HOLDER-14 3 LUG	56505800	0			
	PAD HOLDER-17 3 LUG	56505780	0	0	0	0



	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB
Disc Brush 4	30 mm					
9	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0	0	0	0
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0	0	0	0
	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0	0	0	0
9	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0	0	0	0
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	•	0	•
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0	0	0	0
0	DISC BRUSH-17 PROLITE 3 LUG	56505785	0	0	0	0
7	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0	0	0	0
Disc Brush 3	70 mm					
0	BRUSH AGLITE 14	56505803	0			
	BRUSH DYNA GRIT 14	56505802	0			
0	BRUSH MAGNAGRIT 14	56505801	0			



	Accessories	Ref. no.	Min. required	SC800 34D ECOFLEX W310 OBC MGB	SC800 34D ECOFLEX A312 OBC MGB	SC800 ST 34D W242 SC MGB	
	BRUSH MIDGRIT 14	56505807	0				
	BRUSH MIDLITE 14	56505808	0				
	BRUSH PROLENE 14	56505804	0				
0	BRUSH PROLITE 14	56505805	0				
	BRUSH UNION MIX 14	56505806	0				
Battery							
	KIT BATTERY WATERING	56601527	0	0	0	0	
Ecoflex Syste	Ecoflex System						
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	0	

 $[\]bullet$ Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
Other					
	KIT-VAC WAND WITH TOTE BAG	56112141	0	0	0
420	PAD RETAINER	56505195	0	0	
	UTILITY CADDY	56112222	0	0	0
Battery and Charger					
	HOUR METER KIT	56302198	0	0	0



	Accessories	Ref. no.	Min. required	SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
	PROGRAMMER WITH CABLE	56112255	0	0	0
Flap and Skir	t .	'	'		
پ	KIT-BRISTLE SKIRT 28	56112306	0		0
	KIT-BRISTLE SKIRT 34	56112307	0	0	
Accessory Kit					
	SQUEEGEE ASSY	56112313	0		
	SQUEEGEE ASSY	56112315	0	0	
Squeegee Bla	ade				
	BLADE KIT-SQUEEGEE GUM	56112330	0		
	BLADE KIT-SQUEEGEE GUM	56112333	0	0	
	BLADE KIT-SQUEEGEE LINATEX	56112331	0		
	BLADE KIT-SQUEEGEE PU	56112332	0		
Battery Wet					
	BATTERY 6V 242AH WET	56206079	0		
Brush Cylindr	ical				
	BRUSH 180 GRIT 28-BLUE/GREY	56412193	0		
	BRUSH 46 GRIT 28-ORANG/BROWN	56412195	0		
	BRUSH 80 GRIT 28-BLACK	56412194	0		
	BRUSH HARD NYLON 28-NATURAL	56412192	0		
	BRUSH POLYPROPYLENE 28-RED	56412046	0		



	Accessories	Ref. no.	Min. required	SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
	BRUSH SOFT NYLON 28-YELLOW	56412191	0		
Pad Holder					
©	PAD HOLDER-14 3 LUG	56505800	0		0
	PAD HOLDER-17 3 LUG	56505780	0	0	
Disc Brush 43	0 mm				
0	DISC BRUSH-17 AGLITE 500 Ø430	56505783	0	0	
9	DISC BRUSH-17 DYNAGRIT 3 LUG	56505782	0	0	
0	DISC BRUSH-17 MAGNAGRIT 3 LUG	56505781	0	0	
0	DISC BRUSH-17 MIDGRIT 3 LUG	56505787	0	0	
0	DISC BRUSH-17 MIDLITE 3 LUG	56505788	0	•	
	DISC BRUSH-17 PROLENE 3 LUG	56505784	0	0	
0	DISC BRUSH-17 PROLITE 3 LUG	56505785	0	0	
	DISC BRUSH-17 UNION MIX 3 LUG	56505786	0	0	
Disc Brush 37	0 mm				



	Accessories	Ref. no.	Min. required	SC800 ST 34D W310 SC MGB	SC800 28D W310 OBC MGB
0	BRUSH AGLITE 14	56505803	0		0
9	BRUSH DYNA GRIT 14	56505802	0		0
0	BRUSH MAGNAGRIT 14	56505801	0		0
	BRUSH MIDGRIT 14	56505807	0		0
	BRUSH MIDLITE 14	56505808	0		0
	BRUSH PROLENE 14	56505804	0		0
0	BRUSH PROLITE 14	56505805	0		0
	BRUSH UNION MIX 14	56505806	0		0
Battery					
	KIT BATTERY WATERING	56601527	0	0	0
Ecoflex Syste	m 				
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	0	

