Walk-Behind Floor Scrubbers

Flexible Cleaning in a Compact Scrubber

Adfinity™ walk-behind floor scrubbers with a 24" scrub path are versatile and easy-to-operate hard floor cleaners in a compact platform. Combined with the optional EcoFlex™ System, this is the choice for sustainable, cost-effective floor scrubbing.

Benefits of Adfinity Walk-Behind Floor Scrubbers

Featuring an easy-to-maneuver platform, interchangeable scrub decks and traction-drive operation, Adfinity is an exceptional hard floor cleaning machine. The optional EcoFlex System will help you reduce detergent and water waste, creating a sustainable cleaning solution that's good for the planet and good for your bottom line.

- Easily operate and maneuver with push button forward and reverse, unique "click on" quick change brushes, pad pressure settings and our exclusive One-Touch™ ergonomic control paddle
- Simplify maintenance with easy access to the battery, recovery tank and detergent dispensing system
- Reduce waste and cleaning costs with Smart Solutions[™] flow rate and optional EcoFlex
- Invest in a floor scrubber that's built to last rugged construction with durable components



- Clean during the day thanks to safe sound levels
- Increase productivity with over 1.5 hours of run time between dump and refill



Picture shown may not represent model quoted

Standard equipment

Included accessories		Ref. no.	Min. required	ADFINITY X20C PACKAGE W/ BAT	ADFINITY X20C PACKAGE W/ BAT	ADFINITY X24D PACKAGE W/ BAT
Brush Cylindr	ical					
	BRUSH CYL 510MM 20 PROLITE RED	909 5823 000	0	•	•	
Ecoflex Syste	m					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	•
Pad Holder						
	PAD HOLDER BRIST. 12 305MM W/CENTER LOCK	L08603939	0			•
Battery Gel						
	BATTERY GEL 12V 98 AH	56206985	0		•	
Battery Wet						
	BATTERY 12V 130AH WET	56025782	0	•		•



Walk-Behind Floor Scrubbers

Standard equipment

	Included accessories		Ref. no.	Min. required	ADFINITY X24D PACKAGE W/ BAT
Brush Cylind	Irical			ı	
	BRUSH CYL 510MM 20 PROLITE RED		909 5823 000	0	
Ecoflex Syst	em				
	CHEM BOTTLE ASSY-ECOFLEX		56601545	0	•
Pad Holder					
(9)	PAD HOLDER BRIST. 12 305MM W/CENTER LOCK		L08603939	0	•
Battery Gel					
	BATTERY GEL 12V 98 AH		56206985	0	•
Battery Wet					
	BATTERY 12V 130AH WET		56025782	0	
Model		ADFINITY X20C PACKAGE W/BAT	ADFINITY X2 PACKAGE W/I		DFINITY X24D CKAGE W/BAT
Ref. no.		56317331	56317332		56317333
PRODUCT I	FEATURES				
Interchange	able brush deck	•	•		•
No tool brus	n removal	•	•		•
Ergonomic h	andle	•	•		•
Ecoflex insta	illed	•	•		•
	eter Traction Wheels	•	•		•
Front Solution		•	•		•
Easy-to-acc	ess recovery tank	•	•		•
Model				A[PA	DFINITY X24D CKAGE W/BAT
Ref. no.					56317334
PRODUCT I	FEATURES				
Interchange	able brush deck				•
No tool brus	n removal				•
Ergonomic h	andle				•



Ref. no. 56817334 PRODUCT FEATURES Ecofex installed	Model			ADFINITY X24D PACKAGE W/BAT
Ecoflex installed	Ref. no.			56317334
Easy-to-access recovery tank	PRODUCT FEATURES			
Pront Solution filliport	Ecoflex installed			•
Easy-to-access recovery tank	Large Diameter Traction Wheels			•
ADFINITY X20C PACKAGE W/BAT PACKAGE W/B	Front Solution fillport			•
Approvals ETL, CSA, CE CE CZ, 12 V batteries (wet-acid and maintenance free available) CWet-acid and maintenance free available on the acid and maintenance free available) CWet-acid and maintenance free available) CWet-acid and maintenance free available on the a	Easy-to-access recovery tank			•
Power source	Technical specifications			
Power source "(wet-acid and maintenance free available) "(wet-acid a	Approvals	ETL, CSA, CE	ETL, CSA, CE	ETL, CSA, CE
Drive system variable forward and reverse Max speed as 5.5 mph (5.6 km/hr), 16% gradeability variable forward and reverse Max speed 5.5 mph (5.6 km/hr), 16% gradeability ververse Max speed 5.5 mph (5.6 km/hr), 16% gradeability ververse Max speed 5.5 mph (5.6 km/hr), 16% gradeability ververse Max speed 5.5 mph (5.6 km/hr), 16% gradeability variable (5.6 km/hr), 10% gradeability variable (5.6 km/hr), 26.5 mph (5.6 km/hr), 16% gradeability variable (5.6 km/hr), 26.5 mph (5.6 km/hr), 26.5 mph (5.6 km/hr), 16% gradeability variable (5.6 km/hr), 26.5 mph (5	Power source	` (wet-acid and maintenance free	` (wet-acid and maintenance free	`(wet-acid and maintenance free
Sound level 65.8 dB A at operator's position overation operator's position of palmin (1.1 L/ min) in 1.1 L/ min in 1.1 L/ palmin (1.1 L/ min) in 1.1 L/ palmin (1.1 L/ min) on 1.4.5 palmin (1.1 L/ min) in 1.1 L/ palm	Drive system	variable forward and reverse Max speed 3.5 mph (5.6 km/hr),	variable forward and reverse Max speed 3.5 mph (5.6 km/hr),	variable forward and reverse Max speed 3.5 mph (5.6 km/hr),
Sound level Operator's position Opera	Voltage (V)	24 V	24 V	24 V
Solution flow rate gpm (l/min.) variable up to 0.15 gal/min (0.55 L/min) gal/min (0.55 L/min) (0.3 gal/min (0.55 L/min) (0.3 gal/min (0.55 L/min) (0.3 gal/min (0.55 L/min) (0.3 gal/min (1.1 L/min) (1.1 L/min) (0.3 gal/min (1.1 L/min) (0.3 gal/min (1.1 L/min) (1.1 L/min) (0.3 gal/min (1.1 L/min) (0.3 gal/min (1.1 L/min) (0.3 gal/min (1.1 L/min) (1.1 L/min) (0.3 gal/min (1.1 L/min) (1.1 L/min) (0.3 gal/min (1.1 L/min) (1.1 L/min) (1.1 L/min) (0.3 gal/min (1.1 L/min)	Sound level			
Recovery tank capacity gal (I)	Solution flow rate gpm (I/min.)	variable up to 0.15 gal/min (0.55 L/min) 0.3 gal/min (1.1 L/	variable up to 0.15 gal/min (0.55 L/min) 0.3 gal/min (1.1 L/	variable up to 0.15 gal/min (0.55 L/min) 0.3 gal/min (1.1 L/
Scrub pressure lbs (kg) Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Floating - 57 lb (26 kg) / Locked - N/A Red (37 lb (170 kg)) 362 lb (164 kg) 362 lb (164 kg) 374 lb (170 kg) 374 lb (170 kg) 24 V wet/ maintenance free compatible 24 V wet/ maintenance free compati	Solution tank capacity gal (I)	14.5 gal (55 L)	14.5 gal (55 L)	14.5 gal (55 L)
Scrub pressure lbs (kg)kg) / Löcked - Ñ/Akg) / Löcked - Ñ/Akg) / Löcked - Ñ/Akg) / Löcked - Ñ/AWeight w/batteries (KG)362 lb (164 kg)362 lb (164 kg)374 lb (170 kg)Onboard charger standard24 V wet/ maintenance free compatible24 V wet/ maintenance free compatible24 V wet/ maintenance free compatibleNational Recognized Test Lab CertificationNFSIWeight without batteries247 lb (112 kg)247 lb (112 kg)243 lb (110 kg)Vacuum motor0.44 hp (330 W)0.44 hp (330 W)0.44 hp (330 W)Scrub head typeCylindrical with debris hopperCylindrical with debris hopperDiscScrub pathDual 20 in (50.8 cm) Cylindrical brush systemCylindrical brush systemCylindrical brush systemCylindrical brush systemDimensions (W/O Squeegee)L= 49.2 in (125 cm) W = 22.4 in (57 cm) H = 42.9 in (109 cm)L= 51.6 in (131 cm) W = 25.6 (65 cm) H = 42.9 in (109 cm)	Recovery tank capacity gal (I)	14.5 gal (55 L)	14.5 gal (55 L)	14.5 gal (55 L)
Onboard charger standard 24 V wet/ maintenance free compatible National Recognized Test Lab Certification NFSI Weight without batteries 247 lb (112 kg) Vacuum motor 24 V wet/ maintenance free compatible 247 lb (112 kg) 247 lb (112 kg) 243 lb (110 kg) Vacuum motor 0.44 hp (330 W) Cylindrical with debris hopper Cylindrical with debris hopper Cylindrical brush system Dual 20 in (50.8 cm) Cylindrical brush system Discoil 125 cm) Discoil	Scrub pressure lbs (kg)			
Onboard charger standard maintenance free compatible maintenance free compatible maintenance free compatible maintenance free compatible NFSI Weight without batteries 247 lb (112 kg) Vacuum motor 0.44 hp (330 W) Scrub head type Cylindrical with debris hopper Cylindrical brush system Dimensions (W/O Squeegee) maintenance free compatible maintenance free compatible NFSI 247 lb (112 kg) 247 lb (112 kg) 247 lb (112 kg) 243 lb (110 kg) Cylindrical with debris hopper Cylindrical with debris hopper Cylindrical brush system Cylindrical brush system Dual 20 in (50.8 cm) Cylindrical brush system Cylindrical brush system Dimensions (W/O Squeegee) L= 49.2 in (125 cm) W= 22.4 in (57 cm) W= 22.4 in (57 cm) W= 22.4 in (57 cm) H= 42.9 in (109 cm) W= 42.9 in (109 cm)	Weight w/batteries (KG)	362 lb (164 kg)	362 lb (164 kg)	374 lb (170 kg)
Weight without batteries 247 lb (112 kg) 247 lb (112 kg) 243 lb (110 kg) Vacuum motor 0.44 hp (330 W) 0.44 hp (330 W) 0.44 hp (330 W) Scrub head type Cylindrical with debris hopper Cylindrical with debris hopper Disc Scrub path Dual 20 in (50.8 cm) Cylindrical brush system Dual 20 in (50.8 cm) Cylindrical brush system Cylindrical brush system Cylindrical brush system Cylindrical brush system L= 49.2 in (125 cm) L= 49.2 in (125 cm) L= 51.6 in (131 cm) Dimensions (W/O Squeegee) W = 22.4 in (57 cm) W = 22.4 in (57 cm) H = 42.9 in (109 cm) H = 42.9 in (109 cm) H = 42.9 in (109 cm)	Onboard charger standard	maintenance free	maintenance free	maintenance free
Vacuum motor 0.44 hp (330 W)	National Recognized Test Lab Certification	-	-	NFSI
Scrub head type Cylindrical with debris hopper Cylindrical with debris hopper Disc Dual 20 in (50.8 cm) Cylindrical brush system Cylindrical brush system Dual 20 in (50.8 cm) Cylindrical brush system Cylindrical brush system Dual 20 in (50.8 cm) Cylindrical brush system Cylindrical with debris hopper Dual 20 in (50.8 cm) pad holders standard; brushes available L= 49.2 in (125 cm) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 25.6 (65 cm) H H = 42.9 in (109 cm) Cylindrical with debris hopper Pad holders Standard; brushes available L= 49.2 in (125 cm) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 25.6 (65 cm) H H = 42.9 in (109 cm)	Weight without batteries	247 lb (112 kg)	247 lb (112 kg)	243 lb (110 kg)
Scrub nead type debris hopper debris hopper Disc Scrub path Dual 20 in (50.8 cm) Cylindrical brush system Dual 20 in (50.8 cm) Cylindrical brush system (2) 12 in (30.5 cm) pad holders standard; brushes available Dimensions (W/O Squeegee) L= 49.2 in (125 cm) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 25.6 (65 cm) H H = 42.9 in (109 cm) L= 51.6 in (131 cm) W = 25.6 (65 cm) H H = 42.9 in (109 cm)	Vacuum motor	0.44 hp (330 W)	0.44 hp (330 W)	0.44 hp (330 W)
Scrub path Cylindrical brush system Standard; brushes available Dimensions (W/O Squeegee) L= 49.2 in (125 cm) L= 49.2 in (125 cm) L= 51.6 in (131 cm) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 25.6 (65 cm) H H = 42.9 in (109 cm) H = 42.9 in (109 cm) = 42.9 in (109 cm)	Scrub head type			Disc
Dimensions (W/O Squeegee) W = 22.4 in (57 cm) W = 22.4 in (57 cm) W = 25.6 (65 cm) H H = 42.9 in (109 cm) H = 42.9 in (109 cm) = 42.9 in (109 cm)	Scrub path	Cylindrical brush (Cylindricàl brush ´ system	pad holders standard; brushes
Squeegee width 29.9 in (75.9 cm) 29.9 in (75.9 cm) 31.9 in (81.0 cm)	Dimensions (W/O Squeegee)	W = 22.4 in (57 cm)	W = 22.4 in (57 cm)	W = 25.6 (65 cm) H
	Squeegee width	29.9 in (75.9 cm)	29.9 in (75.9 cm)	31.9 in (81.0 cm)



Technical specifications	ADFINITY X20C PACKAGE W/BAT	ADFINITY X20C PACKAGE W/BAT	ADFINITY X24D PACKAGE W/BAT
Max. productivity	@ 3.0 mph (4.8 km/ hr) 26,400 sq ft (2,453 sq m)	@ 3.0 mph (4.8 km/ hr) 26,400 sq ft (2,453 sq m)	@ 3.0 mph (4.8 km/ hr) 31,680 sq ft (2,943 sq m)
Scrub motor	(2) 0.54 hp (400 W)	(2) 0.54 hp (400 W)	(2) 0.47 hp (350 W)
Max. scrub speed	570 rpm	570 rpm	230 rpm
Technical specifications			ADFINITY X24D PACKAGE W/BAT
Approvals			ETL, CSA, CE
Power source			(2) 12 V batteries (wet-acid and maintenance free available)
Drive system			0.3 hp (200 W) variable forward and reverse Max speed 3.5 mph (5.6 km/hr), 16% gradeability
Voltage (V)			24 V
Sound level			65.8 dB A at operator's position
Solution flow rate gpm (I/min.)			Smart Solutions™ variable up to 0.15 gal/min (0.55 L/min) 0.3 gal/min (1.1 L/ min)
Solution tank capacity gal (I)			14.5 gal (55 L)
Recovery tank capacity gal (I)			14.5 gal (55 L)
Scrub pressure lbs (kg)			Floating - 61 lb (28 kg) / Locked - N/A
Weight w/batteries (KG)			374 lb (170 kg)
Onboard charger standard			24 V wet/ maintenance free compatible
National Recognized Test Lab Certification			NFSI
Weight without batteries			243 lb (110 kg)
Vacuum motor			0.44 hp (330 W)
Scrub head type			Disc
Scrub path			(2) 12 in (30.5 cm) pad holders standard; brushes available
Dimensions (W/O Squeegee)			L= 51.6 in (131 cm) W = 25.6 (65 cm) H = 42.9 in (109 cm)
Squeegee width			31.9 in (81.0 cm)
Max. productivity			@ 3.0 mph (4.8 km/ hr) 31,680 sq ft (2,943 sq m)
Scrub motor			(2) 0.47 hp (350 W)
Max. scrub speed			230 rpm



Walk-Behind Floor Scrubbers

 \bullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	ADFINITY X20C PACKAGE W/ BAT	ADFINITY X20C PACKAGE W/ BAT	ADFINITY X24D PACKAGE W/ BAT
Brush Cylindr	cal					
	BRUSH CYL 510MM 20 GRIT 320 GREY	909 5825 000	0	0	0	
	BRUSH CYL 510MM 20 PROLITE RED	909 5823 000	0	•	•	
	BRUSH CYL 510MM 20 SOFT NYLON BLUE	909 5824 000	0	0	0	
Pad Holder						
(PAD HOLDER BRIST. 12 305MM W/CENTER LOCK	L08603939	0			•
Squeegee Bla	de					
	BLADES SQUEE. 830MM 33 GUM RUBBER KIT	9100000280	0			0
	BLADES SQUEEGEE 740MM 29 PU KIT	909 6858 000	0	0	0	
P	BLADES SQUEEGEE 830MM 33 PU KIT	909 6859 000	0			0
Other			,			
	COUNTER HOUR 24V KIT	9096951000	0	0	0	0
0	HOSE FILLING SIP	9100000703	0	0	0	0
Ecoflex Syste	Ecoflex System					
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•	•	•



	Accessories	Ref. no.	Min. required	ADFINITY X20C PACKAGE W/ BAT	ADFINITY X20C PACKAGE W/ BAT	ADFINITY X24D PACKAGE W/ BAT
Disc Brush 30	05 mm					
9	BRUSH DISC 305MM 12 MID GRIT 240	L08603873	0			0
9	BRUSH DISC 305MM 12 MIDLITE GRIT 180	L08603872	0			0
	BRUSH DISC 305MM 12 PROLENE BLUE	L08603842	0			0
	BRUSH DISC 305MM 12 PROLITE	L08603874	0			0
Battery Gel						
	BATTERY GEL 12V 98 AH	56206985	0		•	
Battery Wet						
	BATTERY 12V 130AH WET	56025782	0	•		•

 $[\]bullet$ Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	ADFINITY X24D PACKAGE W/ BAT	
Brush Cylindr	ical				
	BRUSH CYL 510MM 20 GRIT 320 GREY	909 5825 000	0		
	BRUSH CYL 510MM 20 PROLITE RED	909 5823 000	0		
	BRUSH CYL 510MM 20 SOFT NYLON BLUE	909 5824 000	0		
Pad Holder					
	PAD HOLDER BRIST. 12 305MM W/CENTER LOCK	L08603939	0	•	
Squeegee Bla	de				



	Accessories	Ref. no.	Min. required	ADFINITY X24D PACKAGE W/ BAT
	BLADES SQUEE. 830MM 33 GUM RUBBER KIT	9100000280	0	0
	BLADES SQUEEGEE 740MM 29 PU KIT	909 6858 000	0	
P	BLADES SQUEEGEE 830MM 33 PU KIT	909 6859 000	0	0
Other				
	COUNTER HOUR 24V KIT	9096951000	0	0
0	HOSE FILLING SIP	9100000703	0	0
Ecoflex Syste	m			
	CHEM BOTTLE ASSY-ECOFLEX	56601545	0	•
Disc Brush 30	5 mm			
9	BRUSH DISC 305MM 12 MID GRIT 240	L08603873	0	0
9	BRUSH DISC 305MM 12 MIDLITE GRIT 180	L08603872	0	0
	BRUSH DISC 305MM 12 PROLENE BLUE	L08603842	0	0
	BRUSH DISC 305MM 12 PROLITE	L08603874	0	0
Battery Gel				
	BATTERY GEL 12V 98 AH	56206985	0	•
Battery Wet				



Accessories	Ref. no.	Min. required	ADFINITY X24D PACKAGE W/ BAT
BATTERY 12V 130AH WET	56025782	0	

