#### Rider Floor Scrubbers

Ride the green-cleaning wave Sustainable cleaning is on everyone's shortlist. But is it possible without sacrificing performance? The Clarke® Focus® II Rider Autoscrubber proves it: Not only does it make green cleaning possible, but it can actually clean and restore floors more thoroughly and cost effectively at the same time. Your choice of a 28- or 34-inch disc deck or a 28-inch BOOST® Technology Deck can quickly clean or restore everything from school gymnasiums to healthcare hallways. And the 31-gallon tank paired with precision-controlled cleaning solution flow rates allow up to 155 minutes of scrubbing between refills. The Clarke Focus II Rider takes operator comfort and easy operation to new levels, as well. Its open design allows drivers to access the drivers' compartment from the left or right, and then quickly modify the seat for optimum comfort. Other features move comfort even further, including the low-step height, anti-slip floor, recessed foot pedal and angled floorboard. The sustainable power of BOOST® Technology The Clarke Focus II Rider offers the option of a 28-inch BOOST deck that could change the way you maintain your floors forever. Stripping floor finish has traditionally been one of the most time-consuming and dangerous floor maintenance tasks. With BOOST, the Clarke Focus II can actually remove floor finish without chemicals—saving you time, cutting your material costs, and reducing the risks of slip-and-falls and chemical spills.



Picture shown may not represent model quoted

- Universal One-Touch™ Controls ensure easy operation
- · Increased cleaning deck down pressure ensures one-pass cleaning of even heavily soiled floors
- · Heavy-duty, fully-adjustable steel side skirts maximize water pickup while protecting against machine damage
- BOOST® Technology allows more sustainable cleaning and more impressive results
- · Optional Chemical Mixing System ensures that every drop of chemical will be used to clean your floors exactly as directed
- · Onboard battery charger eliminates downtime by ensuring continuous operation and quick maintenance
- · Wide turn radius ensures cleaning even in tight spaces

#### Standard equipment

	Included accessories	Ref. no.	Min. required	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0			•

#### Standard equipment

Included accessories		Ref. no.	Min. required	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0	•		

#### Standard equipment

	Included accessories	Ref. no.	Min. required	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0			•



#### Rider Floor Scrubbers

Standard equipment

Included accessories		Ref. no.	Min. required	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0	•		

Standard equipment

Included accessories		Ref. no.	Min. required	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0	•	•	

Standard equipment

	Included accessories	Ref. no.	Min. required	FOCUS II R 34D CH A312 OBC PH
Battery Wet				
	BATTERY 6V 420AH WET	56388582	0	

Model	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
Ref. no.	56114012	56114014	56114015
PRODUCT FEATURES			
Low working sound level	•	•	•
Roller bumpers on squeegee	•	•	•
Non marking traction wheels	•	•	•
On-board charger	•	•	•
One touch control panel	•	•	•
Adjustable seat	•	•	•
Polyurethane front & rear wheels	•	•	•
Built-in squeegee hanger	•	•	•
Superior Line of Sight	•	•	•
BOOST® Technology			
Open machine design	•	•	•
Tools-free adjustable seat	•	•	•
Fully adjustable side skirts	•	•	•
Angled Floorboard	•	•	•
Solution sight tube	•	•	•
Large recovery tank opening	•	•	•



Ref. no.         56114016         56114017         56114018           PRODUCT FEATURES  <	Model	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH
Low working sound level         • • • • • • • • • • • • • • • • • • •	Ref. no.	56114016	56114017	56114018
Roller bumpers on squeegee         • </td <td>PRODUCT FEATURES</td> <td></td> <td></td> <td></td>	PRODUCT FEATURES			
Non marking traction wheels         •<	Low working sound level	•	•	•
On-board charger	Roller bumpers on squeegee	•	•	•
One touch control panel	Non marking traction wheels	•	•	•
Adjustable seat         .	On-board charger	•	•	•
Polyurethane front & rear wheels         •         <	One touch control panel	•	•	•
Built-in squeegee hanger         • <td>Adjustable seat</td> <td>•</td> <td>•</td> <td>•</td>	Adjustable seat	•	•	•
Superior Line of Sight         •	Polyurethane front & rear wheels	•	•	•
BOOST® Technology         .         .         .           Open machine design         .         .         .           Tools-free adjustable seat         .         .         .           Fully adjustable side skirts         .         .         .           Angled Floorboard         .         .         .         .           Solution sight tube         .         .         .         .         .           Large recovery tank opening         .	Built-in squeegee hanger	•	•	•
Open machine design         •         •         •           Tools-free adjustable seat         •         •         •           Fully adjustable side skirts         •         •         •           Angled Floorboard         •         •         •           Solution sight tube         •         •         •           Large recovery tank opening         •         •         •           Model         FOCUS II R 28B W310 OBC PH         FOCUS II R 28B W310 OBC	Superior Line of Sight	•	•	•
Tools-free adjustable seat         •         •         •           Fully adjustable side skirts         •         •         •           Angled Floorboard         •         •         •           Solution sight tube         •         •         •           Large recovery tank opening         •         •         •           Model         FOCUS II R 28B W310 OBC PH         FOCUS II R 28B W420 SC PH	BOOST® Technology			
Fully adjustable side skirts         •         •         •           Angled Floorboard         •         •         •           Solution sight tube         •         •         •           Large recovery tank opening         •         •         •           Model         FOCUS II R 28B W310 OBC PH         FOCUS II R 28B W420 SC PH         FOCUS II R 28B W420 SC PH         FOCUS II R 28B W310 OBC PH         FOCUS II R 28B W420 SC PH	Open machine design	•	•	•
Angled Floorboard         •         •         •           Solution sight tube         •         •         •           Large recovery tank opening         •         •         •           Model         FOCUS II R 28B W310 OBC PH W310 OBC PH W310 OBC PH W420 SC PH W420 SC PH         FOCUS II R 28B W310 OBC PH W310 OBC PH W420 SC PH W420 SC PH         FOCUS II R 28B W310 OBC PH W420 SC PH W420 SC PH         FOCUS II R 28B W310 OBC PH W420 SC	Tools-free adjustable seat	•	•	•
Solution sight tube         •         •         •           Large recovery tank opening         •         •         •           Model         FOCUS II R 28B W310 OBC PH	Fully adjustable side skirts	•	•	•
Large recovery tank opening         •         •         •           Model         FOCUS II R 28B W310 OBC PH W310	Angled Floorboard	•	•	•
Model         FOCUS II R 28B W310 OBC PH         FOCUS II R 28B W420 SC PH           Ref. no.         56114020         56114022         56114023           FRODUCT FEATURES           Low working sound level         •         •         •           Roller bumpers on squeegee         •         •         •           Non marking traction wheels         •         •         •           On-board charger         •         •         •           One touch control panel         •         •         •           Adjustable seat         •         •         •           Polyurethane front & rear wheels         •         •         •           Built-in squeegee hanger         •         •         •           Superior Line of Sight         •         •         •           BOOST® Technology         •         •         •           Open machine design         •         •         •           Tools-free adjustable seat         •         •         •           Full yadjustable side skirts         •         •         •	Solution sight tube	•	•	•
Ref. no.         \$6114020         \$6114022         \$6114023           PRODUCT FEATURES           Low working sound level         •         •         •           Roller bumpers on squeegee         •         •         •           Non marking traction wheels         •         •         •           On-board charger         •         •         •           One touch control panel         •         •         •           Adjustable seat         •         •         •           Polyurethane front & rear wheels         •         •         •           Built-in squeegee hanger         •         •         •           Superior Line of Sight         •         •         •           BOOST® Technology         •         •         •           Open machine design         •         •         •           Tools-free adjustable seat         •         •         •           Fully adjustable side skirts         •         •         •	Large recovery tank opening	•	•	•
PRODUCT FEATURES  Low working sound level	Model	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	
Low working sound level  Roller bumpers on squeegee  Non marking traction wheels  On-board charger  One touch control panel  Adjustable seat  Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts	Ref. no.	56114020	56114022	56114023
Roller bumpers on squeegee  Non marking traction wheels  On-board charger  One touch control panel  Adjustable seat  Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts	PRODUCT FEATURES			
Non marking traction wheels  On-board charger  One touch control panel  Adjustable seat  Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  •  •  •  •  •  •  •  •  •  •  •  •  •	Low working sound level	•	•	•
On-board charger  One touch control panel  Adjustable seat  Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts	Roller bumpers on squeegee	•	•	•
One touch control panel  Adjustable seat  Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts	Non marking traction wheels	•	•	•
Adjustable seat  Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  • • • • • • • • • • • • • • • • • •	On-board charger	•	•	•
Polyurethane front & rear wheels  Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  • • • • • • • • • • • • • • • • • •	One touch control panel	•	•	•
Built-in squeegee hanger  Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  • • • • • • • • • • • • • • • • • •	Adjustable seat	•	•	•
Superior Line of Sight  BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  • • • • • • • • • • • • • • • • • •	Polyurethane front & rear wheels	•	•	•
BOOST® Technology  Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  •  •  •  •  •  •  •  •  •  •  •  •  •	Built-in squeegee hanger	•	•	•
Open machine design  Tools-free adjustable seat  Fully adjustable side skirts  • • • • • • • • • • • • • • • • • •	Superior Line of Sight	•	•	•
Tools-free adjustable seat  Fully adjustable side skirts  • • • • • • • • • • • • • • • • • • •	BOOST® Technology	•	•	•
Fully adjustable side skirts   • • •	Open machine design	•	•	•
	Tools-free adjustable seat	•	•	•
Angled Floorboard • • •	Fully adjustable side skirts	•	•	•
	Angled Floorboard	•	•	•



Model	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
Ref. no.	56114020	56114022	56114023
PRODUCT FEATURES			
Solution sight tube	•	•	•
Large recovery tank opening	•	•	•
Model	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
Ref. no.	56114024	56114025	56114026
PRODUCT FEATURES			
Low working sound level	•	•	•
Roller bumpers on squeegee	•	•	•
Non marking traction wheels	•	•	•
On-board charger	•	•	•
One touch control panel	•	•	•
Adjustable seat	•	•	•
Polyurethane front & rear wheels	•	•	•
Built-in squeegee hanger	•	•	•
Superior Line of Sight	•	•	•
BOOST® Technology	•	•	•
Open machine design	•	•	•
Tools-free adjustable seat	•	•	•
Fully adjustable side skirts	•	•	•
Angled Floorboard	•	•	•
Solution sight tube	•	•	•
Large recovery tank opening	•	•	•
Model	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Ref. no.	56114031	56114032	56114033
PRODUCT FEATURES			
Low working sound level	•	•	•
Roller bumpers on squeegee	•	•	•
Non marking traction wheels	•	•	•
On-board charger	•	•	•
One touch control panel	•	•	•
Adjustable seat	•	•	•
Polyurethane front & rear wheels	•	•	•
Built-in squeegee hanger	•	•	•



Model	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Ref. no.	56114031	56114032	56114033
PRODUCT FEATURES			
Superior Line of Sight	•	•	•
BOOST® Technology			
Open machine design	•	•	•
Tools-free adjustable seat	•	•	•
Fully adjustable side skirts	•	•	•
Angled Floorboard	•	•	•
Solution sight tube	•	•	•
Large recovery tank opening	•	•	•
Model			FOCUS II R 34D CH A312 OBC PH
Ref. no.			56114034
PRODUCT FEATURES			
Low working sound level			•
Roller bumpers on squeegee			•
Non marking traction wheels			•
On-board charger			•
One touch control panel			•
Adjustable seat			•
Polyurethane front & rear wheels			•
Built-in squeegee hanger			•
Superior Line of Sight			•
BOOST® Technology			
Open machine design			•
Tools-free adjustable seat			•
Fully adjustable side skirts			•
Angled Floorboard			•
Solution sight tube			•
Large recovery tank opening			•



Technical specifications	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
Power source	24 VDC	24 VDC	24 VDC
Drive motor hp (W)	1.05 hp (780 W)	1.05 hp (780 W)	1.05 hp (780 W)
Max. transport speed mph (km/h)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)
Sound pressure level (dB(A))	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)
Solution tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Min. aisle turn (cm)	63 in (160 cm) Radius	63 in (160 cm) Radius	63 in (160 cm) Radius
Recovery tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Brush motor hp (W)	0.64 hp (480 Watts)	0.64 hp (480 Watts)	0.64 hp (480 Watts)
Brush speed (RPM)	260 RPM	260 RPM	260 RPM
Gross weight (GVW) (KG)	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank
Gradeability transport % (DEG)	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees
Vacuum motor	0.75 hp (560 Watts)	0.75 hp (560 Watts)	0.75 hp (560 Watts)
Scrub head type	Disc	Disc	Disc
Max. cleaning speed	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)
Max. coverage per hour @ 3.12 MPH	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)
Scrub pressure - regular scrub	90 lb (39 kg)	90 lb (39 kg)	90 lb (39 kg)
Scrub pressure - heavy scrub	150 lb (65 kg)	150 lb (65 kg)	150 lb (65 kg)
Scrub pressure - extreme scrub	220 lb (96 kg)	220 lb (96 kg)	220 lb (96 kg)
Sealed waterlift	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)
Max. airflow rate (cfm)	76.5 (36 L/sec)	76.5 (36 L/sec)	76.5 (36 L/sec)
Body length	60 in (152 cm)	60 in (152 cm)	60 in (152 cm)
Body height	55 in (140 cm)	55 in (140 cm)	55 in (140 cm)
Body width	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)
Max. width w/o squeegee	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)
Max. weight w/o batteries	547 lb (257.6 kg)	547 lb (257.6 kg)	547 lb (257.6 kg)
Cleaning path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Squeegee width	32.6 in (83 cm)	32.6 in (83 cm)	32.6 in (83 cm)
Max. PSI	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider
Low flow rate	0.33 gal/min (1.25 L/ min)	0.33 gal/min (1.25 L/ min)	0.33 gal/min (1.25 L/ min)
Medium flow rate	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)
High flow rate	0.80 gal/min (3.03 L/ min)	0.80 gal/min (3.03 L/ min)	0.80 gal/min (3.03 L/ min)



Technical specifications	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
Gradeability - Cleaning	4.5%, 7.9 degrees	4.5%, 7.9 degrees	4.5%, 7.9 degrees
Agency approval	CSA, ETL Canada and US	CSA, ETL Canada and US	CSA, ETL Canada and US
Technical specifications	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH
Power source	24 VDC	24 VDC	24 VDC
Drive motor hp (W)	1.05 hp (780 W)	1.05 hp (780 W)	1.05 hp (780 W)
Max. transport speed mph (km/h)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)
Sound pressure level (dB(A))	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)
Solution tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Min. aisle turn (cm)	63 in (160 cm) Radius	63 in (160 cm) Radius	63 in (160 cm) Radius
Recovery tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Brush motor hp (W)	0.64 hp (480 Watts)	0.64 hp (480 Watts)	0.64 hp (480 Watts)
Brush speed (RPM)	260 RPM	260 RPM	260 RPM
Gross weight (GVW) (KG)	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank
Gradeability transport % (DEG)	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees
Vacuum motor	0.75 hp (560 Watts)	0.75 hp (560 Watts)	0.75 hp (560 Watts)
Scrub head type	Disc	Disc	Disc
Max. cleaning speed	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)
Max. coverage per hour @ 3.12 MPH	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)
Scrub pressure - regular scrub	90 lb (39 kg)	90 lb (39 kg)	90 lb (39 kg)
Scrub pressure - heavy scrub	150 lb (65 kg)	150 lb (65 kg)	150 lb (65 kg)
Scrub pressure - extreme scrub	220 lb (96 kg)	220 lb (96 kg)	220 lb (96 kg)
Sealed waterlift	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)
Max. airflow rate (cfm)	76.5 (36 L/sec)	76.5 (36 L/sec)	76.5 (36 L/sec)
Body length	60 in (152 cm)	60 in (152 cm)	60 in (152 cm)
Body height	55 in (140 cm)	55 in (140 cm)	55 in (140 cm)
Body width	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)
Max. width w/o squeegee	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)
Max. weight w/o batteries	547 lb (257.6 kg)	547 lb (257.6 kg)	547 lb (257.6 kg)
Cleaning path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Squeegee width	32.6 in (83 cm)	32.6 in (83 cm)	32.6 in (83 cm)
Max. PSI	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider



Technical specifications	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH
Low flow rate	0.33 gal/min (1.25 L/ min)	0.33 gal/min (1.25 L/ min)	0.33 gal/min (1.25 L/ min)
Medium flow rate	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)
High flow rate	0.80 gal/min (3.03 L/ min)	0.80 gal/min (3.03 L/ min)	0.80 gal/min (3.03 L/ min)
Gradeability - Cleaning	4.5%, 7.9 degrees	4.5%, 7.9 degrees	4.5%, 7.9 degrees
Agency approval	CSA, ETL Canada and US	CSA, ETL Canada and US	CSA, ETL Canada and US
Technical specifications	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
Power source	24 VDC	24 VDC	24 VDC
Drive motor hp (W)	1.05 hp (780 W)	1.05 hp (780 W)	1.05 hp (780 W)
Max. transport speed mph (km/h)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)
Sound pressure level (dB(A))	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)
Solution tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Min. aisle turn (cm)	63 in (160 cm) Radius	63 in (160 cm) Radius	63 in (160 cm) Radius
Recovery tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Brush motor hp (W)	0.75 hp (559 Watts)	0.75 hp (559 Watts)	0.75 hp (559 Watts)
Brush speed (RPM)	2,250 RPM	2,250 RPM	2,250 RPM
Gross weight (GVW) (KG)	1,371 lb (621.9 kg) with 175 lb operator, 310 Ah batteries, full tank	1,371 lb (621.9 kg) with 175 lb operator, 310 Ah batteries, full tank	1,371 lb (621.9 kg) with 175 lb operator, 310 Ah batteries, full tank
Gradeability transport % (DEG)	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees
Vacuum motor	0.75 hp (560 Watts)	0.75 hp (560 Watts)	0.75 hp (560 Watts)
Scrub head type	BOOST	BOOST	BOOST
Max. cleaning speed	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)
Max. coverage per hour @ 3.12 MPH	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)
Scrub pressure - regular scrub	90 lb (39 kg)	90 lb (39 kg)	90 lb (39 kg)
Scrub pressure - heavy scrub	120 lb (54 kg)	120 lb (54 kg)	120 lb (54 kg)
Scrub pressure - extreme scrub	150 lb (68 kg)	150 lb (68 kg)	150 lb (68 kg)
Sealed waterlift	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)
Max. airflow rate (cfm)	76.5 (36 L/sec)	76.5 (36 L/sec)	76.5 (36 L/sec)
Body length	60 in (152 cm)	60 in (152 cm)	60 in (152 cm)
Body height	55 in (140 cm)	55 in (140 cm)	55 in (140 cm)
Body width	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)
Max. width w/o squeegee	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)
Max. weight w/o batteries	590 lb (616.4 kg)	590 lb (616.4 kg)	590 lb (616.4 kg)



Technical specifications	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
Cleaning path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Squeegee width	32.6 in (83 cm)	32.6 in (83 cm)	32.6 in (83 cm)
Max. PSI	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider
Low flow rate	0.20 gal/min (0.76 L/ min)	0.20 gal/min (0.76 L/ min)	0.20 gal/min (0.76 L/ min)
Medium flow rate	0.40 gal/min (1.51 L/ min)	0.40 gal/min (1.51 L/ min)	0.40 gal/min (1.51 L/ min)
High flow rate	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)
Gradeability - Cleaning	4.5%, 7.9 degrees	4.5%, 7.9 degrees	4.5%, 7.9 degrees
Agency approval	CSA, ETL Canada and US	CSA, ETL Canada and US	CSA, ETL Canada and US
Technical specifications	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
Power source	24 VDC	24 VDC	24 VDC
Drive motor hp (W)	1.05 hp (780 W)	1.05 hp (780 W)	1.05 hp (780 W)
Max. transport speed mph (km/h)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)
Sound pressure level (dB(A))	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)
Solution tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Min. aisle turn (cm)	63 in (160 cm) Radius	63 in (160 cm) Radius	63 in (160 cm) Radius
Recovery tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Brush motor hp (W)	0.75 hp (559 Watts)	0.75 hp (559 Watts)	0.75 hp (559 Watts)
Brush speed (RPM)	2,250 RPM	2,250 RPM	2,250 RPM
Gross weight (GVW) (KG)	1,371 lb (621.9 kg) with 175 lb operator, 310 Ah batteries, full tank	1,371 lb (621.9 kg) with 175 lb operator, 310 Ah batteries, full tank	1,371 lb (621.9 kg) with 175 lb operator, 310 Ah batteries, full tank
Gradeability transport % (DEG)	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees
Vacuum motor	0.75 hp (560 Watts)	0.75 hp (560 Watts)	0.75 hp (560 Watts)
Scrub head type	BOOST	BOOST	BOOST
Max. cleaning speed	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)
Max. coverage per hour @ 3.12 MPH	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)	38,438 sq ft (3,751 sq m)
Scrub pressure - regular scrub	90 lb (39 kg)	90 lb (39 kg)	90 lb (39 kg)
Scrub pressure - heavy scrub	120 lb (54 kg)	120 lb (54 kg)	120 lb (54 kg)
Scrub pressure - extreme scrub	150 lb (68 kg)	150 lb (68 kg)	150 lb (68 kg)
Sealed waterlift	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)
Max. airflow rate (cfm)	76.5 (36 L/sec)	76.5 (36 L/sec)	76.5 (36 L/sec)
Body length	60 in (152 cm)	60 in (152 cm)	60 in (152 cm)
Body height	55 in (140 cm)	55 in (140 cm)	55 in (140 cm)



	500110 II B 00B 011	E00110 II B 00B	500H0 H B 00B 0H
Technical specifications	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
Body width	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)
Max. width w/o squeegee	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)	31.5 in (80 cm) (Doorway)
Max. weight w/o batteries	590 lb (616.4 kg)	590 lb (616.4 kg)	590 lb (616.4 kg)
Cleaning path	28 in (71 cm)	28 in (71 cm)	28 in (71 cm)
Squeegee width	32.6 in (83 cm)	32.6 in (83 cm)	32.6 in (83 cm)
Max. PSI	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider
Low flow rate	0.20 gal/min (0.76 L/ min)	0.20 gal/min (0.76 L/ min)	0.20 gal/min (0.76 L/ min)
Medium flow rate	0.40 gal/min (1.51 L/ min)	0.40 gal/min (1.51 L/ min)	0.40 gal/min (1.51 L/ min)
High flow rate	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)
Gradeability - Cleaning	4.5%, 7.9 degrees	4.5%, 7.9 degrees	4.5%, 7.9 degrees
Agency approval	CSA, ETL Canada and US	CSA, ETL Canada and US	CSA, ETL Canada and US
Technical specifications	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Power source	24 VDC	24 VDC	24 VDC
Drive motor hp (W)	1.05 hp (780 W)	1.05 hp (780 W)	1.05 hp (780 W)
Max. transport speed mph (km/h)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)	3.91 mph (6.3 kph)
Sound pressure level (dB(A))	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)	68.6 dB A (IEC 60704-1)
Solution tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Min. aisle turn (cm)	67.5 in (171 cm) Radius	67.5 in (171 cm) Radius	67.5 in (171 cm) Radius
Recovery tank capacity gal (I)	31 gal (117 L)	31 gal (117 L)	31 gal (117 L)
Brush motor hp (W)	0.64 hp (480 Watts)	0.64 hp (480 Watts)	0.64 hp (480 Watts)
Brush speed (RPM)	260 RPM	260 RPM	260 RPM
Gross weight (GVW) (KG)	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank	1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank
Gradeability transport % (DEG)	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees	7.1 %, 12.5 degrees
Vacuum motor	0.75 hp (560 Watts)	0.75 hp (560 Watts)	0.75 hp (560 Watts)
Scrub head type	Disc	Disc	Disc
Max. cleaning speed	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)	3.12 mph (4.8 kph)
Max. coverage per hour @ 3.12 MPH	46,675 sq ft (4,336 sq m)	46,675 sq ft (4,336 sq m)	46,675 sq ft (4,336 sq m)
Scrub pressure - regular scrub	90 lb (39 kg)	90 lb (39 kg)	90 lb (39 kg)
Scrub pressure - heavy scrub	150 lb (65 kg)	150 lb (65 kg)	150 lb (65 kg)
Scrub pressure - extreme scrub	220 lb (96 kg)	220 lb (96 kg)	220 lb (96 kg)



Technical specifications	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Sealed waterlift	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)	46.1 in of H2O (11.48 kPa)
Max. airflow rate (cfm)	76.5 (36 L/sec)	76.5 (36 L/sec)	76.5 (36 L/sec)
Body length	60 in (152 cm)	60 in (152 cm)	60 in (152 cm)
Body height	55 in (140 cm)	55 in (140 cm)	55 in (140 cm)
Body width	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)
Max. width w/o squeegee	35.8 in (91 cm) (Doorway)	35.8 in (91 cm) (Doorway)	35.8 in (91 cm) (Doorway)
Max. weight w/o batteries	547 lb (257.6 kg)	547 lb (257.6 kg)	547 lb (257.6 kg)
Cleaning path	34 in (86 cm)	34 in (86 cm)	34 in (86 cm)
Squeegee width	41.4 in (105 cm)	41.4 in (105 cm)	41.4 in (105 cm)
Max. PSI	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider
Low flow rate	0.33 gal/min (1.25 L/ min)	0.33 gal/min (1.25 L/ min)	0.33 gal/min (1.25 L/ min)
Medium flow rate	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)	0.60 gal/min (2.27 L/ min)
High flow rate	0.80 gal/min (3.03 L/ min)	0.80 gal/min (3.03 L/ min)	0.80 gal/min (3.03 L/ min)
Gradeability - Cleaning	4.5%, 7.9 degrees	4.5%, 7.9 degrees	4.5%, 7.9 degrees
Agency approval	CSA, ETL Canada and US	CSA, ETL Canada and US	CSA, ETL Canada and US
Technical specifications			FOCUS II R 34D CH A312 OBC PH
Power source			24 VDC
Drive motor hp (W)			1.05 hp (780 W)
Max. transport speed mph (km/h)			3.91 mph (6.3 kph)
Sound pressure level (dB(A))			68.6 dB A (IEC 60704-1)
Solution tank capacity gal (I)			31 gal (117 L)
Min. aisle turn (cm)			67.5 in (171 cm) Radius
Recovery tank capacity gal (I)			31 gal (117 L)
Brush motor hp (W)			0.64 hp (480 Watts)
Brush speed (RPM)			260 RPM
Gross weight (GVW) (KG)			1,328 lb (602.4 kg) with 175 lb operator, 310 Ah batteries, full tank
Gradeability transport % (DEG)			7.1 %, 12.5 degrees
Vacuum motor			0.75 hp (560 Watts)
Scrub head type			Disc
Max. cleaning speed			3.12 mph (4.8 kph)



### Rider Floor Scrubbers

Technical specifications	FOCUS II R 34D CH A312 OBC PH
Max. coverage per hour @ 3.12 MPH	46,675 sq ft (4,336 sq m)
Scrub pressure - regular scrub	90 lb (39 kg)
Scrub pressure - heavy scrub	150 lb (65 kg)
Scrub pressure - extreme scrub	220 lb (96 kg)
Sealed waterlift	46.1 in of H2O (11.48 kPa)
Max. airflow rate (cfm)	76.5 (36 L/sec)
Body length	60 in (152 cm)
Body height	55 in (140 cm)
Body width	30 in (76 cm)
Max. width w/o squeegee	35.8 in (91 cm) (Doorway)
Max. weight w/o batteries	547 lb (257.6 kg)
Cleaning path	34 in (86 cm)
Squeegee width	41.4 in (105 cm)
Max. PSI	175 PSI (12.3 kg/sq cm) Full tank and 200 lb rider
Low flow rate	0.33 gal/min (1.25 L/ min)
Medium flow rate	0.60 gal/min (2.27 L/ min)
High flow rate	0.80 gal/min (3.03 L/ min)
Gradeability - Cleaning	4.5%, 7.9 degrees
Agency approval	CSA, ETL Canada and US

 $\bullet$  Standard equipment,  $\circ$  Supplementary accessories,  $\square$  Mountable equipment

	Accessories	Ref. no.	Min. required	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
Pad Boost						
	PAD-BLACK-14X28-5/CS	997000	0			
	PAD-BLACK-14X28-10/CS	997016	0			
0	PAD-BLUE-14X28-5/CS	997006	0			
	PAD-MAROON-14X28-10/CS	997018	0			



	Accessories	Ref. no.	Min. required	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
	PAD-RED-14X28-5/CS	997001	0			
0	PAD-WHITE-14X28-5/CS	997002	0			
	SCR SAND 14X28 80GRIT CS/10EA	997009	0			
	SCR SAND 14X28 100GRIT CS/10EA	997010	0			
	SCR SAND 14X28 120GRIT CS/10EA	997011	0			
	VELCRO 2 SIDE SHT 14X28 BOOST	30794A	0			
Detergent Equ	uipment					
	CHEMICAL INJECTION KIT	56114088	0	0	0	0
Disc Brush 34	0 mm					
	BRUSH ASM-HEAVY GRIT 13.5	56114227	0	0	0	0
	BRUSH ASM-MEDIUM GRIT 13.5	56114226	0	0	0	0
(CO)	BRUSH ASM-POLY 13.5	56114223	0	0	0	0
	BRUSH ASM-SOFT NYLON 13.5	56114224	0	0	0	0
Disc Brush 42	0 mm					
	BRUSH ASM-HEAVY GRIT 16.5	56114232	0			
9	BRUSH ASM-MEDIUM GRIT 16.5	56114231	0			
	BRUSH ASM-POLY 16.5	56114228	0			
0	BRUSH ASM-SOFT NYLON 16.5	56114229	0			
Pad Holder						
	PAD DRIVER ASM 13.75	56114242	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
	PAD DRIVER ASM 16.75	56114243	0			
Light Option						
	KIT-WARNING BEACON	56114253	0	0	0	0
Squeegee, Bl	ade, Skirt and Splash Guard					
	BLADE FRONT 28	56601248	0	0	0	0
	BLADE KIT GUM	56114359	0			
	BLADE KIT RED GUM	56114361	0			
	BLADE-FRONT-STANDARD-34	56601275	0			
Deck Blade						
	SIDE SKIRT KIT GUM 24/610	56114364	0	0	0	0
	SIDE SKIRT KIT PU 24/610	56114366	0	0	0	0
P	SIDE SKIRT KIT RED 24/610	56114368	0	0	0	0
Squeegee Bla	ade					
700	BLADE KIT-SQUEEGEE-GUM 28	56382734	0	0	0	0
	BLADE KIT-SQUEEGEE-GUM 34	56382738	0			
	BLADE KIT-SQUEEGEE-PU 34	56382740	0			
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0			•
Other						
<b>S</b>	ARM REST LH & RH	7-03-04249	0	0	0	0
	KIT SEAT BELT	56422162	0	0	0	0
	KIT VACUUM WAND WITH CADDY	56601087	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 28D W310 OBC PH	FOCUS II R 28D CH W310 OBC PH	FOCUS II R 28D W420 SC PH
438	PAD RETAINER	56505195	0	0	0	0
Flap and Skir	t					
	BLADE FRONT 28	56601521	0	0	0	0
	BLADE-FRONT-PU-34	56601522	0			
Battery	Battery					
	KIT BATTERY WATERING	56601527	0	0	0	0

ullet Standard equipment,  $\sc\$  Supplementary accessories,  $\sc\$  Mountable equipment

	Accessories	Ref. no.	Min. required	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH	
Pad Boost							
	PAD-BLACK-14X28-5/CS	997000	0				
	PAD-BLACK-14X28-10/CS	997016	0				
0	PAD-BLUE-14X28-5/CS	997006	0				
	PAD-MAROON-14X28-10/CS	997018	0				
	PAD-RED-14X28-5/CS	997001	0				
0	PAD-WHITE-14X28-5/CS	997002	0				
	SCR SAND 14X28 80GRIT CS/10EA	997009	0				
	SCR SAND 14X28 100GRIT CS/10EA	997010	0				
	SCR SAND 14X28 120GRIT CS/10EA	997011	0				
	VELCRO 2 SIDE SHT 14X28 BOOST	30794A	0				
Detergent Eq	Detergent Equipment						
	CHEMICAL INJECTION KIT	56114088	0	0	0	0	



	Accessories	Ref. no.	Min. required	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH
Disc Brush 34	0 mm					
	BRUSH ASM-HEAVY GRIT 13.5	56114227	0	0	0	0
	BRUSH ASM-MEDIUM GRIT 13.5	56114226	0	0	0	0
(*)(*)(*)	BRUSH ASM-POLY 13.5	56114223	0	0	0	0
	BRUSH ASM-SOFT NYLON 13.5	56114224	0	0	0	0
Disc Brush 42	20 mm		1			
	BRUSH ASM-HEAVY GRIT 16.5	56114232	0			
9	BRUSH ASM-MEDIUM GRIT 16.5	56114231	0			
	BRUSH ASM-POLY 16.5	56114228	0			
0	BRUSH ASM-SOFT NYLON 16.5	56114229	0			
Pad Holder						
	PAD DRIVER ASM 13.75	56114242	0	0	0	0
	PAD DRIVER ASM 16.75	56114243	0			
Light Option						
	KIT-WARNING BEACON	56114253	0	0	0	0
Squeegee, Bl	ade, Skirt and Splash Guard					
	BLADE FRONT 28	56601248	0	0	0	0
	BLADE KIT GUM	56114359	0			
	BLADE KIT RED GUM	56114361	0			
	BLADE-FRONT-STANDARD-34	56601275	0			
Deck Blade						
3	SIDE SKIRT KIT GUM 24/610	56114364	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 28D CH W420 SC PH	FOCUS II R 28D A312 OBC PH	FOCUS II R 28D CH A312 OBC PH
	SIDE SKIRT KIT PU 24/610	56114366	0	0	0	0
	SIDE SKIRT KIT RED 24/610	56114368	0	0	0	0
Squeegee Bl	ade					
70	BLADE KIT-SQUEEGEE-GUM 28	56382734	0	0	0	0
	BLADE KIT-SQUEEGEE-GUM 34	56382738	0			
	BLADE KIT-SQUEEGEE-PU 34	56382740	0			
Battery Wet		·				
	BATTERY 6V 420AH WET	56388582	0	•		
Other						
S.	ARM REST LH & RH	7-03-04249	0	0	0	0
	KIT SEAT BELT	56422162	0	0	0	0
	KIT VACUUM WAND WITH CADDY	56601087	0	0	0	0
400	PAD RETAINER	56505195	0	0	0	0
Flap and Skir	t					
	BLADE FRONT 28	56601521	0	0	0	0
	BLADE-FRONT-PU-34	56601522	0			
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	0



### Rider Floor Scrubbers

 $\bullet$  Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
Pad Boost						
	PAD-BLACK-14X28-5/CS	997000	0	0	0	0
	PAD-BLACK-14X28-10/CS	997016	0	0	0	0
0	PAD-BLUE-14X28-5/CS	997006	0	0	0	0
	PAD-MAROON-14X28-10/CS	997018	0	0	0	0
	PAD-RED-14X28-5/CS	997001	0	0	0	0
0	PAD-WHITE-14X28-5/CS	997002	0	0	0	0
	SCR SAND 14X28 80GRIT CS/10EA	997009	0	0	0	0
	SCR SAND 14X28 100GRIT CS/10EA	997010	0	0	0	0
	SCR SAND 14X28 120GRIT CS/10EA	997011	0	0	0	0
	VELCRO 2 SIDE SHT 14X28 BOOST	30794A	0	0	0	0
Detergent Equ	uipment					
	CHEMICAL INJECTION KIT	56114088	0	0	0	0
Disc Brush 34	0 mm					
(200)	BRUSH ASM-HEAVY GRIT 13.5	56114227	0			
	BRUSH ASM-MEDIUM GRIT 13.5	56114226	0			
Sils/is	BRUSH ASM-POLY 13.5	56114223	0			
	BRUSH ASM-SOFT NYLON 13.5	56114224	0			
Disc Brush 42	0 mm					



	Accessories	Ref. no.	Min. required	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
	BRUSH ASM-HEAVY GRIT 16.5	56114232	0			
9	BRUSH ASM-MEDIUM GRIT 16.5	56114231	0			
	BRUSH ASM-POLY 16.5	56114228	0			
6	BRUSH ASM-SOFT NYLON 16.5	56114229	0			
Pad Holder		'			'	
	PAD DRIVER ASM 13.75	56114242	0			
6	PAD DRIVER ASM 16.75	56114243	0			
Light Option						
	KIT-WARNING BEACON	56114253	0	0	0	0
Squeegee, Bl	ade, Skirt and Splash Guard					
	BLADE FRONT 28	56601248	0			
	BLADE KIT GUM	56114359	0	0	0	0
	BLADE KIT RED GUM	56114361	0	0	0	0
	BLADE-FRONT-STANDARD-34	56601275	0			
Deck Blade						
3	SIDE SKIRT KIT GUM 24/610	56114364	0			
	SIDE SKIRT KIT PU 24/610	56114366	0			
P	SIDE SKIRT KIT RED 24/610	56114368	0			
Squeegee Bla	nde					
70	BLADE KIT-SQUEEGEE-GUM 28	56382734	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 28B W310 OBC PH	FOCUS II R 28B CH W310 OBC PH	FOCUS II R 28B W420 SC PH
	BLADE KIT-SQUEEGEE-GUM 34	56382738	0			
	BLADE KIT-SQUEEGEE-PU 34	56382740	0			
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0			•
Other						
	ARM REST LH & RH	7-03-04249	0	0	0	0
	KIT SEAT BELT	56422162	0	0	0	0
	KIT VACUUM WAND WITH CADDY	56601087	0	0	0	0
420	PAD RETAINER	56505195	0			
Flap and Skirt	Flap and Skirt					
	BLADE FRONT 28	56601521	0			
	BLADE-FRONT-PU-34	56601522	0			
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	0

 $<sup>\</sup>bullet$  Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

Accessories		Ref. no.	Min. required	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
Pad Boost						
	PAD-BLACK-14X28-5/CS	997000	0	0	0	0
	PAD-BLACK-14X28-10/CS	997016	0	0	0	0
0	PAD-BLUE-14X28-5/CS	997006	0	0	0	0
	PAD-MAROON-14X28-10/CS	997018	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
	PAD-RED-14X28-5/CS	997001	0	0	0	0
6	PAD-WHITE-14X28-5/CS	997002	0	0	0	0
	SCR SAND 14X28 80GRIT CS/10EA	997009	0	0	0	0
	SCR SAND 14X28 100GRIT CS/10EA	997010	0	0	0	0
	SCR SAND 14X28 120GRIT CS/10EA	997011	0	0	0	0
	VELCRO 2 SIDE SHT 14X28 BOOST	30794A	0	0	0	0
Detergent Eq	uipment					
	CHEMICAL INJECTION KIT	56114088	0	0	0	0
Disc Brush 3	40 mm	<u>'</u>	'			
(mg)	BRUSH ASM-HEAVY GRIT 13.5	56114227	0			
	BRUSH ASM-MEDIUM GRIT 13.5	56114226	0			
SHALL .	BRUSH ASM-POLY 13.5	56114223	0			
	BRUSH ASM-SOFT NYLON 13.5	56114224	0			
Disc Brush 42	20 mm					
	BRUSH ASM-HEAVY GRIT 16.5	56114232	0			
0	BRUSH ASM-MEDIUM GRIT 16.5	56114231	0			
	BRUSH ASM-POLY 16.5	56114228	0			
0	BRUSH ASM-SOFT NYLON 16.5	56114229	0			
Pad Holder						
	PAD DRIVER ASM 13.75	56114242	0			



	Accessories	Ref. no.	Min. required	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
(6)	PAD DRIVER ASM 16.75	56114243	0			
Light Option						
	KIT-WARNING BEACON	56114253	0	0	0	0
Squeegee, Bl	ade, Skirt and Splash Guard					
	BLADE FRONT 28	56601248	0			
	BLADE KIT GUM	56114359	0	0	0	0
	BLADE KIT RED GUM	56114361	0	0	0	0
	BLADE-FRONT-STANDARD-34	56601275	0			
Deck Blade						
3	SIDE SKIRT KIT GUM 24/610	56114364	0			
	SIDE SKIRT KIT PU 24/610	56114366	0			
P	SIDE SKIRT KIT RED 24/610	56114368	0			
Squeegee Bla	ade	'				
200	BLADE KIT-SQUEEGEE-GUM 28	56382734	0	0	0	0
	BLADE KIT-SQUEEGEE-GUM 34	56382738	0			
	BLADE KIT-SQUEEGEE-PU 34	56382740	0			
Battery Wet						
	BATTERY 6V 420AH WET	56388582	0	•		
Other						
N. S.	ARM REST LH & RH	7-03-04249	0	0	0	0
	KIT SEAT BELT	56422162	0	0	0	0
	KIT VACUUM WAND WITH CADDY	56601087	0	0	0	0



Accessories		Ref. no.	Min. required	FOCUS II R 28B CH W420 SC PH	FOCUS II R 28B A312 OBC PH	FOCUS II R 28B CH A312 OBC PH
428	PAD RETAINER	56505195	0			
Flap and Skir	t					
	BLADE FRONT 28	56601521	0			
	BLADE-FRONT-PU-34	56601522	0			
Battery	Battery					
	KIT BATTERY WATERING	56601527	0	0	0	0

ullet Standard equipment,  $\sc\$  Supplementary accessories,  $\sc\$  Mountable equipment

	Accessories	Ref. no.	Min. required	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Pad Boost						
	PAD-BLACK-14X28-5/CS	997000	0			
	PAD-BLACK-14X28-10/CS	997016	0			
0	PAD-BLUE-14X28-5/CS	997006	0			
	PAD-MAROON-14X28-10/CS	997018	0			
	PAD-RED-14X28-5/CS	997001	0			
0	PAD-WHITE-14X28-5/CS	997002	0			
	SCR SAND 14X28 80GRIT CS/10EA	997009	0			
	SCR SAND 14X28 100GRIT CS/10EA	997010	0			
	SCR SAND 14X28 120GRIT CS/10EA	997011	0			
	VELCRO 2 SIDE SHT 14X28 BOOST	30794A	0			
Detergent Eq	Detergent Equipment					
	CHEMICAL INJECTION KIT	56114088	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
Disc Brush 34	90 mm					
	BRUSH ASM-HEAVY GRIT 13.5	56114227	0			
	BRUSH ASM-MEDIUM GRIT 13.5	56114226	0			
CONTRACT OF STREET	BRUSH ASM-POLY 13.5	56114223	0			
	BRUSH ASM-SOFT NYLON 13.5	56114224	0			
Disc Brush 42	20 mm					
	BRUSH ASM-HEAVY GRIT 16.5	56114232	0	0	0	0
0	BRUSH ASM-MEDIUM GRIT 16.5	56114231	0	0	0	0
	BRUSH ASM-POLY 16.5	56114228	0	0	0	0
9	BRUSH ASM-SOFT NYLON 16.5	56114229	0	0	0	0
Pad Holder						
	PAD DRIVER ASM 13.75	56114242	0			
0	PAD DRIVER ASM 16.75	56114243	0	0	0	0
Light Option						
	KIT-WARNING BEACON	56114253	0	0	0	0
Squeegee, Bl	ade, Skirt and Splash Guard					
	BLADE FRONT 28	56601248	0			
	BLADE KIT GUM	56114359	0			
	BLADE KIT RED GUM	56114361	0			
	BLADE-FRONT-STANDARD-34	56601275	0	0	0	0
Deck Blade						
3	SIDE SKIRT KIT GUM 24/610	56114364	0	0	0	0



	Accessories	Ref. no.	Min. required	FOCUS II R 34D W420 SC PH	FOCUS II R 34D CH W420 SC PH	FOCUS II R 34D A312 OBC PH
	SIDE SKIRT KIT PU 24/610	56114366	0	0	0	0
	SIDE SKIRT KIT RED 24/610	56114368	0	0	0	0
Squeegee Bl	ade					
70	BLADE KIT-SQUEEGEE-GUM 28	56382734	0			
	BLADE KIT-SQUEEGEE-GUM 34	56382738	0	0	0	0
	BLADE KIT-SQUEEGEE-PU 34	56382740	0	0	0	0
Battery Wet		'				
	BATTERY 6V 420AH WET	56388582	0	•	•	
Other						
<b>S</b>	ARM REST LH & RH	7-03-04249	0	0	0	0
	KIT SEAT BELT	56422162	0	0	0	0
	KIT VACUUM WAND WITH CADDY	56601087	0	0	0	0
	PAD RETAINER	56505195	0			
Flap and Skir	t					
	BLADE FRONT 28	56601521	0			
	BLADE-FRONT-PU-34	56601522	0	0	0	0
Battery						
	KIT BATTERY WATERING	56601527	0	0	0	0



## Rider Floor Scrubbers

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

	Accessories	Ref. no.	Min. required	FOCUS II R 34D CH A312 OBC PH
Pad Boost				
	PAD-BLACK-14X28-5/CS	997000	0	
	PAD-BLACK-14X28-10/CS	997016	0	
0	PAD-BLUE-14X28-5/CS	997006	0	
	PAD-MAROON-14X28-10/CS	997018	0	
	PAD-RED-14X28-5/CS	997001	0	
0	PAD-WHITE-14X28-5/CS	997002	0	
	SCR SAND 14X28 80GRIT CS/10EA	997009	0	
	SCR SAND 14X28 100GRIT CS/10EA	997010	0	
	SCR SAND 14X28 120GRIT CS/10EA	997011	0	
	VELCRO 2 SIDE SHT 14X28 BOOST	30794A	0	
Detergent Equ	uipment			
	CHEMICAL INJECTION KIT	56114088	0	0
Disc Brush 34	10 mm			
	BRUSH ASM-HEAVY GRIT 13.5	56114227	0	
	BRUSH ASM-MEDIUM GRIT 13.5	56114226	0	
Seleting of	BRUSH ASM-POLY 13.5	56114223	0	
	BRUSH ASM-SOFT NYLON 13.5	56114224	0	
Disc Brush 42	20 mm			



	Accessories	Ref. no.	Min. required	FOCUS II R 34D CH A312 OBC PH
	BRUSH ASM-HEAVY GRIT 16.5	56114232	0	0
9	BRUSH ASM-MEDIUM GRIT 16.5	56114231	0	0
	BRUSH ASM-POLY 16.5	56114228	0	0
6	BRUSH ASM-SOFT NYLON 16.5	56114229	0	٥
Pad Holder			'	
	PAD DRIVER ASM 13.75	56114242	0	
6	PAD DRIVER ASM 16.75	56114243	0	0
Light Option				
	KIT-WARNING BEACON	56114253	0	0
Squeegee, Bl	ade, Skirt and Splash Guard			
	BLADE FRONT 28	56601248	0	
	BLADE KIT GUM	56114359	0	
	BLADE KIT RED GUM	56114361	0	
	BLADE-FRONT-STANDARD-34	56601275	0	0
Deck Blade				
3	SIDE SKIRT KIT GUM 24/610	56114364	0	0
	SIDE SKIRT KIT PU 24/610	56114366	0	0
P	SIDE SKIRT KIT RED 24/610	56114368	0	0
Squeegee Bla	ide			
200	BLADE KIT-SQUEEGEE-GUM 28	56382734	0	



Accessories		Ref. no.	Min. required	FOCUS II R 34D CH A312 OBC PH
	BLADE KIT-SQUEEGEE-GUM 34	56382738	0	0
	BLADE KIT-SQUEEGEE-PU 34	56382740	0	0
Battery Wet				
	BATTERY 6V 420AH WET	56388582	0	
Other				
	ARM REST LH & RH	7-03-04249	0	0
	KIT SEAT BELT	56422162	0	0
	KIT VACUUM WAND WITH CADDY	56601087	0	0
	PAD RETAINER	56505195	0	
Flap and Skirt				
	BLADE FRONT 28	56601521	0	
	BLADE-FRONT-PU-34	56601522	0	0
Battery				
	KIT BATTERY WATERING	56601527	0	0

