

Husqvarna Construction Products

Material Safety Data Sheet

17400 W 119th St Olathe, Kansas 66061 Phone 913-928-1000 Fax 913-438-7971

SECTION I - COMPANY & PRODUCT IDENTIFICATION

TRADE NAME: Husqvarna GM-3000

PRODUCT CODE: N/A

CHEMICAL NAME: Acrylic Resin

CAS #: Mixture, no single number applies

DATE: January 7, 2012

SECTION II - COMPOSITION FORMULA - COMPONENT INFORMATION

INTENTIONAL INGREDIENTS CAS #

No hazardous ingredients present

SECTION III - HAZARDS IDENTIFICATION

PERMISSIBLE EXPOSURE LEVEL: Undetermined

EYES: May cause irritation.

SKIN: Overexposure may cause some skin dryness.

INHALATION: Overexposure may cause irritation of upper respiratory tract.

INGESTION: May cause nausea.

THIS MATERIAL IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA

SECTION IV - FIRST AID MEASURES

EYE CONTACT: Flush with water lifting eyelids.

SKIN CONTACT: Wash skin with soap and water.

INHALATION: Remove victim to fresh air.

INGESTION: Do not induce vomiting. Give plenty of water and milk of magnesia.

SECTION V - FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT: None/Setaflash (ASTM 93)

FLAMMABLE LIMITS: N/A

LOWER: N/A

UPPER: N/A

FIRE/EXPLOSION HAZARDS: No unusual hazards.

EXTINGUISHING MEDIA: Foam, CO2, dry chemical

FIRE FIGHTING PROCEDURES: Fire fighters should wear self-contained breathing apparatus with a full-face piece operated in the positive pressure demand mode and full protective clothing. Use water spray to cool nearby containers and structures.

HMIS HAZARD CLASS: Health =1 Flammability =0 Reactivity =0 Other =NA

Ranking: 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

SECTION VI - ACCIDENTAL RELEASE PROCEDURES

SMALL SPILLS: Mop with water and flush to drain with plenty of water.

LARGE SPILLS: Contain with dike, absorb or vacuum to storage container. Dispose in accordance with all regulations.

SECTION VII - HANDLING & STORAGE

STORAGE: Keep cool and dry

HANDLING: Avoid heat.

SECTION VIII - EXPOSURE CONTROL/PERSONAL PROTECTION

EYE AND FACIAL: None required under normal conditions.

SKIN: None required under normal conditions.

RESPIRATORY: None required under normal conditions.

VENTILATION: Local mechanical ventilation is acceptable

OTHER: None required under normal conditions.

Husqvarna Construction Products
Material Safety Data Sheet
17400 W 119th St Olathe, Kansas 66061 Phone 913-928-1000 Fax 913-438-7971

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: F 210 SOLUBILITY: Miscible pH: 8 VOC: 0 %
PERCENT VOLATILE: 85 VAPOR DENSITY: N/A VAPOR PRESSURE: N/A
EVAPORATION RATE (BUTYL ACETATE=1): N/A SPECIFIC GRAVITY: 1.11
APPEARANCE & ODOR: Milky white semi viscous liquid, characteristic odor.

SECTION X - STABILITY & REACTIVITY INFORMATION

STABILITY: Stable
REACTIVITY: N/A
HAZARDOUS DECOMPOSITION INGREDIENTS: CO₂ & CO.
HAZARDOUS POLYMERIZATION: Will not occur

SECTION XI - TOXICOLOGICAL INFORMATION

No toxicological information has been generated for this material

SECTION XII - ECOLOGICAL INFORMATION

This product has never been found to present any environmental or ecological problems. Use according to the instructions. Dispose of in a sanitary manner.

SECTION XIII - DISPOSAL CONSIDERATION

Dispose in accordance with federal, state and local regulations. Usually may be flushed down drain with large amounts of water.

SECTION XIV - TRANSPORT INFORMATION

DOT HAZARD CLASS: None.
DOT SHIPPING NAME: Cleaning compound, NOI.

SECTION XV - REGULATORY INFORMATION

U.S. Federal Regulations: TSCA-Intentional ingredients are listed; CERCLA RQ-N/A; SARA 302 Components-N/A; Section 311/312-N/A; Section 313 Components-N/A

SECTION XVI - OTHER INFORMATION

Refer to product label for directions and any other cautions.

LEGEND: ND, Not Determined; N/A Not Applicable; NA, Not Available.

NOTICE

All information appearing herein is based upon data obtained from chemical manufacturers and or recognized technical sources. While the information is believed to be accurate, Snyder Manufacturing Corporation makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Snyder Manufacturing Corporation's control and therefore users are responsible for and assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.