




- Brass Manifold
- Solid Ceramic Plungers
- Stainless Steel Plunger Guides and Check Valves
- Bronze Connecting Rods
- Heavy Duty Flat Base High Pressure Seals
- 57.6 oz. Capacity Vented Oil Bath Crank Case
- Max Fluid Temp, 160°F

NKC Series Direct Drive, Hydraulic Flange Plunger Pumps

NKC Series super duty plunger pumps include a wide range of models with flow rates from 12.5 to 37.8 GPM and pressures up to 5075 PSI.

Other drive options include 30mm solid shaft or gas engine gear reduction

Applications include general pressure cleaning,, construction, hydro-excavation UHP fire fighting, mining and street cleaning.

	Model	Flow		Pressure		Plunger Dia.	Crankshaft		Power	Seal Kit	Valve Kit	Wt.
		GPM	l/min	PSI	bar		Stroke	Code				
1450 RPM	NKC 47/350 R MI	12.5	47.1	5075	350	22mm	30.0mm	F	42.5 EBHP	6061.10	6061.J1	67 lbs
	NKC 55/300 R MI	14.1	53.4	4350	300	22mm	34.0mm	7	41.1 EBHP	6061.10	6061.J1	67 lbs
	NKC 60/250 R MI	16.1	60.9	3625	250	25mm	30.0mm	F	39.0 EBHP	6061.11	6061.94	67 lbs
	NKC 70/250 R MI	18.2	69.0	3625	250	25mm	34.0mm	7	44.2 EBHP	6061.11	6061.94	67 lbs
	NKC 75/170 R MI	19.9	75.1	2465	170	28mm	30.0mm	F	32.8 EBHP	6061.12	6061.M6	67 lbs
	NKC 85/170 R MI	23.0	87.0	2465	170	28mm	34.0mm	7	37.9 EBHP	6061.12	6061.M6	67 lbs
	NKC 100/150 R MI	26.4	100.0	2175	150	30mm	34.0mm	7	38.4 EBHP	6072.02	6061.M6	67 lbs
	NKC 130/130 R MI	33.3	126.2	1885	130	36mm	30.0mm	F	42.1 EBHP	6061.Q1	6061.S7	67 lbs
	NKC 145/100 R MI	37.8	143.0	1450	100	36mm	34.0mm	7	36.7 EBHP	6061.Q1	6061.S7	67 lbs


NOTE: All pump models available with left-hand drive option. Substitute 'L' for 'R' in model number when ordering (ex. NKC 145/100 L MI)



NKC 60/250 R MI

MAX FLOW
MAX PRESSURE
RATED PUMP SPEED
POWER REQUIREMENT
LUBRICATION

16.1 GPM / 60.9 L/MIN
3625 PSI / 250 BAR
1450 RPM
39.0 HP ELECTRIC
57.6 OZ UDOR LUBE



Revised 2-23-2022

Part #	Description	Qty
0002.09	CRANKSHAFT MI	1
0007.26	OIL SEAL D35	3
0007.59	OIL SEAL	1
0014.01	PLUNGER GUIDE	3
0023.94	UPPER RING D25 ^{D E}	3
0115.06	BUSHING D35	3
0208.26	OIL SIGHT GLASS	1
0208.B3	BACK COVER	1
0209.51	CRANKCASE	1
0248.08	BALL BEARING	2
0301.36	SLINGER RING ^A	3
0302.13	SPACER	3
0501.35	BEARING FLANGE	1
0517.18	BEARING FLANGE – MI	1
0602.51	GASKET – PUMP BODY	1
0605.43	GASKET – D17	1
0614.15	SET SCREW	3
0635.06	HIGH PRESSURE SEAL KIT D25 ^{B E}	3
1101.23	O-RING – VALVE PLUG ^E	6
1101.60	O-RING – PLUNGER BOLT ^A	3
1101.A9	O-RING – PRESSURE RING ^{B D E}	3
1101.B8	O-RING – VALVE ^{C E}	6
1101.H6	O-RING – OIL SIGHT GLASS	1
1101.Q1	O-RING – BEARING FLANGE	4
1205.02	CERAMIC PLUNGER D25	3
1208.46	PLATE	1
1221.14	PRESSURE RING D25 ^{D E}	3
1240.R9	LIFTING HOOK M10	1
1401.05	RIVET 3.5X8	2
1401.06	RIVET D4X10	2
1403.14	WASHER – PLUNGER BOLT ^A	3
1403.57	WASHER M8	6
1411.02	SERRATED WASHER D8	6
1411.03	WASHER	16

Part #	Description	Qty
1412.19	BONDED WASHER D21.5	1
1412.25	BONDED WASHER D33.9 (G1")	1
1502.22	PIN	3
1506.36	SNAP RING	2
1512.09	PIN D5X20	6
1534.07	GASKET - BEARING FLANGE	1
1534.08	SPACER / GASKET	1
1603.62	PLUG G1/2"	1
1603.64	PLUG 3/8"	1
1603.B8	OIL SIGHT GLASS W/GASKET	1
1603.C5	PLUG G1"	1
1603.K2	VALVE PLUG D25 ^E	6
1604.K1	HEAD D25 ^E	1
1625.19	OIL CAP W/GASKET	1
1804.22	HEX BOLT	8
1805.02	ALLEN BOLT	8
1805.23	ALLEN BOLT M8X40	6
1805.62	ALLEN BOLT M6X20	12
1807.19	PLUNGER BOLT ^A	3
6002.L1	CRANKCASE ASSEMBLY	1
6006.48	VALVE ^C	6
6017.23	COMPLETE MANIFOLD ASSEMBLY NK D25	1
6020.02	CONNECTING ROD	3
6030.30	LOW PRESSURE SEAL KIT D25 ^{B E}	3
6180.01	CONNECTING ROD ASS'Y COMPLETE	3
6061.11	WATER SEAL KIT (KIT 11)	1
6061.94	VALVE KIT (KIT 93)	1
6061.P2	BRASS RING KIT D25 (KIT 212)	1
6061.Z8	PLUNGER BOLT KIT (KIT 254)	1

^A Parts in 6061.Z8 (Kit 254).

^B Parts in 6061.11 (Kit 11).


^c Parts in 6061.94 (Kit 93).

D Parts in 6072.P2 (Kit 212).

^E Parts in 6017.23 (Complete Manifold Assembly).

*Dimensional Drawings are
Shown in Millimeters.
To Convert to Inches,
Multiply Dimension x 0.03937*

NK SERIES PUMPS - MI Flange, 22/25mm Plungers



TORQUE SPECS

Ref.	Description	Ft./lb.	Nm	Loctite®
1	Head Bolts	37	50	-
2	Valve Caps	88	120	243
3	Inlet Cap	133	180	-
4	Outlet Cap	88	120	243
5	Bearing Flange Bolts	37	50	-
6	Rear Cover Bolts	8	11	-
7	Connecting Rod Bolts	19	25	243
8	Plunger Bolts	22	30	270
9	Valve Cover Bolts	-	-	-
10	Oil Drain Plug	8	11	-

