SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME : QUAKE

SYNONYMS : Product is a mixture: No synonyms are available.

PRODUCT USE : Moderately Alkaline Material

SUPPLIER : HYDRAMASTER CORP. **SUPPLIER'S ADDRESS** : 1500 Industry St. Suite 300

Everett, WA 98203 (425) 775-7272

EMERGENCY RESPONSE PHONE: PERS: 1-800-633-8253

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS U.S. – CLASSIFICATION : H302 Harmful if swallowed.

: H315 Causes skin irritation

: H319 Causes serious eye irritation

LABEL ELEMENTS : GHS – US HAZARD PICTOGRAMS The product is classified and labeled according

to the Globally Harmonized System (GHS).

HAZARD PICTOGRAMS :

SIGNAL WORD : DANGER

HAZARD STATEMENTS: H302 Harmful if swallowed.

P101

: P102

(GHS-US)

: H314 Causes severe skin burns and eye damage.

: H318 Causes serious eye damage.

PRECAUTIONARY STATEMENTS

(GHS-US)

: P103 Read label before use.

P264 Wash skin and contaminated clothing thoroughly after handling.

: P270 Do not eat, drink, or smoke when using this product.

Keep out of reach of children.

P280 Wear suitable protective gloves / protective clothing / eye protection /

If medical advice is needed, have product container or label at hand.

face protection.

: P301+ IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

P312 unwell.

: P302+P352 IF ON SKIN: Wash with plenty of soap and water.

: P305+351+ IF IN EYES: Rinse cautiously with water for several minutes. Remove

P338 contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with

local/regional/national/international regulations

CLASSIFICATION SYSTEM : NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4) : Health = 2, Fire = 0, Reactivity = 0 HMIS RATINGS (SCALE 0-5) : Health = 2, Fire = 0, Reactivity = 0

SECTION 3 - COMPOSITON/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTIC

Mixtures

DESCRIPTION

Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS#	EINECS #	GHS CLASSIFICATION	
Potassium Hydroxide	1-5	1310-58-3	215-181-3	Metal Corr Cat 1, Skin Corr Cat. 1A	
				Eye Dam Cat. 1, Aquatic Acute Cat 4	
Sodium Tripolyphosphate	1-5	7758-29-4	231-838-7	Skin & Inhalation Irrit. Cat 4	
Ethylene Glycol Monobutyl Ether	1-5	111-76-2	203-905-0	Acute Oral Tox Cat 4, Eye Irrit Cat 2A,	
				Skin Irrit Cat 2	
Sodium Dodecylbenzene Sulfonate	1-5	25155-30-0	246-680-4	Skin Irrit Cat 4, Eye Dam Cat 2	
				Acute Tox Cat 4, STOT-SE Cat 3	
Laurydimethylamine Oxide	1-5	1643-20-5	216-700-6	Eye Irrit Cat 2B	

Irrit = Irritation, Corr = Corrosion, Cat = Category, Dam = Damage, Tox = Toxic, STOT-SE = Single Target Organ Toxicity Single exposure.

SECTION 4 - FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL

: Never give anything by mouth to an unconscious person. If you feel unwell, seek

medical advice. Show the label where possible.

EYE CONTACT

Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to

ensure adequate flushing. Get immediate medical attention.

SKIN CONTACT

Remove contaminated clothing and shoes. Wash affected skin area with soap and water. Delayed skin damage is possible if product is not completely washed off. Get

immediate medical attention.

SWALLOWING (INGESTION)

If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate medical attention.

INHALATION

Remove to fresh air. Get immediate medical attention.

OTHER INSTRUCTIONS

Rescue personnel must wear appropriate protective equipment during removal of

victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

SPECIAL PROTECTIVE

EQUIPMENT AND PRECAUTIONS FOR FIRE

FIGHTERS

UNUSUAL FIRE AND **EXPLOSION HAZARDS** : Dry chemical, foam, water, or carbon dioxide.

: In the event of a fire, wear a NIOSH (USA) or CEN (EU) approved, positive pressure, self-contained breathing apparatus (SCUBA) and full protective clothing. Evacuate all

non-essential personnel from the danger area.

No further relevant information is available.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, **PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES**

: Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.

ENVIRONMENTAL PROCEDURES METHODS AND MATERIALS

FOR CONTAINMENT AND **CLEAN-UP**

: Keep spilled material away from sewage/drainage systems and waterways.

All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an

appropriate absorbent material such as clay or vermiculite. Place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE

HANDLING

: Use with adequate ventilation. Wear proper protective equipment. Do not mix with water or acids without proper dilution and agitation to prevent a potentially violent reaction.

CONDITIONS FOR SAFE

STORAGE

: Store in closed, properly labeled containers. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.





SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

TLV (THRESHOLD LIMIT VALUE)

The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH – TLV	ACGIH – STEL	
Potassium Hydroxide	2 mg/m ³	Not Established	2 mg/m³ (Ceiling)	
Sodium Tripolyphosphate	Not Established	Not Established	Not Established	
Ethylene Glycol Monobutyl Ether	50 ppm	20 ppm	Not Established	
Sodium Dodecylbenzene Sulfonate	Not Established	Not Established	Not Established	
Laurydimethylamine Oxide	Not Established	Not Established	Not Established	

EYE PROTECTION: Wear chemical splash goggles or face shield.

SKIN PROTECTION : Minimize contact with product. Wear chemical resistant coveralls, boots, gloves,

apron and/or suitable long-sleeved clothing.

RESPIRATORY PROTECTION : In case of brief exposure use respiratory filter device. In case of intensive or longer

exposure, use respiratory protective device that is independent of circulating air.

VENTILATION : Ensure adequate ventilation.

ADDITIONAL MEASURES : Emergency eyewash and safety shower facilities should be available in the

immediate work area.

REQUIRED WORK/HYGIENE: Wash hands thoroughly after handling. Keep away from all food stuffs, beverages,

and feed. Do not eat, drink, or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE : Clear light amber liquid with mild odor.

ODOR : Slight sweet odor.
ODOR THRESHOLD : Not available
PH : > 13.5

MELTING POINT/FREEZING

POINT

: Not available

BOILING POINT : Approx. 212°
FLASH POINT : Above 200 Degr. F
EVAPORATION RATE : Not available

FLAMMABILITY : Nonflammable, Noncombustible

LOWER FLAMMABILITY LIMIT Not available **UPPER FLAMMABILITY LIMIT** Not available **VAPOR PRESSURE** Not available **VAPOR DENSITY (AIR=1)** Not available

RELATIVE DESNITY 1.06

SOLUBILITY IN WATER PARTITION COEFFICIENT n-

Not available

Soluble in water

OCTANOL/WATER

AUTOIGNITION TEMPERATURE : Not available **DECOMPOSITION** : Not available

TEMPERATURE

SECTION 10 – STABILITY AND REACTIVITY

STABILITY : Stable under recommended storage conditions.

HAZARDOUS CONDITONS TO

No decomposition if used according to specifications

AVOID

INCOMPATIBLE MATERIALS Keep away from strong acids.

HAZARDOUS DECOMPOSITION

PRODUCTS

No dangerous decomposition products known.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Potassium Hydroxide

Draize test, rabbit, skin: 50 mg/24H Severe; Oral, rat: LD50 = 273 mg/kg; <BR. LD50

values: Potassium Hydroxide: Oral (rat): 214 mg/kg. LC50 dermal and inhalation:

Not listed.

EYE CONTACT : Causes severe eye damage.

SKIN CONTACT : Causes skin burns. Onset of symptoms may be delayed following exposure.

INHALATION Corrosive to respiratory tract.

INGESTION : May be harmful if swallowed. Ingestion may cause chemical burns, pain, vomiting,

difficulty breathing and other gastrointestinal effects.

CARCINOGENICITY The components of this product are not classified as carcinogenic by OSHA, NTP

IARC or CA Prop 65.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Asthma and other respiratory conditions, skin disorders.

TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Sodium Tripolyphosphate

Oral - rat LD50 - 5,400 mg/kg; practically non-toxic

Dermal - rabbit LD50 - > 7,940 mg/kg; practically non-toxic

Eye Irritation - rabbit - 3.3/110.0; slightly irritating Skin Irritation - rabbit - 0-0/8.0 (24-hr exp.); not irritating

Inhalation - LC50 > 0.39 mg/L (rat, 4 hr) (maximum attainable concentration)

TOXICOLOGICAL INFORMATION

ACUTE ORALTOXICITY

Ethylene Glycol Monobutyl Ether

LD50 Oral: 1,414 mg/kg Species: guinea pig Remarks: Ingestion may cause weakness, confusion, anxiety, decreased blood pressure, and CNS depression with collapse and

coma. LD50 Oral (rat): 1746 mg/kg.

ACUTE INHALATION TOXICITY LC50: ~ 932 ppm Exposure time: 4 HOURS Species: guinea pig Remarks: Exposure to

> vapor may cause irritation of the eyes, nose, and respiratory tract. May cause nausea. May cause headaches. Extensive and prolonged contact with skin may cause confusion, anxiety, decreased blood pressure, and CNS depression with collapse and

coma. LC50 Inhalation (rat) 7hr: ~ 700 ppm.

ACUTE DERMAL TOXICITY LD50: > 2,000 mg/kg Species: guinea pig Remarks: Minimal hazard by skin contact

with liquid or vapor. This material may be absorbed through the skin. High dermal doses (most likely achieved from exposure to undiluted liquid) may cause weakness, headache, and nausea. Extensive and prolonged contact with skin may cause confusion, anxiety, decreased blood pressure, and CNS depression with collapse and

IRRITATION : Skin: Repeated or prolonged contact may cause skin irritation.

Eyes: Moderate to severe eye irritant.

SENSITISATION : Did not cause sensitization on lab animals.

CARCINOGENICITY : No component of this product present at levels greater than or equal to 0.1% is

identified as probable or confirmed human carcinogen by IARC, ACGIH, NTP, and

OSHA.

TOXICOLOGICAL INFORMATION : Sodium Dodecylbenzene Sulfonate

ACUTE TOXICITY : LD50 Oral rat: 438 mg/kg.

INHALATION TOXICITY : No data available DERMAL TOXICITY : No data available

SKIN CORROSION/IRRITATION: Skin – rabbit Result: Skin irritation - 24 h

SERIOUS EYE : Eyes – rabbit Result: Severe eye irritation - 24 h

DAMAGE/IRRITATION

RESPIRATORY/SKIN: No data available

SENSITISATION

GERM CELL MUTAGENICITY: No data available

CARCINOGENICITY : No components of this product present at levels greater than or equal to 0.1% are

identified as probable, possible, or confirmed human carcinogen by IARC ACGIH, NTP

or OSHA.

TOXICOLOGICAL INFORMATION : Lauryldimethylamine Oxide

ACUTE TOXICITY : LD50 Oral (Rat): >2000mg/kg, Skin (rabbit): Moderate to severe irritant, Eyes

(rabbit): Severe irritant.

FURTHER INFORMATION : Information given is based on data on the components and the toxicology of similar

products. No data is available on the product itself.

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION : Potassium Hydroxide

ECOTOXICITY : Fish: Mosquito Fish: LC50 = 80.0 mg/L; 24 Hr.; Unspecified No data available.

ENVIRONMENTAL : No information found. **PHYSICAL** : No information found.

OTHER : No relevant information available.

PERSISTENCE AND : No relevant information available.

DEGRADABILITY

BIOACCUMULATIVE POTENTIAL: No relevant information available.

NOTES

: Water hazard class 1 (Self-assessment): slightly hazardous for water. Do not allow

undiluted product or large quantities of this product to reach ground water, water course or sewage system. Must no reach bodies of water or drainage ditch undiluted or un-neutralized. Rinse off larger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic

organisms.

ECOLOGICAL INFORMATION : Sodium Tripolyphosphate

ECOTOXICITY: Invertebrate: 48-hr LC50 Daphnia magna: > 1000 mg/L; Practically Nontoxic 96 hr. LC 50 > 100 mg/L, non-toxic (Rainbow trout, Inland silversides, and mysid shrimp). [FMC 189-1081, 1082 & 1083] 48 hr. LC 50> 100 mg/L, non-toxic (Daphnia magna) [FMC

189-1084]

PERSISTENCE and DEGRADABILITY

: No data available.

ENVIRONMENTAL FATE

Phosphates: Inorganic phosphates, including this product, at high concentrations in the environment have the potential to cause eutrophication in aquatic systems. This condition is characterized by excessive algal growth, and subsequent decreases in oxygen levels. In general, proper use and disposal of this product should pose no

adverse ecological risk.

ECOLOGICAL INFORMATION

: Ethylene Glycol Monobutyl Ether

ECOTOXICITY

: Fish: 96h LC50:>100 mg/L (Oryzias Latipes)

Crustacea: 48h EC50:>1000 mg/L (Daphnia magna)

Algae: 72h EC50:630 mg/L (Selenastrum capricornutum)

PERSISTENCE AND

96.0% (by BOD), 96.0% (by TOC), 100% (by GC).

DEGRADABILITY
MOBILITY IN SOIL

: No data available.

ECOLOGICAL INFORMATION

Lauryldimethylamine Oxide

ECOTOXICITY (Aquatic Toxicity):

LC50 Species: Brachy danio rerio (zebra fish) Concentration: 10,00 - 100,00 mg/l

Exposure time: 96 h.

TOXICITY TO DAPHNIA /

: Immobilization EC50 Species: Daphnia magna (Water flea) Concentration: 4,40 mg/l Exposure time: 48 h.

AQUATIC INVERTEBRATES

This material is subject to biodegradation.

BIODEGRADATION PERSISTENCE

: This material is believed to persist in the environment.

BIOCONCENTRATION

: This material is not expected to bio-concentrate in organisms.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

: This product must be disposed of in accordance with Federal, state, and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.

SECTION 14 – TRANSPORTATION INFORMATION

DOT/IMDG/ IATA PROPER

: UN1814, POTASSIUM HYDROXIDE, SOLUTION 8 PGII

SHIPPING NAME

HAZARD CLASS AND LABEL : 8 (Corrosive)
UN NUMBER : UN1814
PACKAGING GROUP : PGII

EPA REPORTABLE QUANTITY

: 1000 LBS: (as Potassium Hydroxide 100%)

(RQ)

MARINE POLLUTANT : Not Listed EMERGENCY RESPONSE GUIDE : ERG-154

SECTION 15 – REGULATORY INFORMATION

U.N. GHS CLASSIFICATION & LABELING INFORMATION: See Section 2 for GHS Hazard Information

U.S. FEDERAL REGULATORY INFORMATION:

LISTED CARCINOGEN : Not listed.

TSCA STATUS: The ingredients of this product are listed in TSCA inventory (40CFR 710.)

SARA SECTION 302 : No chemicals in this material are subject to the reporting requirements of SARA Title

III, Section 302.

SARA SECTION 312 : Chronic health hazard

SARA SECTION 313 : This material does not contain any chemical components with known CAS numbers

that exceed the threshold (De Minimis) reporting levels established by SARA Title III,

Section 313.

NFPA HEALTH : 2 NFPA FLAMMABILITY : 0 NFPA REACTIVITY : 0

EUROPEAN UNION REGULATORY INFORMATION:

EC CLASSIFICATION : C: Corrosive, Xn: Harmful DSD/DPD RISK (R) PHRASES : R22: Harmful is swallowed.

R36/38: Irritating to eyes and skin.

DSD/DPD SAFETY (S) PHRASES : S1/2: Keep locked up and out of reach of children.

S24/25: Avoid contact with eyes and skin.

S26: In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S36/S37/39: Wear suitable protective clothing, gloves, and

eye/face protection.

S45: In case of accidents or if you feel unwell, seek medical

advice immediately. Show label where possible.

S61: Avoid release to the environment. S62: If swallowed, do not induce vomiting.

S64: If swallowed, rinse mouth with water if victim is

conscious.

DSD/DPD HAZARD SYMBOL : C: Corrosive, Xn: Harmful

CANADIAN REGULATORY INFORMATION:

WHMIS CATEGORY : E: Corrosive. D2B: Materials that cause other toxic effects

(TOXIC). Listed

DOMESTIC SUBSTANCES LIST

(DSL)

INGREDIENT DISCLOSURE LIST : Listed

SECTION 16 – OTHER INFORMATION

DISCLAIMER : The information contained herein has been compiled from sources believed to be

realiable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Hydramaster Corp. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and

recommendations in the specific context of their intended use.

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act.

EINECS : European Inventory of Existing Commercial Chemical Substances

IMDG
 International Maritime Code for Dangerous Goods
 IARC
 International Agency for Research on Cancer
 IATA
 International Air Transportation Association

ACGIH : American Conference of Governmental Industrial Hygienists

NFPA : National Fire Protection Association (USA)

NTP : National Toxicology Program

SARA : Superfund Amendments and Reauthorization Act

TSCA : Toxic Substances Control Act

HMIS : Hazardous Materials Identification System (USA)





WHMIS : Workplace Hazardous Materials Information System

LC50 : Lethal concentration, 50 percent

LD50 : Lethal dose, 50 percent

STOT : Systemic Target Organ Toxicity

DATE PREPARED : MAR 1, 2018 **DATE REVISED** : NOV 7, 2022