

# UPGRADE your Carpet Extractor's performance with the new AQUATEC 170 & 220 psi pumps.

**IMPROVE CLEANING RESULTS AND JOB EFFICIENCY WHEN YOU REPLACE YOUR OLD 60 & 100 PSI PUMPS. FEATURES:**

- **SELF PRIMING & CAPABLE OF BEING RUN DRY.**
- PATENTED TRIPLE BYPASS DESIGN. 3/8" FPT PORTS.
- HIGHER OPERATING TEMPERATURE OF 170 DEG F MAX
- 3 CHAMBER NYLON HOUSING, VITON VALVES, SANTOPRENE DIAPHRAGM. PM NON-VENTILATED TOTALLY ENCLOSED DC MOTOR. AVAILABLE IN 230 VOLT MODELS WITH RFI/EMI FILTER.
- **MODEL 58-FLC-170** 170 PSI PRESSURE SWITCH. 1.5 A @ 150 PSI . **MODEL 58-FLC-220** 220 PSI PRESSURE SWITCH. 1.6 AMPS @ 200 PSI.

**PROUDLY MADE IN THE USA**



## **TECHNICAL NOTES:**

Use a 500 psi + hose for the internal plumbing and the external solution hose assembly if the 220 psi pump model is used. The pressure regulator is not required when replacing a PUMPTEC unit. Picture shown on the left shows the size comparison of the comparable PUMPTEC 114T series, SHURFLO 8030-863-239 (150 psi) and the AQUATEC 220 psi pump models.



**DISTRIBUTED BY:**

**Steam-Brite.com**