

忍者战士 Ninja Warrior

Reimagined
Redesigned
Reintroduced

After a long and thorough process of research and development that entailed trips across the United States, focus groups and rigorous in-field testing; Century 400 proudly re-introduces the Ninja series!

FASTER DRYING TIMES!

The Ninja Warrior uses a parallel vacuum motor system which delivers a 25% greater solution recovery rate than series vacuum motor systems.



Maintenance is easier than ever providing an open access to all components delivering the ability to easily maintain, clean and care for your Ninja Warrior after jobs.



Several models are available, including 150, 200 and 500 PSI pumps, dual 2-stage or 3-stage vacuum motors and optional internal heaters, (see opposite side).

CENTURY
400

忍者戰士 Ninja Warrior

CENTURY 400™

All controls and connections have moved up and are now located on the upper center panel for easy access and operation.



The onboard carrying system provides storage for your wand, double cord wrap stow, 5 gallon bucket, hose, and a quart of pre-spray.

Capacity is improved to 13 gallons, with an 11 gallon recovery tank, allowing you to work 16% longer without downtime!



Integrated handle and upper rear casters assist with loading and unloading.



500 PSI 2-Stage with Heat 1.007-068.0

Pump.....	500 PSI
Heat.....	1850W
Motor.....	Dual 2-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

500 PSI 2-Stage 1.007-062.0

Pump.....	500 PSI
Motor.....	Dual 2-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

200 PSI 3-Stage 1.007-067.0

Pump.....	200 PSI
Motor.....	Dual 3-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

150 PSI 2-Stage with Heat 1.007-064.0

Pump.....	150 PSI
Heat.....	1850W
Motor.....	Dual 2-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

500 PSI 3-Stage 1.007-069.0

Pump.....	500 PSI
Motor.....	Dual 3-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

200 PSI 2-Stage with Heat 1.007-066.0

Pump.....	200 PSI
Heat.....	1850W
Motor.....	Dual 2-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

200 PSI 2-Stage 1.007-065.0

Pump.....	200 PSI
Motor.....	Dual 2-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"

150 PSI 2-Stage 1.007-063.0

Pump.....	150 PSI
1.007-063.0 Motor.....	Dual 2-Stage Vacuum Motors
Housing.....	Roto-mold Polyethylene (10 yr. warranty)
Dimensions.....	30-1/2" x 22" x 43-1/4"