



Husqvarna LT 6005

LT 6005 is a well-balanced and powerful rammer, developed for efficient compaction of granular and cohesive soils such as clay and silt. Ideal for compaction in trenches or other narrow spaces, for example around pillars and pipes. Equipped with the latest Honda GXR120 engine, which is especially designed for rammers. The rammer offers superb control, low noise and low emissions.



Easy to maneuver

The three-position throttle control (idle, full speed, stop/closed) also closes the fuel line to prevent leakage. The balanced design provides excellent traction and maneuverability.



Great ergonomics

The single lifting point and rollers on the steering bow make on-site handling easy. Transport wheel kit available as an accessory.

High compaction performance

Efficient compaction thanks to a powerful Honda engine mounted in a compact, durable chassis delivering high speed and high impact force.



Easy to service

Easy access to all service points including oil level checking (engine and foot), air filter cleaning/replacing. Equipped with hour meter, air filter indicator and oil warning indicator.



FEATURES

- High compaction performance
 - Great ergonomics
 - Easy to maneuver
- Easy to service
 - Easy to service

| Technical Specifications | |
|---------------------------------------|---------------------|
| ENGINE | |
| Motor/engine model | 4-stroke air-cooled |
| Exhaust emissions (CO2 EU V) | 674 g/kWh |
| Power/fuel type | Petrol |
| SPECIFICATIONS | |
| Speed forward max | 0 mph |
| Speed | 16.5 m/min |
| DIMENSIONS | |
| Plate width | 280 mm |
| Weight | 151 lbs |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 106 dB(A) |
| Sound pressure level at operators ear | 92 dB(A) |
| PACKAGING | |
| Packaging length | 1100 mm |
| Packaging width | 450 mm |
| Packaging height | 970 mm |
| Packaging volume | 480 dm³ |