



Husqvarna LT 5005

LT 5005 is a well-balanced and lightweight yet powerful rammer, developed for efficient compaction of granular and cohesive soils such as clay and silt. Ideal for compaction in trenches or other narrow spaces, for example around pillars and pipes. Equipped with the latest Honda GXR120 engine, which is especially designed for rammers. The rammer offers superb control, low noise and low emissions.



Easy to maneuver

The three-position throttle control (idle, full speed, stop/closed) also closes the fuel line to prevent leakage. The balanced design provides excellent traction and maneuverability.



Great ergonomics

The single lifting point and rollers on the steering bow make on-site handling easy. Transport wheel kit available as an accessory.

High compaction performance

Efficient compaction thanks to a powerful Honda engine mounted in a compact, durable chassis delivering high speed and high impact force.



Easy to service

Easy access to all service points including oil level checking (engine and foot), air filter cleaning/replacing. Equipped with hour meter, air filter indicator and oil warning indicator.



FEATURES

- High compaction performance
- Great ergonomics
- Easy to maneuver
- Easy to service

Technical Specifications

ENGINE

Motor/engine model	GX120
Exhaust emissions (CO2 EU V)	976 g/kWh
Power/fuel type	Petrol

SPECIFICATIONS

Speed forward max	0 mph
Speed	16.5 m/min

DIMENSIONS

Plate width	230 mm
Weight	134 lbs

SOUND AND NOISE

Sound power level, guaranteed (LWA)	106 dB(A)
Sound pressure level at operators ear	92 dB(A)

PACKAGING

Packaging length	1100 mm
Packaging width	450 mm
Packaging height	970 mm
Packaging volume	480 dm ³