

# Husqvarna LG 204

LG 204 is a compact, lightweight yet powerful reversible plate compactor developed for smaller jobs, such as driveways and pathways, private house projects and narrow trenches. It is the ideal machine to use when macadam beds are thinner and you need nimble, responsive handling. The Honda GX200 petrol engine reduces fuel consumption and emissions, while quality components reduce vibrations. It is equipped with a durable Hardox 400-steel bottom plate.



### Easy operation

The forward/reverse lever and fixed handle grip make handling easy on all surfaces. You don't have to push/pull constantly during operation.



## Strong protection, easy transportation

The heavy-duty steel frame protects the engine and transmission. The frame is also equipped with a lifting eye for easy transportation.



The plates are made from the extremely durable and wear-resistant Hardox 400 steel. The special design keeps rocks from getting stuck between the plate and frame.



#### Low handle vibration levels

Great engineering and quality components minimise handle vibration levels and strain, therefore contributing to a safer, more productive and enjoyable workday.



### **FEATURES**

- Plates made to last
- Strong protection, easy transportation

- Easy operation
- Low handle vibration levels

| ENGINE                                |                     |
|---------------------------------------|---------------------|
| Motor/engine model                    | GX200               |
| Power output                          | 5.8 hp              |
| Exhaust emissions (CO2 EU V)          | 757 g/kWh           |
| Power/fuel type                       | Petrol              |
| SPECIFICATIONS                        |                     |
| Speed forward max                     | 0.86 mph            |
| Speed                                 | 23 m/min            |
| Starter                               | Recoil              |
| DIMENSIONS                            |                     |
| Plate width                           | 500 mm              |
| Weight                                | 465 lbs             |
| SOUND AND NOISE                       |                     |
| Sound power level, guaranteed (LWA)   | 106 dB(A)           |
| Sound pressure level at operators ear | 84 dB(A)            |
| PACKAGING                             |                     |
| Packaging length                      | 600 mm              |
| Packaging width                       | 800 mm              |
| Packaging height                      | 1430 mm             |
| Packaging volume                      | 686 dm <sup>3</sup> |