

# SAFETY DATA SHEET

Issuing date 08-May-2015 Revision Date 08-May-2015 Version 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### **Product identifier**

Product Label Name Hydro-Force - Viper Venom

Other means of identification

UPC Code(s) Not applicable Product code CR22

Product code CR22
UN/ID No UN3266
Synonyms None

# Recommended use of the chemical and restrictions on use

**Recommended Use** Specialty cleaner. Tile and grout cleaner.

Uses advised against Follow label instructions. Not recommended for any use except intended use.

# Supplier's details

Supplier Address Manufacturer Address

Hydro-Force Hydro-Force

4282 South 590 West
Salt Lake City, UT 84123
Salt Lake City, UT 84123
Salt Lake City, UT 84123

USA USA

#### **Emergency telephone number**

Company Phone Number 1-801-268-2673

**Company Emergency Phone**United States: 1-800-535-5053 (INFOTRAC – 24 hours, 7 days a week)

Number

United States: 1-800-535-5053 (INFOTRAC – 24 hours, 7 days a week)

International: 1-352-323-3500 (INFOTRAC – 24 hours, 7 days a week)

Emergency telephone Poison Control 1-800-222-1222 (24 hour)

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Gases)	Category 4
Skin corrosion/irritation	Category 1C
Serious eye damage/eye irritation	Category 1C

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

# Danger

# **Hazard Statements**

Harmful if inhaled

Causes severe skin burns and eye damage



Appearance Clear Liquid Physical state liquid Odor No information available

# **Precautionary Statements - Prevention**

Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection

# **Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor/physician

Call a POISON CENTER or doctor/physician if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

# **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

#### Other information

- May be harmful in contact with skin
- May cause respiratory irritation General Hazards

Keep out of reach of children

Please see Section 11. Toxicological Information for further information

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade Secret
Butoxyethanol	111-76-2	1 - 5	*
Diethylene glycol monobutyl ether	112-34-5	1 - 5	*
Sodium Hydroxide	1310-73-2	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

# 4. FIRST AID MEASURES

# First aid measures for different exposure routes

**General advice** Immediate medical attention is required.

Eye contact Immediate medical attention is required. Rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected

area.

Skin contact If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water

while removing all contaminated clothes and shoes.

**Toxic - Inhalation** Move to fresh air. Call a physician or Poison Control Center immediately. If not breathing,

give artificial respiration. If breathing is difficult, give oxygen.

**Immediate medical attention is required.** Do NOT induce vomiting. Drink plenty of water.

Never give anything by mouth to an unconscious person. Remove from exposure, lie down. Clean mouth with water and drink afterwards plenty of water. Call a physician or Poison

Control Center immediately.

**Protection of First-aiders**Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms/effects, acute and delayed

Main Symptoms No information available.

Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

# Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

**Hazardous Combustion** 

No information available.

**Products** 

**Explosion Data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment. Avoid contact with

skin, eyes and clothing. Keep people away from and upwind of spill/leak.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**Advice for emergency responders** For personal protection see section 8.

Environmental precautions

**Environmental precautions** 

Do not allow material to contaminate ground water system. Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

# Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains. Dam up. After cleaning, flush away traces

with water.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Handle product only in closed system or provide appropriate exhaust ventilation at

machinery.

#### Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep out of the reach of children. Keep containers tightly closed in a dry, cool and

well-ventilated place. Keep in properly labeled containers.

Packaging material Keep product in packaging product is initially sold in.

Incompatible products Incompatible with strong acids and bases. Incompatible with oxidizing agents.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm inhalable fraction and vapor		
Sodium Hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> (vacated) Ceiling: 2 mg/m <sup>3</sup>	IDLH: 10 mg/m³ Ceiling: 2 mg/m³

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

**Engineering Measures** Showers

> Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Tightly fitting safety goggles. Face-shield.

Skin and body protection Protective gloves

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene measures Remove and wash contaminated clothing before re-use. When using, do not eat, drink or

smoke. Keep away from food, drink and animal feeding stuffs. Contaminated work clothing should not be allowed out of the workplace. Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. For environmental protection, remove and wash all contaminated protective equipment before re-use. Wear suitable gloves

125

and eye/face protection.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# **Physical and chemical properties**

Physical state liquid

Appearance Clear Liquid Odor Characteristic

Color No information available Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH 12.5

Melting pointNo information availableBoiling point/boiling rangeNo information available

Flash Point No information available Evaporation rate No information available

Flammability (solid, gas) No information available

Flammability Limits in Air

Upper Flammability LimitNo information availableLower Flammability LimitNo information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 1.015

Water solubility Soluble in water

Solubility in other solvents
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature
No information available
No information available
No information available

Viscosity, kinematic 200 cps

Viscosity, dynamicNo information availableExplosive propertiesNo information availableOxidizing PropertiesNo information available

# Other information

Softening pointNo information availableMolecular weightNo information availableVOC Content(%)No information available

Density VALUE 1.015

Bulk Density VALUE No information available

# 10. STABILITY AND REACTIVITY

# Reactivity

#### **Chemical stability**

Stable under recommended storage conditions.

# Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization None under normal processing.

#### **Conditions to Avoid**

Exposure to air or moisture over prolonged periods.

# **Incompatible Materials**

Incompatible with strong acids and bases. Incompatible with oxidizing agents.

# **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

#### **Product Information**

**Toxic - Inhalation** Harmful by inhalation. Toxic by inhalation. Avoid breathing vapors or mists. May cause

irritation of respiratory tract.

**Eye contact** Avoid contact with eyes. May cause burns.

**Skin contact** Avoid contact with skin. May cause burns.

**Ingestion** Do not taste or swallow. Ingestion may cause irritation to mucous membranes. Ingestion

causes burns of the upper digestive and respiratory tracts.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )	= 220 mg/kg ( Rabbit )	= 450 ppm (Rat) 4 h
Diethylene glycol monobutyl ether 112-34-5	= 3384 mg/kg (Rat)	= 2700 mg/kg ( Rabbit )	
Sodium Hydroxide 1310-73-2		= 1350 mg/kg ( Rabbit )	

# Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.Eye damage/irritationNo information available.SensitizationNo information available.Germ Cell MutagenicityNo information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Butoxyethanol 111-76-2	A3	Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity

Developmental Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.
No information available.

Chronic toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure.

Possible risks of irreversible effects. May cause adverse liver effects.

Target Organ Effects Blood, Central nervous system, Eyes, Hematopoietic System, Kidney, Liver, Respiratory

system, Skin.

**Aspiration hazard** No information available.

# Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document.

 ATEmix (oral)
 7393 mg/kg

 ATEmix (dermal)
 3852 mg/kg

 ATEmix (inhalation-gas)
 14143 mg/l

 ATEmix (inhalation-dust/mist)
 30.3 mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Butoxyethanol		1490: 96 h Lepomis macrochirus	1000: 48 h Daphnia magna mg/L
111-76-2		mg/L LC50 static 2950: 96 h	ÉC50
		Lepomis macrochirus mg/L LC50	
Diethylene glycol monobutyl ether	100: 96 h Desmodesmus	1300: 96 h Lepomis macrochirus	100: 48 h Daphnia magna mg/L
112-34-5	subspicatus mg/L EC50	mg/L LC50 static	EC50
Sodium Hydroxide		45.4: 96 h Oncorhynchus mykiss	
1310-73-2		mg/L LC50 static	

# Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Butoxyethanol	0.81
111-76-2	

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

**Contaminated packaging** Do not re-use empty containers.

US EPA Waste Number D002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
Sodium Hydroxide	Toxic	
1310-73-2	Corrosive	

4.4	TDA	LCDO	DTI	LICOD	84 A T	101
14.	IKAI	NOPU	וו אי	NFOR	IVIAI	ION

.

DOT

UN/ID No UN3266

Proper shipping name Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide)

Hazard class 8
Packing Group III

Reportable Quantity (RQ) Sodium hydroxide: RQ lb.= 1000

154

Special Provisions IB3, T7, TP1, TP28

**Emergency Response Guide** 

Number

Quantity Limits Inner packaging not over 5.0 L (1.3 gallons) net capacity each for liquids

**IMDG - Maritime Transportation** 

UN/ID No UN3266

Proper shipping name Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide)

Hazard class 8
Packing Group III
EmS No. F-A, S-B

Special Provisions Check regulations for limited quantity exceptions

IATA - Air Transportation

UN/ID No

Proper shipping name

Hazard class Packing Group Special Provisions

# 15. REGULATORY INFORMATION

Do not ship by air unless within allowed limits

International Inventories

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Butoxyethanol - 111-76-2	1.0
Diethylene glycol monobutyl ether - 112-34-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard
Chronic Health Hazard
Yes
Fire Hazard
No
Sudden Release of Pressure Hazard
No
Reactive Hazard
No

# Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
---------------	--------------------------------	------------------------	---------------------------	-------------------------------

Sodium Hydroxide	1000 lb		X
1310-73-2	. 8 6 8 12		

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Sodium Hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

# **US State Regulations**

# **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butoxyethanol 111-76-2	Х	Х	Х
Diethylene glycol monobutyl ether 112-34-5	Х		Х
Sodium Hydroxide 1310-73-2	X	Х	X
Sodium Sulfate 7757-82-6		Х	Х

#### U.S. EPA Label information

**EPA Pesticide Registration Number** Not applicable

# **16. OTHER INFORMATION**

NFPAHealth hazard3Flammability1Instability0Physical and chemical hazards -HMISHealth hazard3Flammability1Physical Hazard0Personal protectionX

Prepared By Hydro-Force

Environmental Health & Safety

Revision Date

08-May-2015

**Revision Note** 

No information available

#### Disclaimer

The (M)SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Bridgewater LLC to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Bridgewater LLC assumes no responsibility for injury to the recipient of third persons, or for any damage to any property resulting from misuse of the product.

**End of Material Safety Data Sheet**