

# Foster FK2BH2B: 1/4in Male and Female Brass Quick Disconnect QD

**Buy More, Save More**

## Description

FHK, TWO WAY SHUT-OFF

Both socket and plug are sealed at disconnect.

Standard industrial interchange design, most widely used in industry.

Within each series, only sockets and plugs of the same size will couple together. Conforms with ISO 7241-1, Series B.

Manual - Socket sleeve must be manually retracted to connect and disconnect.

Standard seals are Buna-N.

Rated pressures as defined by ANSI/B93.2-1986, based on 4:1 safety factor and non-shock service.

## Specification

- QTY: 1 Set, 2 PC
- Material: Brass
- Interchange: ISO 7241-1, Series B
- Type: FHK, Two Way Shut off
- Country/Region of Manufacture: United States
- MPN: H2B - K2B (1 Set)
- Body Type: 1/4" Valve
- Thread Type: 1/4" Female NPT, FPT

## Includes



Foster FK2B Bretco 1/4in Male Brass Quick Disconnect QD Nipple Plug Coupler  
ONE



**Foster QD 1/4in Female Brass Quick Disconnect Mytee B102 25-001 FH2B 8.697-350.0 Socket Coupler ONE**

## Set-Up

- ONEWAY SHUT-OFF: Suffix VA to either socket or plug catalog number for valve actuator.
- STRAIGHT-THRU: Suffix LV to both socket and plug catalog number for less valve.
- BL: Locks against accidental disconnect.To connect, align ball with slot. After connection, rotate sleeve to lock.To disconnect, realign ball with slot and retract sleeve.



## Optional



Optional

1/4in Stainless Steel In Line Ball Bearing Live Hose and Wand Swivel MXF 3500 Psi [8.712-457.0] 421034 (makes your work easier)

Mounts on wand or mounts on the end of your solution hose.

E20190702JMG