
Parts & Accessories > Pumps (Water Pumps) > Pumptec > Pumptec Pump & Motor Assbly > Pumptec 81813 Sodium Hypochlorite XPVC-6/M81 with 150PSI PVC Regulator Soft Wash Pump 120/230 Volts GTIN: 10679065070043

Pumptec 81813 Sodium Hypochlorite XPVC-6/M81 with 150PSI PVC Regulator Soft Wash Pump 120/230 Volts GTIN: 10679065070043



Model Number: 81813

Pumptec 81813 Sodium Hypochlorite XPVC-6/M81 with 150PSI PVC Regulator Soft Wash Pump 120/230 Volts GTIN: 10679065070043

Manufacturer: Pumptec

Pumptec 81813 Sodium Hypochlorite XPVC-6/M81 with 150PSI PVC Regulator Soft Wash Pump 120/230 Volts

Soft Wash X6PVC Pump System
The Pumptec X series pumps engineered for use with Sodium Hypochlorite commonly used in the soft wash industry. The XPVC/M960 high performance pump is a perfect equipment for professionals who are interested in owning a peak performance electric pump designed for high performance and long life in the soft wash industry. The Pumptec XPVC high flow pump features solid ceramic 4 plunger design and dual PTFE seals. The X6 provides the pressure and high flow you need for the most demanding Soft Wash jobs. This state of the art Pumptec pump is designed with Viton seals, Hastelloy Valves, ceramic plungers and a PVC/CPVC body. The XPVC machined PVC body and alloy C-276 valves for insure maximum chemical compatibility and dependability. This is critical for for use with Sodium Hypochlorite.
The pumps 150 PSI at 6.7 GPM performance allows for an even spray at great distances, 38’ vertical and 55” horizontal spray. Pumptec succeeded in building the X6PVC to eliminate the short life span that many Softwash pumps experience. If you are serious about having the best equipment for the soft wash industry, it’s time to invest in the best pump on the market. The Pumptec XPVC-6.
Like all Pumptec pumps, you can look forward to a long and problem-free life.
One High Performance X6PVC 12 Volt Sodium Hypochlorite soft wash pump

- Max flow 6.7 GPM
- Max Pressure 150 PSI-capable of spraying 38’ vertical spray and 55’ horizontal spray
- Liquid temperature 140 degrees F
- Delivery type-bypass system
- Priming capability 12 feet
- Inlet/outlet ports ½” NPT
- Weight 50 LBS
- Seal material-Viton
- Valve material-Hastelloy
- Plunger material-Ceramic
- Pump body material-PVC/CPVC

Parts & Accessories > Pumps (Water Pumps) > Pumptec > Pumptec Pump & Motor Assbly > Pumptec 81813 Sodium Hypochlorite XPVC-6/M81 with 150PSI PVC Regulator Soft Wash Pump 120/230 Volts GTIN: 10679065070043

Pumptec 81813 Sodium Hypochlorite XPVC-6/M81 with 150PSI PVC Regulator Soft Wash Pump 120/230 Volts GTIN: 10679065070043

50 PSI Regulator material-PVC
One 1/2MPT x ½ poly hose barb
One 1/2MPT x 1/MPT poly nipple for regulator
One elbow 90 degree 1/2MPT x ½ barb
Factory installed
Pumptec M81, Motor Only, Marathon, 9 amps 120 volts 4.5 amps 120/ 230 volts 48 Frame, GTIN 10679065072146

Availability: This product was added to our catalog on Monday 24 June, 2024

Steambrite Supply