

Auto Detailing & Car Wash: > Car Wash Supplies: Rotor Arms & More > Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment



Model Number: 20180720

Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Manufacturer: Clean Storm

Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Description

Clean Storm 20180720 20.5-inch stainless steel undercarriage pressure washing attachment delivers high-pressure cleaning up to 4000 PSI at 250°F. Engineered with a 17-inch dual-nozzle spray bar, heavy-duty casters, and a 3/8-inch ID hose, it effortlessly removes road grime, salt, mud, and debris from vehicles, trucks, and equipment.

Features

- Heavy-duty stainless steel construction provides exceptional corrosion resistance and long-lasting durability in harsh automotive environments.
- Features a 20.5-inch circular cleaning deck equipped with a 17-inch dual-nozzle spray bar utilizing zero-degree spray patterns for maximum cleaning power.
- Integrated 3/8-inch inner diameter high-pressure hose rated for up to 4000 PSI operating pressure and a maximum temperature of 250°F.
- Smooth-rolling caster wheel setup with an 18-inch wheel width and a 47-inch total length from front caster to rear wheels for effortless maneuverability.
- Low-profile 6-3/4-inch height designed to easily clear standard passenger vehicles, trucks, SUVs, and commercial equipment.

Applications

- Automotive undercarriage cleaning for cars, trucks, SUVs, and commercial fleet vehicles.
- Pressure washing systems and professional truckmount carpet cleaning setups capable of handling high-pressure output.
- Industrial maintenance yards, heavy equipment wash bays, and agricultural machinery sanitation.
- Removal of stubborn road salt, mud, oil, grease, and winter de-icing chemicals from vehicle frames.

Specifications

Brand
Clean Storm

Auto Detailing & Car Wash: > Car Wash Supplies: Rotor Arms & More > Clean Storm 20180720,
20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Model / Part Number
20180720

Primary Material
Stainless Steel

Deck Diameter
20.5 Inches

Spray Bar Length
17 Inches

Nozzle Configuration
2 Nozzles with Zero-Degree Spray Pattern

Unit Height
6-3/4 Inches

Total Length
47 Inches (Front Caster to Rear Wheels)

Wheel Width
18 Inches

Hose Specification
3/8 Inch ID High-Pressure Hose

Maximum Pressure Rating
4000 PSI

Maximum Operating Temperature
250°F

Shipping Dimensions
47" x 23" x 11"

Auto Detailing & Car Wash: > Car Wash Supplies: Rotor Arms & More > Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Shipping Weight
33 lbs.

Video

Pictures

Cross-Reference SKUs

Clean Storm 20180720

CS-20180720

Clean Storm Undercarriage Cleaner 20.5"

20180720 Undercarriage Pressure Washer

CS20180720

Tips and Additional Information

Ensure all threaded connections are properly sealed using rated thread sealant tape (PTFE) to prevent high-pressure leaks during operation. Always inspect the 3/8-inch ID hose, swivel joints, and nozzle tips for debris or wear before each use to maintain optimal spray performance and prevent clogging. Maintain proper alignment and

Auto Detailing & Car Wash: > Car Wash Supplies: Rotor Arms & More > Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

Clean Storm 20180720, 20.5-Inch Stainless Steel Automotive Undercarriage Pressure Washing Attachment

stable movement across the undercarriage surface to achieve uniform cleaning results. Verify that your pressure washer pump does not exceed the maximum rating of 4000 PSI and 250°F to prevent premature wear on internal seals and components.

Frequently Asked Questions

Q: What is the maximum pressure rating for this undercarriage cleaner?

A: The attachment is rated for a maximum operating pressure of up to 4000 PSI and can withstand temperatures up to 250°F.

Q: What type of spray pattern do the nozzles use?

A: It features two nozzles configured with a zero-degree spray pattern mounted on a 17-inch rotating or fixed spray bar inside the 20.5-inch deck.

Q: Will this fit under low-profile vehicles?

A: Yes, the unit has a low-profile height of 6-3/4 inches, allowing it to easily glide beneath most cars, trucks, and SUVs.

Q: What are the total dimensions and shipping weight?

A: The unit is 47 inches long from the front caster to the rear wheels with an 18-inch wheel width. The shipping box measures 47" x 23" x 11" and weighs 33 lbs.

Warranty & Safety Information

Manufacturer warranty covers defects in materials and workmanship under normal operating conditions when used within specified parameters. Warranty is strictly voided if the unit is operated above its maximum pressure rating of 4000 PSI or maximum temperature rating of 250°F. Damage resulting from improper chemical usage, frozen water expansion, lack of pre-installation filtration, or physical impact from obstacles during operation is not covered. Always wear appropriate personal protective equipment (PPE), maintain a secure stance, and ensure the pressure washer system is depressurized before performing maintenance, disconnecting lines, or inspecting nozzles.

Availability: This product was added to our catalog on Tuesday 23 July, 2024