

>



Model Number: HD20004E2G

Hydro Tek HD20004E2G, HD Series Electric/Diesel Hot Pressure Washer, 2000 PSI 3.8 GPM, Belt Drive General Pump Triplex Plunger Pump, 230V, 1PH, 5HP, 30A

Manufacturer: Hydrotek

Hydro Tek HD20004E2G, HD Series Electric/Diesel Hot Pressure Washer, 2000 PSI 3.8 GPM, Belt Drive General Pump Triplex Plunger Pump, 230V, 1PH, 5HP, 30A
Description

The HD Series offers rugged, dependable, affordable washing. It features a heavy-duty stainless steel frame, handles, panels and coil protection & offering superior corrosion resistance, as well as four pneumatic wheels. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full Steam Settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives, which can be delivered at full pressure & for optimal cleaning effectiveness. High efficiency coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever sanitizing and degreasing are needed.

Features

- Efficient Heating: Schedule 80 coil is stainless steel wrapped and insulated to make efficient use of the burner heat.
- Flexible, Effective Cleaning: Adjustable temperature with steam setting and soap/chemical injection delivers more cleaning power over a wide range of applications.
- Compact and Portable: Wheels included. Easily moved to wherever you need to clean
- Inlet Chemical Injection
- Belt Driven Pump
- Bypass Cool System
- SpiraLast® Coil
- High-Intensity Diesel Burners & Efficient Heating System
- 8-Gallon Fuel Tank with Filtration
- Adjustable Temperature
- Fuel Tank with Filtration

Specification

PRESSURE: 2000psi

>

FLOW CAPACITY: 3.8gpm
 OUTLET TEMP: Adj. to 250°F (130°F Rise)
 POWER/ENGINE: 5.0 HP
 VOLTS/PHASE/AMPS: Dual rated for 208v or 230v - 1ph, 24a
 POWER CORD: 35' cord with Ground Fault Circuit Interrupter for additional safety
 CONTROLS/SWITCHES: Lighted rocker switches, panel mounted soap control, adjustable thermostat
 PUMP: General Pump, Forged brass manifold, Triplex Ceramic Plunger
 POWER DRIVE: V-Belt Drive with EZ Align™; pump rail, Low RPM – Cooler, Quieter
 PRESSURE CONTROL: Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc, By-Pass-Cool System
 WATER SUPPLY: 4 Gal Float Tank, Double Inlet Filtration
 PRESSURE HOSE: 3/8" x 50' Steel Wire Braid Hose, 3000 PSI, 250°F Rated
 GUN / WAND: Insulated Shut Off Gun / 36" Wand w/Nozzle Quick Connector
 SOAP INJECTION: Inlet soap/chemical injection, Injects Soap At Full Pressure
 NOZZLE: #5.0(15°, 40°) #4.0(25°)
 BURNER COIL: Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
 BURNER/POWER: Beckett Oil Fired, Automatic Ignition, Forced Draft, Fuel Filter w/ Water Separator
 BURNER FUEL / CAP: Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity – 392,000 Btu input
 CONSTRUCTION: All Stainless: frame, panels, coil wrap, and double wall coil end caps
 WHEELS: 4) wheels installed
 NET WEIGHT / DIMS: 381# 47x29x36

\$6,037.00

<https://3rpressurewashers.com/products/2000-psi-3-8-gpm-hot-water-pressure-washer-hydhd20004e2g/> -->

Availability: This product was added to our catalog on Friday 27 September, 2024