# Husqvarna 970471805, FS 4600 G Floor Saw, 48hp 30in Kubota 3 Speed, GTIN 805544581950



Model Number: 970471805

Husqvarna 970471805, FS 4600 G Floor Saw, 48hp 30in Kubota 3 Speed, GTIN 805544581950

Manufacturer: Husqvarna Equipment

Husqvarna 970471805, FS 4600 G Floor Saw, 48hp 30in Kubota 3 Speed, GTIN 805544581950
Description
This rear pivot saw is easy to manoeuver when making multiple direction changes on the job. The 3-speed gearbox makes the saw more efficient by enabling different diameter blades to operate at their ideal performance level.

Features

- The power transmission system with right-angle gearbox transmits high power to the blade shaft with optimum torque and minimized vibrations.
- Well-balanced design with a low profile gives you high visibility and makes it easy to handle and transport.
- Intuitive and ergonomic control panel
- Helps maintain traction and gives comfortable operation.
- Provides good visibility when cutting and can be folded for transport.
- Low maintenance
- Adjustable handlebars, intuitive control layout, easy manoeuvrability and low vibrations facilitate operation and reduce user-fatigue.

Specification
ENGINE
Engine specification Kubota WG1605
Engine Power (As rated by the engine manufacturer) 49.6 hp
Engine cooling Water
Power source Gas (Petrol)
Fuel tank volume 828.4 fl oz
Cylinders 4
Number of strokes 4-stroke engine
Exhaust emissions (COâ„, EU V) 1090 g/kWh

CUTTING EQUIPMENT
Arbor diameter 1"
Blade depth control Electric hydraulic
Blade diameter, max 30 in
Cutting depth, max 12.5 in
Blade flanges 5 in

TRANSMISSION
Number of gearbox speeds 3
Transmission speed (forward/reverse) 0-196 fpm

*Construction Equipment > Concrete Saws Cutters > Husqvarna 970471805, FS 4600 G Floor Saw, 48hp 30in Kubota 3 Speed, GTIN 805544581950*

# Husqvarna 970471805, FS 4600 G Floor Saw, 48hp 30in Kubota 3 Speed, GTIN 805544581950

Output shaft RPM, speed 1 | optimal blade size 1,866 rpm | 26 in (660 mm)
Output shaft RPM, speed 2 | optimal blade size 2,400 rpm | 20 in (508 mm)
Output shaft RPM, speed 3 | optimal blade size 3,200 rpm | 14 in (356 mm)
Transmission type Hydrostatic Drive

DIMENSIONS
Product size length 66 in (1,675 mm)
Product size width 33.6 in (853 mm)
Product size height 50 in (1,270 mm)
Weight 1,235 lbs (560 kg)

*Availability: This product was added to our catalog on Saturday 12 October, 2024*

Steambrite Supply