AR Pump XWL42.15N-SX Pump: 11/2200 1450RPM



Model Number: XWL42.15N-SX

AR Pump XWL42.15N-SX Pump: 11/2200 1450RPM

Manufacturer: Annovi Reverberi Pumps

AR Pump XWL42.15N Pump: 11/2200 1450RPM
Description

The Annovi Reverberi (AR) Plunger Pump XWL42.15N-SX boasts an impressive 1450 RPM, making it optimal for challenging cleaning tasks where efficiency and power are key. This reliable plunger pump is designed for longevity and constant operation, maintaining its performance across a number of industrial, agricultural and commercial applications.
Whether it's high-pressure washing, industrial process applications, or even agricultural irrigation, the XWL42.15N-SX delivers superior performance. It's uniquely suitable for heavy-duty applications, including car wash stations, power wash contractors, and roof cleaning services to name only a few. This resilient equipment will not let you down in demanding conditions.
Features

- Manifold:
- - Forged Brass: Strength and no porosity – long life. Higher hydrostatic pressures – safety, performance.
- - Inlet and Discharge Ports: Heavy bosses for added strength.
- - Offset Discharge Ports: High efficiency, smooth flow.
- - Bolts: Eight bolts, 10mm, grade 8.8.
- Valves:
- - Ultra Form Cages: Durable, strength, and long life.
- - Poppets, Seat and Spring: 303 and 400 series stainless steel.
- - Valve Caps: Forged. Patented Valve Cap Design
- Packing and Plungers:
- - High Pressure Packing: “V” style (D-1) Buna-N (cotton duct weave base) strong and tightens under load.
- - Low Pressure Seals: “U” cup double lip Buna-N for a good positive seat.
- - Support and Guides: Machined brass, 2-piece construction to assure proper plunger alignment and to maximize packing and seal life.
- - Plungers: Are a special aluminum oxide blend, solid ceramic for long life, strong durability and more resilient.
- Bearings: Oversized for maximum life and load disbursement
- Bearing Support: Precision die-cast and machined to assure concentricity and alignment.
- Crankcase: Precision die-cast, large cross head for strength, large cooling fins and anodized (for maximum heat dissipation).
- Rear Cover: Precision die-cast, O-ring sealed and bayonet style sight glass for positive sealing and locking (no threads to loosen).
- Plunger Rods: Stainless steel construction for strength (no plating to scrape off), back-up and O-ring plunger sealing system.

Steambrite Supply

AR Pump XWL42.15N-SX Pump: 11/2200 1450RPM

• Rod Pins: Precision ground and hardened steel, oversized for load disbursement.
• Connecting Rods: Heavy 2-piece special alloy aluminum based, oversized for maximum strength, load disbursement, and life. Heavy pin area construction, for added load strength.
• Crankshaft: Forged, precision ground and hardened for extremely long life and durability.
• Oil Seals and O-rings: All are constructed of Buna-N rubber. The O-rings have stainless steel garder springs to assure constant tension on the sealing surface.
• Oil Capacity: 32 oz.
• Dyno Proven: All pumps are dyno tested to assure the theoretical design meets the actual design.
• Valve Design: Each pump series has a valve design that optimizes its highest efficiency.
• Hot Water: High temperature kits are available to 180ºF. Refer to breakdown.
• Wet End Repair: Very simple no special tools required.
• Design: Using advanced fluid handling design programs. Overall pump efficiency is increased.

Specifications

Brand:
Annovi Reverberi (AR)

Drive Type:
Solid Shaft

Series:
XWL Series

Maximum Flow Rate:
11.09 gpm

Maximum Pressure:
2200 psi

Pump Orientation:

Steambrite Supply

AR Pump XWL42.15N-SX Pump: 11/2200 1450RPM

Left Hand

Maximum Speed:
1450 rpm

Plunger Diameter:
28 mm

Shaft Diameter:
24 mm

Inlet Size:
3/4 in (female)

Outlet Size:
3/8 in (female)

Oil Capacity:
32 oz

Maximum Fluid Temperature:
140 degrees (F)

Manifold Material:
Brass

Crankcase Material:
Aluminum

Weight:
34 lb

Crankcase Stamp ID:
2

Country of Origin:

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Annovi Reverberi Pumps > AR Industrial Triplex Plunger Pumps > XW Series > AR Pump XWL42.15N-SX Pump: 11/2200 1450RPM

AR Pump XWL42.15N-SX Pump: 11/2200 1450RPM

Italy

Availability: This product was added to our catalog on Wednesday 27 November, 2024

Steambrite Supply