

Parts & Accessories > Quick Disconnects And Couplers > Clean Storm 86035RG, Insulated Female Brass Coupler with Molded Rubber Grip, 1/4" QD x 1/4" FIP

Clean Storm 86035RG, Insulated Female Brass Coupler with Molded Rubber Grip, 1/4" QD x 1/4" FIP



Model Number: 86035RG

Clean Storm 86035RG, Insulated Female Brass Coupler with Molded Rubber Grip, 1/4" QD x 1/4" FIP

Manufacturer: Clean Storm

Clean Storm 86035RG, Insulated Female Brass Coupler with Molded Rubber Grip, 1/4" QD x 1/4" FIP

Description

Upgrade your pressure washing setup with the Clean Storm 86035RG Insulated Female Brass Coupler. Designed for durability, safety, and ease of use, this high-pressure quick disconnect coupler features an integrated red molded rubber grip that insulates your hands against extreme temperatures. Whether you are operating with hot water or handling high-vibration applications, the heavy-duty brass construction ensures a corrosion-resistant and leak-free seal.

Featuring a 1/4" female quick-connect socket on one side and a 1/4" Female Iron Pipe (FIP/FPT) thread on the other, this fitting connects wands, spray guns, and pressure washer hoses. The textured rubber sleeve offers non-slip control even when wet or wearing gloves, making accessory changes fast, safe, and efficient.

Features

- Thermal Hand Protection: Integrated insulated molded rubber grip protects operators' hands when using hot water systems.
- Ergonomic Non-Slip Sleeve: Textured rubber outer casing provides a firm grip in wet conditions or while wearing heavy work gloves.
- Durable Brass Construction: High-grade solid brass body resists corrosion, wear, and rust for long-lasting performance.
- High-Pressure Performance: Rated up to 4,000 PSI to withstand demanding commercial and industrial pressure washing tasks.
- Universal Quick Disconnect: Standard 1/4" quick-connect female socket allows effortless attachment and release of compatible plugs.

Specifications

Brand
Clean Storm

Part Number

Parts & Accessories > Quick Disconnects And Couplers > Clean Storm 86035RG, Insulated Female Brass Coupler with Molded Rubber Grip, 1/4" QD x 1/4" FIP

Clean Storm 86035RG, Insulated Female Brass Coupler with Molded Rubber Grip, 1/4" QD x 1/4" FIP

86035RG

Body Material
Solid Brass

Grip Material
Insulated Molded Rubber

Connection Type 1
1/4" Female Quick Disconnect (QD) Coupler

Connection Type 2
1/4" Female Iron Pipe Thread (FIP / FPT / NPT)

Maximum Pressure Rating
4,000 PSI

Maximum Temperature Rating
212°F (100°C)

Flow Rate
10.5 GPM

Application
Pressure Washing, Hot & Cold Water Systems

Availability: This product was added to our catalog on Monday 16 December, 2024